Finite Element Analysis of Lathe Machine Tumbler Gear Mechanism

¹**Prof. Jay P. Joshi,** ²**Prof. Ankit V. Sata,** ^{1, 2,} Assistant Professor

^{1, 2,} Assistant Professor ^{1, 2,} Mechanical Engineering Department ^{1, 2,} V.V.P. Engineering College, Gujarat, India

Abstract : Gear is the special division of Mechanical Engineering concerned with the transmission of power and motion between the rotating shafts. In this study, a lathe machine tumbler gear mechanism used for threading purpose is taken and applied finite element analysis methodology on each metallic spur gears. Main purpose of this study is to compare FEA stresses of metallic spur gears with the AGMA standard stress. Modelling of gears is done in PRO-ENGINEERING and analysis is done using ANSYS workbench v11.

Keywords: Spur Gear, FEM, Bending Stress, AGMA, PRO-ENGINEERING, ANSYS V11.

I. INTRODUCTION

Gears are the most useful and common means of transmitting motion and power in the today modern engineering field. They vary from tiny size used in watches to the large gears used in the lifting devices and speed reducers. Gears are the valuable mechanical element of mechanism such as rolling machinery, metal cutting machinery and automotive machinery. Gears with toothed shape generally used to vary or change speed- power ratio also to change the direction of input and output shaft. Gears are used in pairs and each gear is usually attached to a rotating shaft.[7]

There are different materials used as a gear material. Gear materials are used as per the type of application of power transmission and loading condition. All material are not providing similar properties during working condition due to their different structure and bonding nature. Materials are to be required to check under loading conditions to find their beneficial properties and remove unnecessary properties during the selection of material. When gears are in a loading condition, mainly two types of failure are produced in gear material like as bending failure due to low bending strength of material and pitting or contact failure due to lower strength of contact area of gear teeth. For analysis purpose of spur gears, **Lathe Machine Tumbler Gear Mechanism** is selected for material analysis.

Objectives of the Work

Check comparative stress in conventional metallic material of spur gears using a static finite element method.
Check stress analysis of metallic spur gears of a lathe machine tumbler gear mechanism with AGMA standard stress for specific loading condition.

Tumbler Gear Mechanism





February 2018, Volume 5, Issue 2

There are different materials used as a gear material. Gear materials are used as per the type of application of power transmission and loading condition. All material are not providing similar properties during working condition due to their different structure and bonding nature. Materials are to be required to check under loading conditions to find their beneficial properties and remove unnecessary properties during the selection of material. When gears are in a loading condition, mainly two types of failure are produced in gear material like as bending failure due to low bending strength of material and pitting or contact failure due to lower strength of contact area of gear teeth.

GEAR NAME	NUMBER OF TEETH	OUTSIDE DIA.	P.C.D
А	44	92	88
В	25	54	50
С	25	54	50
D	33	70	66
E	30	64	60
F	100	204	200
G	55	114	110
Н	127	258	254

Table-1:- Gear Parameter

Natraj Brand		
2 HP, 3PH, 1440		
rpm		
Parallel spur gear		
200		
2		
Nodular Cast Iron		

Table-2:- Lathe Machine Specification

There are eight gears in this gear mechanism and minimum speed of first input gear A is 200 rpm that I have measured with digital tachometer.

GEAR NAME	NUMBER OF TEETH	OUTSIDE DIA.	P.C.D
A	44	92	88
B	25	54	50
С	25	54	50
D	33	70	66
E	30	64	60
F	100	204	200
G	55	114	110
Н	127	258	254

Table-3:- Gear Parameter

II Design Calculation Material Data

Table-2.1:-Material Data Material Nodu				Nodular	ar Cast Iron(Ductile)		
Density	Compress	sive	ive Tensile		Young's Modulus		Poisson's
	Ultimate St	rength	ength Ultimate		MPa		Ratio
	MPa		Streng	gth MPa			
7300 kg/m3	840		7	00		35000	0.28
Chemical Composition							
Carbon	Manganese	Sil	icon	Phospho	orous	Sulphur	Magnesium
3.40 - 3.85 %	0.10 - 0.30 %	2.30 -	3.10 %	0.10	%	0.02 %	0.07

Design Input for Gear A

Input Parameters Gear A Power	1492 watt
Pitch circle diameter	88 mm
Module	2 mm
Gear Rpm	200
No. of teeth	44

III FEA Analysis

Bending stress of spur gear teeth is generally calculated by analytically and finite element method. Analytical bending stress is calculated by two formula Lewis formula and AGMA formula. Analytical result is compared with the finite element method result for validation. For above purpose, the solid model of spur gear is imported in a fem software ANSYS as an IGES file. Result of bending stress is obtained after the meshing and boundary condition are applied on the spur gear geometry. Nodes and element generated in meshing of gear are 26518 and 4851 respectively.

February 2018, Volume 5, Issue 2

Von-Mises stress is equal to the tension stress and generally it is main cause of crack in the gear teeth if the applied load is greater than strength of the gear teeth so gear teeth is crack from tensile force.



Von mises stress distribution in gear B

IV Comparison of Fem Result with AGMA Standard

All metallic gears of a lathe machine gear mechanism are analysed for a stress analysis under loading condition. The study is applied in to finite element method software ANSYS V11. Here FEA stress for metallic spur gears is compared with AGMA stress and a table is formed.

e emparison er menning metanie genis					
Gear Name	σ (AGMA)	σ (ANSYS)	Difference %		
	[Mpa]	[Mpa]	±		
Gear A	126.55	126.79	0.18		
Gear B	126.55	123.59	2.30		
Gear C	146.72	144.85	1.29		
Gear D	142.59	135.52	5.21		
Gear E	150.49	149.08	0.94		
Gear F	150.49	157.25	4.49		
Gear G	204.48	195.38	4.65		
Gear H	202.39	195.24	3.66		

Comparison of AGMA and ANSYS stress of existing metallic gears

COCLUSION

In this research, FEA analysis of metallic spur of lathe machine gear mechanism is done. FEA stresses in all metallic gears are similar to the AGMA stress for all gears and are within their allowable strength limit and are within 6 % difference.

Journal Papers:

- Ashwini Joshi, Vijay Kumar Karma-September 2011, "Effect on Strength of Involute Spur Gear by Changing the Fillet Radius Using FEA"
- [2] Kailash C. Bhosale-2011, "Analysis of bending strength of helical gear by FEM"
- [3] Zeping Wei-July 2009, "Stresses and deformation in involute spur gears by finite element method"
- [4] Pushpendra Kumar Mishra, Dr. M.S. Murthy-July 2013, "Comparison of Bending Stresses for Different Face Width of Helical Gear Obtained Using MATLAB Simulink with AGMA and ANSYS"
- [5] Gagandeep Singh, August 2014, "Increasing life of spur gears with the help of finite element analysis"
- [6] L Kavin Rajkumar1 and A Dyson Bruno, August-2014, "Design And Analysis Of Shear Stress Reduction in Aero-Fin Holed Spur Gears"
- [7] M. S. Hebbal, G.B. Kulkarni, K. H. Prakash, S. S. Patil; May-2014, "Empirical Relation To Estimate The Reduction Of Root Fillet Stress In Spur Gear Due To Elliptical Stress Relief Features"
- [8] Pradeep Kumar Singh, Manwendra Gautam, Gangasagar and Shyam Bihari Lal; July 2014, "Stress Analysis Spur Gear Design by Using Ansys Workbench"
- [9] Dr.Shivappa.D, Shivakumar.N, Ananda.G.K; Dec 2013, "Modeling and Analysis Of Metallic Sintered Spur Gear"

Books:

- [10] Mechanical Engineering Design, Joseph E Shingley, Charles Mischke, Richard G Budynas, Keith J Nisbett, the McGraw-Hill companies.
- [11] Design of Machine element, V. B. Bhandari
- [12] Hand Book of Gear Design, Gitin Maitry.

Thesis:

[13] Makwana rudreshkumar dineshbhai-june 2011 "Analysis of Plastic Spur and Plastic Helical Gear under the effect of Tooth Deformation on Tooth Stresses and Contact Ratio using FEA".

