



A HIGH GAIN HIGH VOLTAGE DC-DC CONVERTER WITH ANFIS CONTROLLER FOR PHOTO VOLTAIC APPLICATIONS

¹D.Sharmila, ²Dr.V.Maheswari, ³M.Murali, ⁴Baladuraikannan P I D T

¹P.G Student, ²Professor, ³Associate Professor

¹ Dept.of EEE, Sreenivasa Institute of Technology and Management Studies, Chittoor, India

² Dept.of EEE, Sreenivasa Institute of Technology and Management Studies, Chittoor, India

³ Dept.of EEE, Vemu Institute of Technology, Chittoor, India

⁴ Dept.of EEE, Vemu Institute of Technology, Chittoor, India

Abstract : Solar energy is considered one of the most promising renewable sources due to the availability of sunlight and its cleaner performance compared to fossil fuels. The transferred energy from the sun to the earth changes during the day. So, absorbing the maximum energy from the solar panel and transferring it to the load is essential. Consequently, maximum power point tracking (MPPT) techniques are proposed in numerous research papers. In this paper, an adaptive neuro fuzzy inference system (ANFIS)-based MPPT controller has been introduced. To transfer maximum power to the load, the duty cycle of the high-gain dc-dc converter, which has been connected between the solar panel and the load, is used. The ANFIS controller combines the merits of neural networks and fuzzy logic. These controllers exhibit fast response and good efficiency in all weather conditions, making them more suitable for nonlinear systems like SPV modules. For validation, the proposed model was analyzed in different situations by hardware kit, and the results show the accuracy and high efficiency of the proposed tracker.

IndexTerms – SPV Module, MPPT, ANFIS Controller, Driver, Converter.

I. INTRODUCTION

The solar photovoltaic modules depend on irradiance and temperature for power generation, but these two factors vary with varying atmospheric conditions like weather, climate, and seasons. This introduces the need for power optimization in solar photovoltaic power generation, which will keep track of the maximum power point and optimize the power accordingly. A maximum power point tracker can be defined as a technique employed in renewable energy-based power generation units like solar photovoltaic or wind turbines to extract maximum power output under uncertain conditions. The efficiency of PV modules in various situations is already known across industries and trades. However, since sunlight, as the source for generating electricity from PV modules, depends on weather conditions, PV modules may have lower efficiency. This results in low electricity generation from solar power. Three factors affect the effectiveness of electricity generation from solar power: solar exposure of the module, module temperature, and PV system properties. The first two factors are beyond human control and are highly unstable because they change from one second to another, depending on the weather conditions and season. Consequently, these properties result in PV systems being an unreliable source of electricity. This paper addresses the above problem and presents the ANFIS method used as the MPPT controller, from which many have been presented in previous papers [2]. In this paper, we developed an ANFIS controller for the actual PV system and applied it in practice [4]. ANFIS is proposed as the MPPT controller and modeled. Therefore, none of them have results compared against those collected from the PV plant. Numerous articles have demonstrated the flexibility of the ANFIS method, although not directly related to PV systems, but were instead compared against the neural network in laboratory conditions [7], used in the role of an expert system for steel grading [8], and integrated bidirectional subsystem MPPT [17]. The articles that have focused on the comparison of the ANFIS method with some other artificial intelligence (AI) methods, such as neural networks (NN) and genetic algorithms (GA), proved that ANFIS is the most suitable for use in uncertain systems [17] and without a doubt presented ANFIS as the most suitable algorithm for MPP tracking. In the past four years, numerous articles and reports have addressed the simulations of PV cells and, consequently, of PV modules and served as the basis for developing authentic models for further research. Type-2 fuzzy logic controller [10], PV MPPT controller with I-V and P-V curve results [12], comparison with fuzzy logic controller [13], standalone complex PV system with MPPT controller [14], trained ANFIS, and fuzzy logic controller according to DC-DC converter The papers that dealt with ANFIS in detail, considering all layers and training methods, opened the path to using ANFIS as the method to resolve all insufficiently defined problems with a high rate of uncertainty in conclusions [2-4], [21]. Many researchers have embedded the ANFIS

algorithm in the field-programmable gate array (FPGA) [2], [6]. This paper deals with ANFIS as an MPPT algorithm in an actual 35 kW PV system used for electricity generation, which has the role of a distributed generation (DG) source of energy, i.e., it feeds all generated energy into the distribution system operator [1]. The specifications of the actual PV system installed on the roof are presented in Section 2. The ANFIS structure, its block diagram, and modeling of the actual system are presented in Section 3. The basics of ANFIS architecture, the data from the actual measurements, the comparison of the obtained results, and the discussion are contained in Section 4. Section 5 contains the conclusion and results.

II. SAMPLING AND SYSTEM MODELLING

2.1 Photo Voltaic System

The most commonly used renewable energy source is solar energy. Increasing the number of solar cells in a panel can increase its voltage output. A photovoltaic, or PV, system is used to convert the solar light energy into electrical energy. The basic component of a PV system is known as a solar cell. A single solar cell has the capacity to produce about 0.5 volts of electricity. A solar panel, or solar module, is a combination of several solar cells connected in series to generate usable voltage. The solar panel voltage can be increased by increasing the number of solar cells. For example, 30 solar cells connected in series will produce an output of 15 volts. A combination of solar panels connected together is known as a solar array and can be used to achieve the required current and voltage. It works by generating electricity when exposed to sunlight, known as the photovoltaic effect. This principle is used by solar cells to produce electricity. The solar cells are made of semiconductors. Mostly, silicon comprises three layers; the top layer, called the N-type layer, is comparatively thin and contains a high concentration of electrons. The bottom layer, called the P-type layer, contains a high concentration of holes. When the p-type and n-type semiconductors join together and form a p-n junction. On forming a p-n junction, the electrons of the n-type material try to reach the p-region, creating a negatively charged layer. Similarly, the holes in the p-type material try to reach the n-region, creating a positively charged layer. This region between the two layers is known as the depletion region of the semiconductor. Sunlight penetrates the top thin layer easily to reach the depletion region. Due to the deficiency of charge in the depletion region, it contains neutral atoms. These neutral atoms are broken, and when the photons from the sun strike the depletion layer, this knocks the electrons from the neutral atoms, leaving behind the holes and using free charge carriers. Then the electrons move towards the n-type layer, and the holes move towards the p-type layer. Due to the electric field present in the depletion region, when connecting an electronic circuit, electrons flow through generating electricity to electrical devices like bulbs, fans, etc.



Fig 2.1 : PV Module

2.2 ANFIS ALGORITHM

Neuro-fuzzy method is important in the designing of fuzzy expert systems. In any case, the right selection of the number, type, rules and parameters of the fuzzy system Membership Functions (MFs) is vital for acquiring the minimum performance. Trial and error is the method to achieve the minimum performance. This fact emphasizes the weight of settings of the fuzzy systems. ANFIS is a Sugeno network within the adaptive systems facilitating learning and training. That framework makes models more systematic and uses expert knowledge so that user does not have to be an expert. For better understanding the ANFIS architecture, consider the following fuzzy system which has two rules, two inputs, and therefore is a first order Sugeno model:

Rule 1: If (x is A1) and (y is B1) then ($f_1 = p_1x + q_1 + r_1$) (1)

Rule 2: If (x is A2) and (y is B2) then ($f_2 = p_2x + q_2 + r_2$) (2)

Literature proposes several types of reasoning of Sugeno fuzzy systems [11]. Based on type of fuzzy reasoning and if-then rules, there are three types of fuzzy inference systems mostly used:

Depending on rule's strength, the overall output is the weighted average of each rule's crisp output (the product or minimum of the degrees of match with the premise part) and MFs. The output membership function used in this example is a monotonic function.

The output of fuzzy system is obtained by applying "maximum" operation to the certified fuzzy outputs (each is equal to the minimum of scoring result and the output membership function of each rule). Diverse schemes have been presented to obtain the final (crisp) output based on the main fuzzy output; some of them are centroid of area (CoA), bisector of area (BoA), mean of max (MoM), etc. [11].

Takagi-Sugeno "if-the" rules are used for the purposes of this paper. Linear combination of fuzzy input variables plus a constant term are used for output of each rule, and the ultimate output is the average weight of output from every rule. One of the ANFIS architectures is the implementation of these two rules as shown in Figure 3. A circle represents a fixed node, as presented in Figure 3, a square indicates an adaptive node (the parameters are changing during training with back propagation or hybrid method of learning).




Fig 2.2 ANFIS Architecture

Layer 1: Nodes in this layer are adaptive nodes. The output of each node is the degree of membership of the input of the fuzzy membership functions represented by the node. Expressions for obtaining those outputs are:

$$O_{1,i} = \mu_{A_i}(x) \quad i=1,2 \quad (3)$$

$$O_{1,i} = \mu_{B_i}(x) \quad i=3,4 \quad (4)$$

where, A_i and B_i are any suitable fuzzy sets in parametric form, and $O_{1,i}$ is the output of the node in the i -th layer. This paper uses trapezoidal shape MFs.

Layer 2: The nodes in this layer are fixed (not adaptive) and therefore are called a Neural Network layer. They are signed with Π to indicate that they play the role of a multiplier function of inputs. Outputs from this node are presented in expression (5).

$$O_{2,i} = W_i = \mu_{A_i}(x)\mu_{B_i}(y) \quad i=1,2 \quad (5)$$

Layer 3: The nodes in this layer are also fixed nodes. They are signed with N to indicate that they perform a normalization of the scoring strength from the previous layer. Output from this node is given in (6).

Layer 4: All the nodes in this layer are adaptive nodes, and therefore this layer is a Fuzzy logic layer. The output of each node is simply the product of the normalized scoring strength and a first order polynomial function. Output from each node from this layer is presented in (7)

$$O_{4,i} = f_i = (p_i x + q_i y + r_i) \quad i=1,2 \quad (7)$$

Layer 5: This layer has one node signed with S to indicate simple summarization in this layer.

The ANFIS architecture is not unique. Combination of some layers can be still produce the same output instead. In ANFIS architecture, there are two adaptive layers (Layers 1 and 4, Fuzzy layers). Layer 1 has three alterable parameters (a_i , b_i and c_i) referring to the input of MFs. These parameters are called premise parameters. Layer 4 also has three alterable parameters (p_i , q_i and r_i) referring to the first order polynomial function. These parameters are consequent parameters. The task of the training or learning algorithm for this architecture is to tune all the alterable parameters to make the ANFIS output match the training data as much as they can.

III. MPPT WITH ANFIS CONTROLLER

The design consists of a PV module, ANFIS controller, DC-DC converter and MOSFET gate driver. The performance of the proposed ANFIS based MPPT controller is evaluated through multimeters physically. The results demonstrated the effectiveness of the proposed technique since the controller can extract the maximum available power for both steady-state and varying weather conditions. Moreover, a comparative study between the proposed ANFIS based MPPT controller is presented. The results that the proposed ANFIS based MPPT controller is more efficient. The below figure shows the block diagram of MPPT with ANFIS controller.




Fig : Block diagram

The below table shows the components list and its specifications:

COMPONENTS	SPECIFICATIONS
Controller	PIC16F877A
Crystal Oscillator	10 MHz
Regulator	7805
Rectifier	W10
Capacitor	470uf, 100uf, 22pf, 47uf
Resistor	330E, 1k, 100E, 470k
Power LED	-
Power supply	12v
PCB Board	-
Driver	IRF2110
MOSFET	IRF840
Inductors	47uH

3.1 MPPT DESCRIPTION

The MPPT solar charge controller is a DC-DC converter for solar power system. It receives voltage from the solar panels and converts it to charge your battery at a more appropriate level. The optimization helps you avoid losing some energy your system captures and generates, maximizing what you can store and use. MPPT stands for Maximum Power Point Tracking. A solar panel has different electric output and different maximum efficiency levels. The efficiency depends on numerous factors, such as the time of day, cloud cover and temperature of the panels. The MPPT identifies the point to get maximum efficiency.




Fig 3.1: MPPT FLOWCHART

The operating points of a PV source feeding a resistive load with a solar insolation level varying from 0.2 W/m² to 1 W/m² are shown in Figure 3.8. It also shows the peak point trajectory at which the PV source gives maximum power as the product of voltage and current. MPPT is employed in PV systems. To ensure the operation of PV modules for maximum power extraction by shifting the operating points (V, I) (Enrique et al. 2010). A special power conversion circuitry and dedicated algorithms are used to ensure that the maximum amount of generated power in PV is transferred to load. A typical PV panel with MPPT fed DC-DC converter is shown in Figure 3.6. The maximum power is delivered from the source when the source impedance matches the load impedance. Therefore MPPT aims at matching the impedance between the PV module and the load using a DC-DC power converter. But, at the same time, the maximum power in a PV panel is not a fixed one and it varies with the environmental changes. Therefore, the duty cycle or control signal of the converter is so adjusted that the PV panel is made to operate at the V_m or I_m, so that the PV panel is operated at its P_m for the given point of time. The choice of converters is made depending on the nature of load and application.




Fig 3.1.1: MPPT description

3.2 DC-DC CONVERTER

The increasing use of electronic devices has drawn more attention to the PV power-producing industry and attempts have been made to develop a dynamic regulation strategy that adapts to the changes in PV source output and load fluctuations. The conventional converters have not been able to handle the changes in operating variables of power systems. Hence, power system engineers and researchers developed isolated and non-isolated converter circuits to provide an integrated solution to the problems of PV systems. These devices are mainly used for regulating the output in terms of stepping up and stepping down the voltage as well as efficiency improvement. The most popular classification of these devices based on topology, number of control elements and the modes of operation are as follows: single-stage converter or DC-DC converter (DC loads), two-stage converter or DC-DC cum AC-AC converter (AC loads), bidirectional converter which feeds the power from source to load and vice versa and its combination, etc. These devices are integrated to improve the PV system performance, which depends on the nature of the load and other related issues.


The suitability of the design and execution of a proper control scheme for the proposed PV system is based on the contribution of PV panel parameters due to the proliferation of nonlinear input and variation in load demand. The DC-DC power converter is an essential element within the MPPT since MPP can be achieved if the converter's operating mode is correctly synchronized. Thus, the major concern for a PV system is the creation of an effective regulator for the DC-DC converter.

3.3 DRIVER

A gate driver is a power amplifier that accepts a low-power input from a controller IC and produces the appropriate high current gate drive for a power device. As requirements for power electronics continue to increase, the design and performance of the gate driver circuitry are becoming ever more important.

Power semiconductor devices are the heart of modern power electronics systems. These systems utilize many gated semiconductor devices such as ordinary transistors, FETs, BJTs, MOSFETs, IGBTs, and others as switching elements in switched-mode power supplies (SMPS), universal power supplies (UPS), and motor drives. Modern technology evolution in power electronics has generally followed the evolution of power semiconductor devices.

Power level requirements and switching frequency are increasing in the power electronics industry. The metal oxide semiconductor field effect transistor (MOSFET) and insulated gate bipolar transistor (IGBT) are two of the most popular and efficient semiconductor devices for medium to high power switching power supplies in most applications.



The gate of a MOSFET or IGBT is the electrically isolated control terminal for each device. The other terminals of these devices are source and drain or emitter and collector. To operate a MOSFET/IGBT, typically a voltage has to be applied to the gate that is relative to the source/emitter of the device. In order to drive these switching devices into conduction, the gate terminal must be made positive with respect to its source/emitter.

3.4 CRYSTAL OSCILLATOR

A crystal oscillator is an electric oscillator type circuit that uses a piezoelectric resonator, a crystal, as its frequency-determining element. Crystal is the common term used in electronics for the frequency-determining component, a wafer of quartz crystal or ceramic with electrodes connected to it. A more accurate term for it is piezoelectric resonator. Crystals are also used in other types of electronic circuits, such as crystal filters.

Piezoelectric resonators are sold as separate components for use in crystal oscillator circuits. They are also often incorporated in a single package with the crystal oscillator circuit.

IV RESULTS

The main parts of hardware kit are Solar panel (12 V, 35 W), High gain DC – DC converter, LED load, Driver circuit and controller circuit. The rating of solar panel is 12 V, 35 W and approximately 3 A. The High gain DC – DC converter consists 2 MOSFET's (IRF 840), 2 inductors (47 μ H), diodes (1N4007) and capacitors (47 μ F). The rating of LED load (100 – 220 V DC / AC). The components of the driver circuit are IR 2110 (MOSFET driver IC), capacitor (470 μ F), diode (1n4007) and resistors (1 k Ω & 470 k Ω). The controller circuit has ANFIS microcontroller (PIC16F877A), crystal oscillator (10 MHz), voltage regulator (7805), full wave bridge rectifier (W10 M) and power supply unit (12 V).




Fig . Hardware kit

The sample solar panel outputs within house are as follows,



Fig. Solar panel without sunlight




Fig. Solar panel with partial sunlight

From above hardware kit outputs, the solar panel outputs at indoor (without solar radiation) and at with partial solar radiation are 1.7 V and 8.84 V respectively. To increase the efficiency of solar panel, it is exposed at sunlight by keeping it in outside house. The sample hardware outputs at exposed to sun light are the solar panel output (input DC voltage) is 13.8 DC Voltage and the DC output voltage (LED voltage) is 169.1. The approximate gain of DC – DC converter is 12.



Fig. Final Hardware output

The sample hardware outputs are tabulated as,

Solar panel output (input DC voltage)	DC output voltage (LED voltage)
1.7 V	20.06 V
8.84 V	105.3 V
10.2 V	123.4 V
11.8 V	143.9 V
13.8 V	169.1 V

V CONCLUSION

In this work, dc-dc converter along with ANFIS control technique was proposed to enhance the output power in the SSPV generation system under any circumstances. The control design was implemented using an additional PIC controller for generating the two inputs for ANFIS control at the source side. Thus, the improved convergence speed and reduced oscillations around the maximum operating point under varying metrological parameters are obtained. The optimal value of the control signal for the converter was generated by employing ANFIS controllers; there by the regulated output is obtained for the required load. The static and dynamic behavior has been presented and analyzed to validate its performance under different operating conditions. The superiority of the proposed control scheme is validated by doing comprehensive comparison with various control schemes. From the test results, it is proved that the proposed scheme offers simple implementation and ease of control. Also, it is established that the proposed control system can track the maximum power with improved efficiency even under transient and steady state operating conditions with reduced power loss using less switches and cost – effective.

VI REFERENCES

- [1] K. Fekete; Z. Klaić; Lj. Majdandzic, “Expansion of the residential photovoltaic systems and its harmonic impact on the distribution grid”, Renewable Energy an International Journal, November 2011.
- [2] S. Selvan, P. Nair, U. Umayal, “A Review on Photo Voltaic MPPT Algorithms”, International Journal of Electrical and Computer Engineering (IJECE), Vol.6 No.2. April 2016.
- [3] A. A. Kulaksız, “ANFIS-based estimation of PV module equivalent parameters: application to a stand-alone PV system with MPPT controller”, November 2013, Turkish Journal of Electrical Engineering & Computer Sciences, (2013) 21: 2127 – 2140.
- [4] D. Mlakić; S. Nikolovski. “ANFIS as a Method for Determinating MPPT in the Photovoltaic System Simulated in Matlab/Simulink”, 39 th International convention on information and communication technology, electronic and microelectronic MIPRO 2016, Opatija, Croatia, 2015.
- [5] D. Mlakić, S. Nikolovski, G. Knežević, “An Adaptive Neuro-Fuzzy Inference System in Assessment of Technical Losses in Distribution Networks”, International Journal of Electrical and Computer Engineering (IJECE), Vol. 6, No 3, June 2016.
- [6] A. Draidi, D. Labeled, “A Neuro-fuzzy Approach for Predicting Load Peak Profile”, International Journal of Electrical and Computer Engineering (IJECE), Vol. 5, No 6, December 2015.
- [7] S. S. Letha; T. Thakur; J. Kumar; D. Karanjkar; S. Chatterji, “Design and Real Time Simulation of Artificial Intelligent based MPP Tracker for Photo-Voltaic System”, International Mechanical Engineering Congress and Exposition IMECE2014, November 2014.
- [8] M. H. F. Zarandi et al, “A Multi-Agent Expert System for Steel Grade Classification Using Adaptive Neuro-fuzzy Systems”, Expert Systems InTech, Petrica Vizureanu (Ed.)
- [9] A. Rezvani; M. Izadbakhsh; M. Gandomkar, “Enhancement of hybrid dynamic performance using ANFIS for fast varying solar radiation and fuzzy logic controller in high speeds wind”, Journal of Electrical Systems (JES), December 2014.
- [10] F. Bendary; et al, “Genetic-ANFIS Hybrid Algorithm for Optimal Maximum Power Point Tracking of PV Systems”, MEPCON 2015, 17th International Middle East Power Systems Conference, December 2015.
- [11] N. Altin, “Interval Type-2 Fuzzy Logic Controller Based Maximum Power Point Tracking in Photovoltaic Systems”, Advances in Electrical and Computer Engineering, August 2013.
- [12] B. Tarek; D. Said; M.E.H. Benbouzid, “Maximum Power Point Tracking Control for Photovoltaic System Using Adaptive Neuro- Fuzzy ANFIS”, Eighth International Conference and Exhibition on Ecological Vehicles and Renewable Energies (EVER), March 2013.
- [13] A. M. S. Aldobhani; R. John, “Maximum Power Point Tracking of PV System Using ANFIS Prediction and Fuzzy Logic Tracking”, Proceedings of the International Multi Conference of Engineers and Computer Scientists (IMECS) March 2008.
- [14] S. S. Mohammed; D. Devaraj; T.P I. Ahamed, “Maximum Power Point Tracking system for Stand-alone Solar PV power system using Adaptive Neuro-Fuzzy Inference System”, 2016 Biennial International Conference on Power and Energy Systems, January 2016.
- [15] A. Arora; P. Gaur, „Comparison of ANN and ANFIS based MPPT Controller for grid connected PV systems”, Annual IEEE India Conference (INDICON), 2015 [16] M. A. Enany; M. A. Farahat; A. Nasr, “Modeling and evaluation of main maximum power point tracking algorithms for photovoltaics systems”, Renewable and Sustainable Energy Reviews, February 2016.
- [17] F. D. Murdianto; O. Penangsang; A. Priyadi, “Modeling and Simulation of MPPT-Bidirectional Using Adaptive Neuro Fuzzy Inference System (ANFIS) in Distributed Energy Generation System”, Intelligent Technology and Its Applications (ISITIA), May 2015.
- [18] S.L. Shimi; et al, “Mppt Based Solar Powered Cascade Multilevel Inverter”, International Conference on Microelectronics, Communication and Renewable Energy (ICMiCR-2013), June 2013.
- [19] F.M.Bendary; et al, “Optimal Maximum Power Point Tracking of PV Systems based Genetic-ANFIS Hybrid Algorithm”, International Journal of Scientific & Engineering Research, Volume 7, Issue 4, April 2016.

[20] F. M. Bendarya; et al, "Optimized Genetic-ANFIS Algorithm for Efficient Maximum PowerPoint Tracking of Photovoltaic Systems", Shubra Conference, January 2015.

[21] A. Tjahjono; et al, "Photovoltaic Module and Maximum Power Point Tracking Modelling Using Adaptive Neuro Fuzzy Inference System", Makassar International Conference on Electrical Engineering and Informatics (MICEEI), December 2014.

Author's profile:

D.SHARMILA from Andhra Pradesh has completed her graduation in VEMU Institute Of Technology was established in the year 2008, is affiliated to Jawaharlal Nehru Technological University Ananthapuram(JNTUA) P.KothaKota in the stream of Electrical and Electronics Engineering in 2020. Presently she is pursuing master's in Power Electronics from Sreenivasa Institute of Technology And Management Studies was established in the year 1998-99 under Srinivasa Trust is affiliated to Jawaharlal Nehru Technological University Ananthapuram(JNTUA) Murakambattu, Chittoor (A.P), India



Dr V Maheswari completed her Graduation Ganadipathy Tulsi's Jain Engineering College, Anna University, Chennai in the year 2007 and done her Masters SKP Engineering College, Anna University, Chennai in the year 2009 and Received Ph.D from St's Peters University, Chennai in the year 2015. She is currently working as Professor, in Department of Electrical & Electronics Engineering, Sreenivasa Institute of Technology and Management Studies, Chittoor, Andhra Pradesh, India.



M Murali completed his Graduation from Jawaharlal Nehru Technological University, Hyderabad in the year 2006 and done his Masters from Jawaharlal Nehru Technological University, Anantapur in the year 2009. He is currently working as Associate Professor, in Department of Electrical & Electronics Engineering, Vemu Institute of Technology, P.Kothakota, Andhra Pradesh, India. And Currently Pursuing Ph.D in Jawaharlal Nehru Technological University, Anantapur, Andhra Pradesh, India.

