

EFFECT OF STEEL RATIO AND MINERAL ADMIXTURES ON SHORT COLUMNS

Kartikya Krishna¹, Mr Afaque Khan²

¹M.Tech Scholar Structural Engineering Department of Civil Engineering, BBDU Lucknow India

²Asst. Proff. Department of Civil Engineering, BBDU Lucknow India

Abstract: during this thesis the study performance of concrete below compression with steel fiber and Ferro-cement partial add of cement, it's been Studied that the relative below Compression load partial adding of steel fiber and Ferro-cement seem that the quantitative relation ar designed for target strength and end in inflated Stress-strain price.

Keywords: cement, Ferro cement, sand, steel fibre, etc.

I. INTRODUCTION

Concrete could be a semisynthetic construction materials that is most ordinarily utilized in construction add the globe. it's obtained by mix of water, cement, fine mixture, coarse mixture and a few minerals admixtures in necessary proportion ar referred to as concrete. The hardened concrete may be worked as a synthetic stone within which the voids of coarse ar crammed by the fine aggregates and cement. The hardening of concrete is caused by reaction between cement, water, and reaction for an extended time and hardening of concrete robust with the age. The properties of concrete depend upon the amount and proportion of the ingredients utilized in the combo and therefore the management exercised in formwork and natural action.

Concrete is that the boon to construction, because it has varied direct and indirect blessings concrete has several inherent blessings such as:

- A. High resistance and weathering action
- B. accessibility of ingredients at affordable value
- C. High compressive strength
- D. Mould ability to any form resulting in branch of knowledge finishes
- E. Aesthetic look. so it wide utilized in construction it's some disadvantages they're
- F. Low lastingness
- G. Poor malleability
- H. a lot of crispness
- I. High W/C quantitative relation

A Concrete with reinforcement fails suddenly once subject to earthquake and nuclear blast etc. This downside may be avoided if the important sections are able to bear massive plastic deformation and be in an exceedingly position to soak up massive of strain energy.

Section composed with high strength steel and better steel ratios fail suddenly while not yielding of tension steel, provision of compression reinforcement helps to some extent. However the planning becomes most uneconomical

The improvement in malleability of concrete permits economical use of high strength steel, higher cement quantitative relation and avoids unforeseen failure and additionally the instant curvature characteristics of ferroconcrete section may be brought nearer to it of a steel section and therefore the analysis of intermediate concrete structures get simplified. The concrete with improved malleability is a lot of economical artefact.

The structural that are designed for seismic resistant demands high malleability. So the malleability of concrete is being improved by confining it in steel binders, as ties in compression member and as stirrups in beams at this time. Within the structures that are statically indeterminate the important section, at that 1st hinge forms are incidentally additionally the section having most shear force. The stirrup reinforcement, that is provided. Moreover, use of refined arrangement of closely spaced stirrups in confinement columns not solely creates plane of weakness between core {and the|and therefore the|and additionally the} concrete and interrupts the continuity however also adds the matter of steel congestion. Therefore it should not be doable to sufficiently the structure by providing the laterals ties alone however it might be helpful if a supplementary or indirect confinement, additionally to laterals, may be devised. Many investigations have maligned that incorporation of discontinuous, distinct and uniformly unfold fibers in concrete will increase lastingness malleability, impact, toughness, flexural and fatigue resistance.

The conclusion highlighted that fibers will provide some confinement, such sort of concrete is termed as Confined fiber ferroconcrete (CFRC). After we use fibers in massive volumes it's tendency to ball. So limitation to the amount of indirect confinement offered by steel additionally. This Limitation confinement necessity the necessity of further confinement may be provided within the variety of Ferro cement shell. Such concrete may be termed as Confined Ferro ferroconcrete (CFRC). gift|this|the current} present investigation is an endeavor to review the strain characteristics of CFRC.

II. LITERATURE REVIEW

A. P Sangeetha one and R. Sumathi 2010 [2] Fiber – Wrapping mistreatment Fiber – strengthened Plastic (FRP) shells is one amongst effective strategies, considerably enhances the strength and malleability of concrete columns. The paper reports the behavior of the GFRP wrapped concrete columns below uniaxial compression. The cross section of the concrete columns thought-about within the work is circular with diameter of 150mm and height 300mm. The Parameters that are varied within the investigation are wrapping shell materials, (which includes GFRP Materials Surface Mat(SM), shredded Strand Mat (CSM) and woven Roving Mat (WRM)), variety of Plies (1Ply and 3plies) and amount of natural action (7 Days). Results from a series of the experimental study were reportable and mentioned. The study on little – scale specimens showed that confinement inflated the strength of the concrete columns loaded axially.

B. Shabans Salik K one, Athira M. M. 2, Lalna S.S 3 ,Prasum C. 4 ,Rafeekha K.5 Rajimol K. R 6, Safna A. M seven 2015 [3] This paper evaluates the performance of short concrete compression members strong with fiber rope wrapping, below axial compression. From the study on small-scale specimens, it's been seen that the fiber rope wrapped specimen exhibit important increase in strength, as compared to regulate specimen, because of the confinement by rope wrapping. The tests were allotted with ropes of various diameters zero.6cm, 1cm and 1.4cm at spacing of zero.0h, 0.1h, 0.2h and 0.3h, wherever h is that the height of the specimen. most improvement was obtained for wrapping with fiber rope of diameter one.4 cm at 0.0h spacing. The strength was found to be inflated with increase in diameter of rope and faded with increase in spacing. the prices for unit improvement with varied wrapping were figured out and therefore the methodology was found to be terribly cost-efficient. because the weight of fiber rope is negligibly little, it's much no impact on footing style.

C. A.R. Rahai 1 ,P.Sadeghian a pair of and M.R. Ehsani 32008 [4] This paper presents the results of experimental studies concerning concrete cylinders confined with high-strength carbon fiber strengthened compound (CFRP) composites. Forty little scale specimens (150×300 mm) were subjected to uniaxial compression up to failure and stress-strain behaviors were recorded. the varied parameters like wrap thickness and fiber orientation were thought-about. completely different wrap thicknesses (1, 2, 3, and four layers), fiber orientation of 0o, 90o, ±45o and combos of them were investigated. The results incontestible important improvement within the compressive strength, stiffness, and malleability of the CFRP-wrapped concrete cylinders as compared to unconfined concrete cylinders.

D. Katsuki Takiguchi one And Abdullah 22000 [5]n Investigation by several researchers have indicated that by providing external confinement at plastic region or over the whole strengthened columns, the strength and malleability may be increased. during this paper, a strengthening methodology mistreatment circular ferrocement jacket to enhance the confinement of a substandard column was investigated and compared with management specimens and completely different strengthening strategies. 5 1:6 scale model sq. columns were created and are tested below constant axial load whereas at the same time being subjected to cyclic lateral load. The loading system utilized in this experiment displaced the tested columns in an exceedingly double bending. 2 columns were tested as management specimens; one column was strong with circular Ferro cement jacket and were compared with those of alternative 2 identical sq. RC columns strong circularly with plate and carbon fiber. The management specimens suffered shear failure and important degradation of strength throughout testing whereas the strong columns showed ductile flexural response and better strength. The check results indicate that circular Ferro cement jacket may be a good different material to strengthen ferroconcrete column with in adequate shear resistance.

E. Hanaa I EI Sayad one and Aiman A. Shaheen 22011 [6] The aim of this investigation is first off to judge the various strategies used for confining the ferroconcrete (R.C) columns either internally or outwardly. Secondly, the result of warming on the performance of confining strategies is studied mistreatment the pc program "ANSYS five.4". Beside the normal crosswise steel ties, the interior confinement was glad by steel fibers or a cage of xpanded metal mesh within the ties, whereas external confinement was achieved by wrapping the studied columns with Ferro cement layers or GFRP sheets. Six R. C columns were ready, namely, the management column strengthened historically with crosswise ties solely, 2 columns containing

I Chronicles and a couple of steel fibers, one column strengthened to boot with a cage of distended metal mesh, 2 columns wrapped with either Ferro-cement laminates or fibre strengthened plastics (GFRP). The columns were tested below axial hundreds to judge the result of the various confining strategies on the final word capability and malleability. it had been found that adding a pair of steel fibers or reinforcing the column with a cage of distended metal mesh within the ties gave virtually similar results (26% increase within the final capability compared therewith of the management column). Despite that {the final|the last word|the final word} capability of the column wrapped with GFRP was the best among the studied columns (37% increase within the ultimate capacity), its malleability was the bottom. The constant quantity study mistreatment ANSYS five.4 showed that the R.C columns containing steel fibers were less littered with hearth than the opposite columns. it had been additionally found that the final word capability of R.C columns wrapped with GFRP was reduced by hearth to a high degree (approximately fifty three reduction within the final capacity).

F. PSangeetha 2006 [7] Fiber wrapping or enclosure of columns with fiber-reinforcedplastic (FRP) sheets considerably enhances strength and malleability of concrete. to research the behavior of concrete columns confined by fiber strengthened compound (FRP) sheets below uniaxial compression, analytical models were resolved mistreatment Finite component methodology (FEM) against revealed experimental information. Cross sections of concrete columns in analysis ar categorised into circular, sq. and rectangular sections. Finite component Analysis (FEA) will effectively simulate the behavior of concrete columns confined by FRP sheets once the correct numerical model is adopted. Results from a series of the analysis on small-scale specimens showed that confinement increase strength (20-25) and malleability of concrete columns loaded axially. ANSYS (version half-dozen.0) offers a series of terribly sturdy nonlinear capabilities for styles and analyses.

G. Emdad K. Z. Balanji 1, M. Neaz ruler a pair of Muhammad N.s. Hadi three 2016 [8] The strength and malleability of high strength concrete columns improve with the addition of steel fiber. This paper reports the behavior of circular High Strength Concrete (HSC) columns strengthened with Hybrid Steel Fibers (HSF) below completely different loading conditions. during this study, HSF consisted of a mix of macro steel fibers and small steel fibers. a complete of eight circular specimens of 205 mmdiameter and 800 millimeter height were forged and tested. All specimens were strengthened with same quantity of steel reinforcements. The specimens were divided into 2 teams of 4 specimens. cluster RC (reference group) contained no steel fibers. cluster HSF (hybrid steel fibers) contained a pair of.5% by volume of HSF. From every cluster one specimen was tested below coaxial loading, one below twenty five millimeter eccentric loading, one below fifty millimeter eccentric loading, and one below four-point loading. The results showed that the specimens strengthened with HSF achieved higher strength and malleability compared to RC specimens below completely different loading conditions. it had been additionally determined that the presence of HSF delayed the spalling of the concrete cowl

H. Azadeh Parvin one and David Brighton a pair of 2014 [9] In recent years, the repair of unstrengthened and broken ferroconcrete member by external bonding like ferrocement laminate is increasing that demands would like of investigations on behavior of ferrocement confinements. important quantity of labor has been allotted on confinement of column with ferrocement laminates considering

amendment in parameter like varieties of meshes with completely different sizes, concrete grade, height of column, etc. during this study, use of ferrocement as associate external confinement to concrete specimen is investigated with respect to layers of confinement and orientation of meshes. The effectiveness of confinement is achieved by scrutiny the behavior of confined specimen therewith of unconfined specimen.

I. Shankarkumar V1 ,Arun K 2, Dhivya P 3, Mahesh Kumar M4, Suresh adult male R5 2010 [10] Invention of latest strategies in strengthening concrete is below work for many years. On the track of such invention Fiber strengthened Composite materials plays a major role. the most perform of fiber reinforcement is to hold the load on its length and additionally to supply stiffness and strength in one direction. FRP therefore alters the compressive strength, lastingness and flexural strength of concrete to an honest extent and therefore it imprints as an honest answer for strengthening concrete. FRP materials may be outwardly bonded or wrapped to the present structure; therefore they will even be used for rehabilitation works. There ar 3 major varieties of fiber strengthened polymers utilized in construction works. they're fibre strengthened compound (GFRP), Carbon fiber strengthened compound (CFRP) and Aramid fiber strengthened compound (AFRP). within the gift investigation the result of GFRP on M25 and M50 concrete combine is studied at 2 cases. First, result of GFRP on the compressive and flexural strength of M25 and M50 concrete combine with relevance variety of layers, and second result of GFRP on compressive strength M25 and M50 concrete combine with relevance variety of layers at 2000C temperature that is termed as sturdiness studies.

J. Md. Mozaffar Masud1 and Arum Kumar2 2013 [11] The present study investigates the result of confinement mistreatment ferrocement as wrapping material on the circular RC columns below coaxial loading condition. Methods: Experimental studies were allotted on the confining result mistreatment external confinement technique with one layer and 2 layers of GI wire mesh below concentrically loaded condition. All columns were tested by uniform coaxial compressive load from prime with a hydraulic compression testing machine of capability 1000KN. Findings: Most of the researches have done on confining result of either long column or short column (slenderness quantitative relation quite 3). This paper demonstrates the confining result on short column having slenderness quantitative relation is a smaller amount than three, such a column is named pedestal. Pedestal could be a variety of short column that is employed as a base support for steel structure, sculpture or jar. to guard the column of steel structure from corrosion that's in direct contact of soil, pedestal is provided. throughout earthquake such a structure will collapse or maybe cracks will develop. Hence, Ferro cement structures ar extremely ductile and energy dissipating material which will undergoes massive deformations while not collapsing throughout earthquakes. Even the malformed structures may be strong at terribly low value when deformation. Steel jacketing has proved to be a good live for strengthening or retrofitting and has been wide utilized in follow, however the engineering community is presently searching for alternatives. Applications/Improvements: Material like Ferro cement is oldest, value effective methodology emerges an alternate answer for strengthening of ferroconcrete column. External confinement or encasing of column with Ferrocement enhances the strength and malleability of concrete column.

III. CONCLUSION

A. On the premise of check result, {we will|we will|we are able to} counsel that stress-strain property of the concrete can more be improved by mix another varieties of mineral admixture like ‘Blast-furnace scum (BFS), ash (FA), Rice Husk ash (RHA)’ as future work.

B. On the premise of result get from current work a study is additionally steered for Flexural strength and Split lastingness connected properties in future.

C. On the premise of result get from current work a study is additionally steered for Bond strength by Pull out check connected properties in Future.

D. The confinement of the reinforcement in column with fibers has improved stress-strain behavior compared to plane concrete.

E. The confinement of Ferro cement shell with fibers has improved the strain strain behavior of the concrete

REFERENCES

- [1] Piyush Sharma “Analytical analysis on Ferro cement: style, Strength and utility aspects “ IJSRSET 2016.
- [2] P. Sangeetha, R Sumathi “Behavior of fibre wrapped concrete columns below uniaxial compression” International Journal of Advanced engineering technology.
- [3] Shabana salih. K Athira M, Lalan S, Pasum C Refeekha K, Rajimol K, Safna A.M “ result of Coil Wrapping on the Compressive Strength of Short Axially Loaded Concrete Members”.
- [4] A R Rahai, P Sadeghian and M R Ehsani “Experimental Behavior of concrete cylinders confined with CFRP composites ” The ordinal World Conference on Earthquake.
- [5] Katsuki Takiguchi, Abdullah “ Experimental study on Reinforcement concrete column strong with ferrocement jacket”
- [6] Hanaa I EISayad, Aiman A Shaheen “ hearth Resistance of Internally or outwardly confined Reinforcement concrete Columns “
- [7] P Sangeetha “Analysis of FRP wrapped concrete column below uniaxial compression “ Journal of Scientific & Industrial analysis.
- [8] Emdad Balanji , M Neaz ruler, Muhammad Hadi “ Performance of high strength concrete columns reinforcement with hybrid fiber below completely different loading conditions.
- [9] “FRP Composites strengthening of concrete columns below varied loading conditions “ Azadeh Parvin , David Brighton.
- [10] Shankar kumar, Arun Kumar, Dhivya, Mahesh Kumar , Suresh adult male “ Strength and sturdiness Characteristics of fiber ferroconcrete “ International journal of Science and analysis .
- [11] Md. Mozaffar Masud , Arun Kumar Indian Journal of Science and Technology “ Strengthening of Circular RC column through external confinement mistreatment Ferro cement.