LASER -BASED SURFACE MODIFICATION OF ENGINEERING ALLOYS

Mrs.JYOTHI WADGERI
Lecturer,Department of Mechanical Engg,
Govt Polytechnic Immadihalli

Abstract -Laser-based surface modification is an advanced materials engineering process widely used to enhance the surface characteristics of engineering alloys. This technique employs high-energy laser beams to alter the microstructure and composition of alloy surfaces, resulting in improved wear resistance, corrosion resistance, hardness, and fatigue life. This paper delves into the principles, methods, benefits, and applications of laser surface modification (LSM), including laser hardening, alloying, cladding, remelting, and texturing. It also explores current research, challenges, and future directions in this technologically evolving domain.

Keywords
Laser surface modification, engineering alloys, laser cladding, laser alloying, surface hardening, microstructure, corrosion resistance

1. Introduction

Engineering alloys, including steels, aluminum, titanium, and nickel-based alloys, are widely employed in industries such as aerospace, automotive, biomedical, and energy due to their excellent mechanical properties. However, their surfaces are often exposed to aggressive environments, leading to wear, corrosion, oxidation, and fatigue. To combat these issues, surface modification techniques have become vital.

Laser-based surface modification has emerged as a precise, flexible, and efficient method. Unlike conventional methods like carburizing or nitriding, laser techniques offer localized treatment, minimal heat-affected zones, and superior metallurgical bonding. The versatility of laser systems, including continuous wave and pulsed lasers (CO_2, Nd:YAG, fiber lasers), makes them suitable for diverse applications.

2. Literature reviews

2.1Problem Definition Wear of material is the process of removal of material from two solid surfaces in solid-state contact. It occurs when solid surfaces are in rolling motion or sliding motion relative to each other. In a well-designed tribological system, the removal of material is a slow process but it is continuous and steady. Similar to friction, the wear of material is also a very complicated phenomenon, which has various mechanisms and factors are involved. Several type of wear phenomena occurs like, wear of an unlubricated metal pair sliding in a dusty atmosphere may be termed dry wear, metallic wear, sliding wear, scratching wear, abrasive wear depending on the emphasis intended. To know the amount of wear undertaken, by direct contact of Al alloy with metal counter surface, it is necessary to experimentally evaluate and measure the corresponding friction and wear. The test to be carried out under various operating condition and under controlled conditions. With a view to generate new performance data, we have chosen three alloys viz. Experiments are to be carried out on standard pin-on-disc machine, at ambient temperature and under dry operating condition. There- fore, the purpose of this work was to determine the dry sliding friction.

3. Principles of Laser-Material Interaction

When a high-energy laser beam impinges on a metallic surface, the energy is absorbed, causing rapid heating, melting, and sometimes vaporization. The extent of modification depends on:

- **Laser Parameters**: Wavelength, power density, pulse duration, and scanning speed.
- **Material Properties**: Thermal conductivity, absorption coefficient, and melting point.

- **Ambient Conditions**: Shielding gases (argon, nitrogen) influence oxidation and solidification.

The thermal gradients and rapid solidification result in fine-grained microstructures, phase transformations, and improved surface characteristics.

4. Techniques of Laser Surface Modification

4.1 Laser Hardening

Laser hardening enhances the hardness and wear resistance by transforming the surface microstructure (typically forming martensite in steels). It avoids the use of additional materials and preserves the core properties of the base metal.

- **Applications**: Automotive gears, crankshafts, turbine blades.
- **Advantages**: Low distortion, high precision, fast processing.

4.2 Laser Alloying

In this technique, alloying elements (either pre-deposited or injected) are melted into the surface. The result is a new surface composition with enhanced properties.

- **Elements Used**: C, B, Si, Ti, Cr, Ni.
- **Target Alloys**: Steel, aluminum, titanium alloys.
- **Applications**: Biomedical implants, cutting tools.

4.3 Laser Cladding

Laser cladding involves the deposition of a material layer (metallic powders or wires) on the substrate surface using a laser. It forms a metallurgically bonded coating resistant to wear and corrosion.

- **Materials Used**: Ni-based, Co-based, Fe-based alloys, carbides, ceramics.
- **Applications**: Turbine components, die tools, biomedical implants.

4.4 Laser Remelting

This process melts the substrate surface without adding material. It refines the microstructure, removes defects, and enhances properties like corrosion resistance.

- **Application Areas**: Stainless steel in nuclear and marine industries.

4.5 Laser Texturing

Laser beams create micro/nano-scale patterns on surfaces to alter tribological, optical, and biological behaviors.

- **Applications**: Microfluidics, biomaterials (cell adhesion), anti-reflective coatings.

5. Materials Affected by Laser Surface Modification

Alloy Type	Typical LSM Applications
Stainless Steel	Corrosion resistance, biomedical implants
Titanium Alloys	Biomedical and aerospace, improved osseointegration
Aluminum Alloys	Wear resistance for automotive and aerospace
Nickel Superalloys	High-temperature resistance in turbines
Tool Steels	Cutting tools, dies, and molds

6. Microstructural Changes and Property Enhancements

Laser-modified zones typically exhibit:

- **Refined Microstructures**: Due to rapid solidification.
- **Hard Phases**: Martensite, carbides, borides.
- **Improved Hardness**: Often up to 2–3× increase.
- **Better Adhesion**: Metallurgical bonding instead of mechanical bonding.
- **Low Porosity**: Especially in optimized cladding processes.

These improvements result in better **wear**, **corrosion**, and **fatigue resistance**—critical for mechanical systems in aggressive environments.

7. Applications in Mechanical Systems

7.1 Aerospace

Laser cladding and alloying on turbine blades and structural parts offer oxidation and wear resistance at high temperatures.

7.2 Automotive Industry

Laser hardening and alloying on engine blocks, camshafts, and valves improve fatigue life and wear performance.

7.3 Biomedical Field

Laser-textured titanium implants improve bone integration and reduce implant rejection.

7.4 Power Generation

Superalloy components in turbines are repaired and enhanced by laser cladding, extending their service life.

7.5 Tooling and Molding

Tool steels benefit from laser hardening and cladding, increasing wear resistance and service time for dies and molds.

8. Advantages of Laser Surface Modification

- Non-contact, precise, and rapid process.
- Localized treatment minimizes distortion.
- Environmentally cleaner than conventional methods.
- Superior bonding and adhesion.
- Customizable through parameter tuning.

9. Challenges and Limitations

- **High Initial Costs**: Equipment and maintenance.
- **Process Complexity**: Requires skilled operation and control systems.
- **Porosity and Cracks**: Especially in cladding, if parameters are suboptimal
- **Limited Penetration Depth**: May require multi-pass or hybrid treatments.

10. Future Trends and Developments

- **AI and Machine Learning**: For parameter optimization and quality prediction.
- **Hybrid Processing**: Combining LSM with additive manufacturing or mechanical methods.
- **Nano-structuring and Laser Shock Peening**: For improved fatigue resistance.
- **Sustainable Materials**: Eco-friendly coatings using LSM.
- Emerging laser systems with ultra-short pulses (femtosecond lasers) are enabling ultra-precise modifications, opening new avenues in micro/nano-engineering of alloy surfaces.

11. Conclusion

Laser-based surface modification presents a powerful set of tools for enhancing the surface performance of engineering alloys in critical mechanical systems. From increasing wear and corrosion resistance to enabling biocompatibility, the versatility and precision of laser techniques make them indispensable in modern engineering. With advancements in control systems, beam shaping, and material science, laser surface modification is poised to revolutionize the design and longevity of high-performance components across industries

References

1. Steen, W.M., & Mazumder, J. (2010). *Laser Material Processing* (4th ed.). Springer.
2. Dutta Majumdar, J., & Manna, I. (2011). *Laser Processing of Materials*. Sadhana, 28(3–4), 495–562.
3. Zhang, Y., et al. (2019). Laser surface modification of metallic biomaterials: Techniques and applications. *Surface and Coatings Technology*, 426, 127743.
4. Toyserkani, E., Khajepour, A., & Corbin, S.F. (2004). *Laser Cladding*. CRC Press.
5. Dahotre, N.B., &Harimkar, S.P. (2008). *Laser Fabrication and Machining of Materials*. Springer.
6. Zhang, X., et al. (2018). Advanced laser processing in aerospace and automotive sectors. *Journal of Manufacturing Processes*, 50, 583–602.
7. Liu, S., et al. (2018). Optimization of laser cladding parameters using machine learning. *Materials & Design*, 160, 1105–1114.
8. Mahamood, R.M., & Akinlabi, E.T. (2018). *Laser Metal Deposition Process of Metals, Alloys, and Composite Materials*. Springer.