

# HIERARCHICAL AND FLAT ROUTING ENERGY ENHANCEMENT PROTOCOLS IN WIRELESS SENSOR NETWORKS

Mrs.L.Sudha  
Research Scholar/AP  
Navarasam Arts And Science College for women  
Arachalur

## Abstract

Late advances in wireless sensor networks have summoned numerous new conventions particularly intended for sensor networks where energy mindfulness is a critical concern. These routing conventions may vary from relying upon the application and the network design. To expand the lifetime of Wireless sensor network (WSN), an energy effective plan can be composed and created by means of a calculation to give sensible energy utilization and network for WSN. To keep up high adaptability and better data aggregation, sensor nodes are regularly gathered into disjoint, non-covering subsets called clusters. Clusters make hierarchical WSNs which fuse effective usage of constrained assets of sensor nodes to lessen energy utilization, in this way expand the lifetime of WSN. The goal of this paper is to display a cutting edge overview and order of energy effective plans for WSNs.

**Keywords – Wireless Sensor Network, cluster, energy efficient clustering, network lifetime, energy efficient algorithms, energy efficient routing, and sensor networks.**

## 1. INTRODUCTION

A Wireless sensor network can be defined as a network of devices that can communicate the information gathered from a monitored field through wireless links. The data is forwarded through multiple nodes, and with a gateway, the data is connected to other networks like wireless Ethernet. There has been a quick development in wireless correspondence strategy. Economical and low power wireless small scale sensors are composed, sent and generally utilized as a part of wireless and versatile condition [1]. Wireless Sensor Networks (WSNs) are an accumulation of gadgets alluded to as nodes which sense nature around them and transmit this data through wireless correspondence to a sink. It is a network of vast number of sensor nodes sent over a topographical region for observing physical marvels like temperature, mugginess, vibrations, seismic occasions, et cetera, where every node is outfitted with constrained on-board preparing, stockpiling and radio abilities. All sensor nodes are utilized for recognizing an occasion and routing the data in wireless networking [2]. These sensor nodes are little in measure that incorporates three essential segments: a detecting subsystem for data procurement from the physical encompassing condition, a preparing subsystem for nearby data handling and capacity, and a wireless correspondence subsystem for data transmission and are conveyed in detecting territory to screen particular targets and gather the data. At that point the sensor nodes send the data to base station (BS) by utilizing wireless transmission strategies. WSN is utilized as a part of different applications like medicinal services framework, war zone observation framework, condition checking framework, human conduct observing, agribusiness observing et cetera. Energy sparing is a standout amongst the most essential highlights for detecting the nodes to expanded their lifetime in WSN[3]. A **sensor node**, also known as a mote is a node in a sensor network that is capable of performing some processing, gathering sensory information and communicating with other connected nodes in the network. A mote is a node but a node is not always a mote. Also, the fundamental power supply of the sensor node is battery. In most application situations, clients are typically hard to achieve an area of sensor nodes. Because of expansive number of substitution of batteries may be inconceivable. Sensor node utilized its battery may make detecting territory revealed on account of limited battery energy [4].

In this way, energy protection winds up noticeably basic worry in WSN. To give nodes a long stretch of independence, new and effective energy plot and relating calculation must be composed and built up that plans to advance energy use are required, to expand the lifetime of nodes and the life expectancy of the network all in all [5].

To keep up high versatility and better data aggregation, sensor nodes are regularly gathered into disjoint, non-covering subsets called clusters. The cluster-based method is one of the methodologies which join effective use of restricted assets of sensor nodes to make smaller liveliness use in wireless sensor networks likewise it gives network adaptability, asset sharing and proficient utilization of obliged possessions that gives network topology strength and energy sparing characteristics [6].

Clustering plans offer tapering correspondence overheads, and proficient asset allotments in this way diminishing the general energy utilization decreasing the obstructions among sensor nodes. The fundamental concentration of this article is to study and study of energy productive conventions to decrease the data transmission separation of sensor nodes in wireless sensor networks [7].

Some of the advantages and limitations of WSNs are:

**Advantage:**

- ✓ Reduce cabling costs.
- ✓ Radio transmission technology optimized for harsh industrial environment.
- ✓ Real time measurement monitoring.

**Limitations:**

- ✓ Limited degree of hardware flexibility, processing power, and communication bandwidth and storage space.
- ✓ Sensors typically powered through batteries.
- ✓ For batteries that cannot be recharged, sensor node should be able to operate during its entire mission time or until battery can be replaced.
- ✓ Energy efficiency is affected by various aspects of sensor node/network design [8].

## 2. ROUTING IN WSN

A sensor network is a system that consists of thousands of very small stations called sensor nodes. The main function of sensor nodes is to monitor, record, and notify a specific condition at various locations to other stations and end users. Eventually, this presents a wide range of applications that motivates research in sensor networks. The communication among nodes is done in a wireless fashion, and thus, the name of wireless sensor networks. This paper studies wireless sensor networks throughout a number of selected articles, papers, and online resources. A good understanding of sensor networks and wireless communications is the main learning outcome of this study. Specifically, the research concentrates on routing in sensor networks, and is supported by a simulation of a sensor network application performed with network simulator.

### Flat Based Routing:

The main class of routing protocols is the multi-bounce level routing protocols. At the point when enormous measure of sensor nodes are required, level base routing is required where each node normally assumes a similar part. In level networks, sensor nodes team up to play out the detecting undertaking. Because of the substantial number of such nodes, it isn't plausible to downgrade a worldwide identifier to every node. This thought has prompted data driven routing, where the BS sends inquiries to unambiguous areas and sits tight for data from the sensors positioned in the chose districts. Since data is being asked for through investigation, property based naming is significant to designate the properties of data [9].

SPIN (Sensor protocols for information via negotiation):

It is a group of versatile protocols that utilization data arrangement and advantage versatile calculations. Turn is a data ambitious routing protocol. These groups of protocols spread data to every last node in the network with the presumptions that all nodes in the network could be potential base sinks. This empowers a client to ask for data from any node in the network and get the asked for data since every one of the nodes in the network have a similar data. In these protocols all neighbors nodes have similar data and it is just data that the others nodes don't have that appropriated to the neighbors nodes [10].

DD (Direct diffusion):

It is a data-centric (DC) and application-mindful protocol in which data produced by sensor nodes is named by characteristic esteem sets. Data that is headed to the sink is consolidated as it is sent keeping in mind the end goal to expel excess; limiting the no. of transmissions along these lines sparing battery energy which thusly draws out the network lifetime. The execution of the data aggregation strategies in coordinated dispersion technique is influenced by variables, for example, position of the source nodes, number of sources and the network topology[11].

RR (Rumor routing):

It is a sort of coordinated distribution and is utilized for applications where geographic routing isn't possible. It joins question flooding and occasion flooding protocols arbitrarily.

Optimized link state routing (OLSR)

Optimized link state routing (OLSR) belongs to the category of proactive routing protocols and it uses table focused practice. The main drawback of OLSR is that it has a massive overhead. To compensate this delay, multipoint relays (MPRs) are used to overcome the large overhead. For data transmission, three adjutant nodes are used as MPRs by every node. No unswerving control information is required as each node sends it alternating

CADR (Constrained anisotropic dispersion routing):

It is a protocol, which endeavors to be a general type of Directed Diffusion. The thought is to question sensors and course data in a network so as to supplement the data pick up, while limiting the dormancy and communication capacity. This is proficient by actuating just the sensors that are near a specific occasion and powerfully changing data courses. The real distinction from Directed Diffusion is the thought of data pick up not withstanding the correspondence cost. In CADR, every node assesses a data/cost goal and courses data in view of the neighborhood data/cost slope and end-client necessities [12].

Hierarchical Based Routing:

Hierarchical or cluster based routing, initially proposed in wire line networks, are notable procedures with extraordinary points of interest identified with versatility and effective correspondence. Accordingly, the idea of hierarchical routing is additionally used to perform energy productive routing in WSNs. In a hierarchical design, higher energy nodes can be utilized to process and send the data while low energy nodes can be utilized to play out the detecting in the nearness of the objective. This implies manufacture of clusters and allotting infrequent assignments to cluster heads can incredibly add to general framework versatility, lifetime, and energy effectiveness. Hierarchical routing is a proficient method to bring down energy utilization inside a cluster and by performing data aggregation and combination so as to make smaller the quantity of transmitted messages to the BS. Hierarchical routing is for the most fraction two-layer routing where one layer is utilized to choose cluster heads and the other layer is utilized for routing [13].

**LEACH (Low Energy Adaptive Clustering Hierarchy):**

It is most well-known hierarchical routing protocol for sensor networks in which most nodes transmit to cluster heads, and the cluster heads pack and total the data and forward it to the base station. Filter accept that every node has a radio sufficiently intense to straightforwardly achieve the base station or the closest cluster head, however that utilizing this radio at full power all the time would squander energy. Nodes that have been cluster heads can't move toward becoming cluster sets out again toward P rounds. Toward the finish of each round, every node that isn't a cluster head chooses the nearest cluster head and joins that cluster to transmit its data [14].

**HEED (Hybrid energy efficient distributed clustering):**

It is a clustering protocol for WSNs, which expands the essential plan of LEACH by utilizing leftover energy as an essential restriction and network topology highlights (e.g. node degree, separations to neighbors) as optional parameter to break bind between hopeful cluster heads, as a metric for cluster choice to accomplish organize adjusting. That implies the cluster heads are probabilistically preferred in view of their leftover energy and sensor nodes connect the clusters as indicated by their energy level. The clustering procedure is isolated into part of emphases and in every sequence; nodes which are not secured by any cluster head twofold their likelihood of receiving to be cluster head. Since this energy effective clustering protocol authorize each node to freely and probabilistically choose its part in the clustered network, They can't guarantee ideal chose set of cluster heads[14].

**TEEN (Threshold sensitive energy efficient sensor network protocol):**

The sensor network design depends on a hierarchical congregation where nearer nodes from clusters and this procedure goes on the second level awaiting the point when base position is come to. High schooler isn't useful for applications where infrequent information are requisite since the client may not acquire any data whatsoever edges are not come to [15].

**PEGASIS (Power efficient gathering in sensor information systems):**

It is a data assembling and close ideal chain-based computation that sets up the idea that energy preservation can come about because of nodes not specifically determining clusters. This computation decreases the energy utilization by formation of a sequence structure contained all nodes and consistently data aggregation over the chain. The calculation introduces the possibility that if nodes shape a fasten from foundation to sink, just a solitary lump in any given communication time span will transmit to the base station. PEGASIS evades cluster development and uses just a solitary node in a fasten to transmit to the BS rather than per surrounding as the power depleting is numerous gestures. Keeping in mind the end goal to build network lifetime, nodes require just speaking with their nearest neighbors and they interchange in speaking with the BS [15].

### 3. COMPARATIVE ANALYSIS

Table 1: Hierarchical routing v/s Flat routing

Hierarchical routing	Flat routing
Reservation-based scheduling	Contention-based scheduling
Collisions avoided	Collision overhead present
Data aggregation by cluster head	Node on multihop path aggregates incoming data From Neighbours
Require global and local synchronization	Links formed on the fly without synchronization
Energy dissipation is uniform	Energy dissipation depends on traffic patterns
Energy dissipation cannot be controlled	Energy dissipation adapts to traffic pattern

### 4.CONCLUSION

A standout amongst the most difficult issues in the WSNs is sparing the energy. To make the sensor node energy proficient with broadened lifetime, diverse energy productive power sparing plans must be created. We have studied the condition of specialty of various clustering calculations in WSNs revealed in the writing. We have discovered that the some energy productive calculations increment the network lifetime. A true exertion has been made to give finish and accurate condition of craftsmanship power talented calculations indication appropriate to WSNs.

### REFERENCES

- [1] ChengzhiLong, Yixing Li and Yihong Li, "A Multi-Hop Routing Scheme Based On Different Spatial Density Of Nodes in WSN'S". Journal of Theoretical and Applied Information Technology. Vol.46 No.1. Dec.2012.
- [2] Amanjot Singh Toor and Taranpreet Kaur, "Implementation and Analysis of Stable Election Protocol", International Journal of Advanced Research in Computer Science and Software Engineering. Vol.3, Issue 9. 2013
- [3] SurenderKumar, M. Parteek, N.J Ahuja, "Multi-hop Energy Efficient Protocol for Heterogeneous Wireless Sensor Network". International Journal of Computer Science and Telecommunications. Vol.5, Issue 3. March 2014.
- [4] SudhanshuTyagi, Sumit Kumar Gupta and Sandeep Tanwar, "EHE-LEACH: Enhanced Heterogeneous LEACH Protocol for Lifetime Enhancement of Wireless SN's.", IEEE International Conference on Advances in Computing, Communications and Informatics (ICACCI). 2013.
- [5] N.Javaid, A.A Khan and M.Akbar, "ACH-Away Cluster Heads Scheme for Energy Efficient Clustering Protocols In WSN's.", IEEE. 2013
- [6] MamtaTewari and Kunwar Singh Vaisla., "Performance Study of SEP and DEC Hierarchical Clustering Algorithm for Heterogeneous WSN.", IEEE Sixth International Conference on Computational Intelligence and Communication Networks. 2014.
- [7] Rajesh Patel, SunilPriyani and Vijay Ukani., "Energy and Throughput Analysis of Hierarchical Routing Protocol (LEACH) for Wirelsss Sensor Network," International Journal of Computer Applications (0975-8887). vol.20-No.4., April 2011.
- [8] Pallavi Jain and Harminder Kaur, "An Improved Gateway Based Multi Hop Routing Protocol for Wireless Sensor Network" International Journal of Information & Computation Technology. Vol.4.No 15, pp.1567-1574. 2014.

- [9] R.K Yadav and Arpan Jain., “*CHAT-SEP: CriticalHeterogeneous Adaptive Threshold Sensitive Election Protocol for Wireless Sensor Networks*”,IEEE, International Conference on Advance Computing,Communications Informatics.(ICACCI). 2014.
- [10] Shobti Saini and Meenakshi Sharma., “*Prolonging the Network Lifetime of Heterogeneous WSN’s Using MECRSEP*”,IEEE, International Conference on Electronics, Communication and Computational engineering.(ICECCE).2014.
- [11] Siddiq Iqbal,Sandesh B.Shagrithaya,and Sandeep Gourda G.P., “*Performance Analysis of SEP and its Extensions in WSN’s.*”, IEEE, International Conference on Advance Communication Control and Computing Technologies.(ICACCT). 2014.
- [12] Chunyao FU,Znifang Jiang,Wei wei., “*An Energy Balanced Algorithm of LEACH Protocol in WSN,*” International Journal of Computer Science.Issue 1,Vol.10,January2013.
- [13] Q.Nadeem,M.B Rasheed,N.Javaid and Z.A Khan, “*M-GEAR: Gateway Based Energy Aware Multi-Hop Routing Protocol for Wireless Sensor Network,*” arXiv.137105v1.July 2013.
- [14] Li Y., Yu N., Zhang W., Zhao W., You X., and Daneshmand M., “*Enhancing the Performance of LEACH Protocol in Wireless Sensor Networks,*” IEEE infocom, pp. 223-228, 2011.
- [15] Jianguo W., Zhongsheng W., Fei S. and Guohua S., “*Research on routing algorithm for wireless sensor network based on energy balance,*” American Journal of Engineering and Technology Research, vol. 11, no.9, pp. 189- 195, 2011.
- [16] Sona Malhotra., Urmila.,” Multi-hop Energy Enhancement Protocols in WSN ” Journal of Network Communications and Emerging Technologies, Volume 8, Issue 2, February (2018).

