

Development of a PAS Integrated Electric Bike for Sustainable Transportation

Vishal Francis^{1,2}, Prathamesh Deshpande², Rishikesh Bobde², Royal Rewatkar², Rupesh Dev²

¹Lovely Professional University, Punjab, India,

²G H Rasoni College of Engineering, Nagpur, India.

Abstract: One of the sustainable solution for local transportation is the utilization of e bicycles. In the current scenario e bikes have are used as an means of compact and less pollution transportaion tool. It would be used to one of the most promising means of transportaion in large crowded cities. In developing countries there is an increased deemand of electric bikes in order to combat the issue of pollution. In this regard, attempt has been made to develop E-Bike for city commute with 60 km range. A Pedal Assist System has been implimented.

Introduction:

Energy crisis is one of the major concerns in today's world due to fast depleting resources of petrol, diesel and natural gas. In combination with this, environmental decay is an additional factor which is contributing to the depletion of resources which is an alarming notification. The electric bike which works on the battery that is powered by the motor is the general mode of transport for a local trip. The solar panels can be alternative source for this by adding it to the system. The electric bike which will be running on battery, the power is supplied by the motor, thereby supplying this power to drive the other gear components. The main purpose of using this e-bike is that it is user friendly, economical and relatively cheap [1-5]. The efficiency of this system undeniable compared to conventional modes of transport.

With the advancement in the design of e bikes by the use of high efficiency batteries and lighter motors, they are being used by geat variety of consumers. They provide environmentally tool for transportation and therefore is one of the sustainable mode of transportaion. [6-7]. As fossil fuels are depleting the utilization of electric bicycle can be a viable solution. E bike is becoming popular because of its various advantages such as less pollution, lighter weight and more economical in terms of fuel and maintenance [8-12]. Moreover, it does not require license and insaurance.

In e-bikes a motor is controlled by a controlling system which can be powered by the battery. Earlier the ebikes were bulky due to the weight of the lead acid batteries. Recently, with usage of lithiun-ion batteries the weight can be reduced and providing more power, duarability and performance.

Methodology:

The methodology adopted for the study is presented below:

- i. A simple control strategy has to be developed for Indian city driving conditions with less fuel consumption for reducing emissions.
- ii. A conventional two-wheeler will be converted into a plug-in hybrid electric two-wheeler by retrofitting a hub motor in the rear wheel.
- iii. Experiments will be carried out on engine and electric hub motor to estimate the power and torque requirements for various operating conditions.
- iv. A detailed investigation will be carried out to estimate the battery energy and power requirements for various conditions.

Components:

Hub motor: Hub motors were used in this work. Hub motors have a number of advantages over others. Hub motors are found to be more efficient as compared to their counterpart. Figure 1 shows the schematic diagram and the image of the actual hub motor used.




Figure 1 Hub motor used in the study

Battery for E-Bike:

Li-ion battery is selected for the study. The LFP-3610S 36-V, 15-AH battery (figure 2) is selected with the following performance specification:

- Weight: approx. 4.5kg
- Battery Cell: Grade A 18650 battery cell
- BMS: Included




Figure 2 Battery used for the e bike

Pedal Assist System:

Pedal assisted system was used in the e bike which powers the motor when pedals are used without the need of throttling. In this study an 8 magnets 5 level PAS Sensor is used.

Speed Control Basics

The speed controller has dual purpose in the e bike. First it controls the speed of motor and also serves as dynamic brake. This is done by using the power from the battery and driving the hub motor. Figure 3 shows the speed control system.




Figure 3 Speed control system for the e bike

LCD Display screen:

A LCD display was used in the system, specifications of the same is as follows:

Quick Details Brand name: Kunteng, Model Number: KT-LCD3 Plug: waterproof/nominal plug Voltage: 24v/36v/48v.



Figure 4 LCD display used in the system

Testing and Observation:

The testing was performed in the city of Nagpur, Maharashtra. The details are illustrated in table 1.

Parameters	Observation
Ease of driving	Smooth driving experience
Maximum speed obtained	28.5km/hr
Average speed obtained	27km/hr
Range of e-bike	57.5km/hr
User friendly	Very easy to use
Working of the display	The display showed correct reading of certain parameters displayed such as range, battery remaining.
Working of the controller	We were able to control the speed of the bike using the hand throttle

Charging time for battery	3 to 4 hr
Stability of bike	The e-bike was stable while driving.

Table 1 Testing and Observation

Conclusions:

The conclusions of the project are as follows:

In order to develop an alternative solution for transportation in local area an e bike is developed employing PAS integrated system. The speed of 28.5 km on a plane terrain was achieved. We are also able to achieve the range of 60km. Through the use of pedal assist system unnecessary power consumption can be saved and thus more range can be obtained. By using lithium ion battery we are able to obtain largest energy density for the battery, also for which low maintenance is required. By using hub motor we are able to obtain more power, low maintenance and longer lifespan. We are able to provide an e-bike at affordable cost for a daily use. As harmful gases are not emitted from the e-bike, we are able to achieve our objective of environmental friendly transportation. The removable battery helps us to charge it anywhere thus making the e-bike useful for any daily activities.

References:

- [1]. Muetze A, Tan Y C (2005), Performance evaluation of electric bicycles, Industry Applications Conference, Vol. 4, pp: 2865 – 2872.
- [2]. Thiyagarajan V, Sekar V, Controlling of brushless DC motors in electric bicycles using electronic based circuit with 8-bit microcontroller, International Journal of Engineering Sciences & Emerging Technologies, Dec. 2012, Volume 4, Issue 1, pp: 26-34.
- [3]. Oman H, Morchin W C, Jamerson F E (1995), Electric-bicycle propulsion power, Microelectronics Communications Technology Producing Quality Products Mobile and Portable Power Emerging Technologies, p 555.
- [4]. Boccaletti C, Duni G, Petrucci P, Santini E, Design of an electrical drive for motorized bicycles, Department of Electrical Engineering, University of Rome "La Sapienza", Italy.
- [5]. McLoughlin I V, et al., Campus Mobility for the Future: The Electric Bicycle, Journal of Transportation Technologies, Jan 2012, pp: 1-12.
- [6]. Bennett C H, Rehkemper G J, Combs D, Flywheel Powered Bicycle with an Articulated Rider, US Patent No. 6517408, 2003.
- [7]. Morchin W C (1994), Battery-powered electric bicycles, Northcon/94 Conference Record, pp: 269 – 274.

- [8]. Somchaiwong N, Ponglangka W (2006), Regenerative Power Control for Electric Bicycle, SICE-ICASE International Joint Conference, pp: 4362-4365.
- [9]. Brand S I, Ertugrul N, Soong W L, Investigation of an Electric Assisted Bicycle and Determination of Performance Characteristics, Australasian Universities Power Engineering Conference, Christchurch, 28 September-1 October 2003, pp: 1-6.
- [10]. Snelson A, Lawson S D, Morris B, Cycling Motorists: How to Encourage Them, Traffic Engineering and Control, Vol. 34, No. 11, 1993, pp: 555-559.
- [11]. Outram C, Ratti C, Biderman A, The Copenhagen Wheel: An Innovative Electric Bicycle System That Harnesses the Power of Real-Time Information and Crowd Sourcing, Conference on Ecologic Vehicles & Renewable Energies (EVER2010), Monaco, May 2010.
- [12]. Starschich E, Muetze A (2007), Comparison of the Performances of Different Geared Brushless-DC Motor Drives for Electric Bicycles, Electric Machines & Drives Conference IEEE International, Volume 1, pp: 140 – 147.

