An Secure Multikeyword Search Using Improved Order Retaining Encryption

[1]Priyanka D.S,[2]Mrs. Jasmine M
[1]Research Scholar, [2]Assistant Professor
[1] Computer Science and Engineering, Vishwavidyalaya Engineering College, Lakhanpur, Sarguja University, Ambikapur India
[2] Computer Science and Engineering, Vishwavidyalaya Engineering College, Lakhanpur, Sarguja University, Ambikapur India

Abstract : Distributed storage is a bearer display wherein records are kept up, oversaw and supported up remotely at the cloud feature, and meanwhile information keeps on being had to the clients over a network. Cloud based thoroughly benefits enables the cell phone clients to spare and recover reports or data at the cloud through Wi-Fi mediums, which enhances the certainties accessibility and empowers the archive sharing way without depleting the area cell phone resources The data protection inconvenience is fundamental in distributed storage gadget, so the delicate information is scrambled with the guide of the proprietor sooner than redistributing onto the cloud. Portable distributed storage machine causes new difficulties over the traditional scrambled look for plans, with regards to the controlled registering and battery limits of cell apparatus, and data sharing and approaching systems through remote verbal trade. Therefore, an appropriate scrambled look for plan is basic for insurance of on line records .The enhanced Order Retaining Encryption is a sort of encryption intended to help seeks on figure writings. Mineral encodes plaintexts to figure writings with the indistinguishable request, making it conceivable to usefully analyze figure writings without unscrambling. The work proposes a protected multi watchword seek plot utilizing enhanced Order holding Encryption**.**

IndexTerms **- Cloud Computing, Cloud Storage, Mobile Cloud Storage (MCS), Cloud Searching, Keyword Search.**

I. INTRODUCTION

Distributed computing is that the conveyance of on-request figuring administrations from applications to capacity and process control by and large over the net and on a compensation as-you-go premise. One beneficial thing about abuse distributed computing administrations is that organizations will stay away from the immediate cost and intricacy of owning and keeping up their very own IT framework, and rather just get what they utilize, when they utilize it. The origination of processing as-a-benefit has been around for a ton of, for any longer as path back on the grounds that the Nineteen Sixties, when pc departments would empower organizations to lease time on a centralized server, rather than must be constrained to acquire one themselves. These 'time-sharing' administrations were generally surpassed by the expansion of the PC that made owning a pc far less expensive, at that point by the expansion of organization learning focuses wherever companies would store huge measures of information. Distributed storage can be an administration demonstrate among the data is kept up, oversaw, spared remotely and made obtainable to clients over a system. Clients ordinarily get their cloud information stockpiling on a for every utilization, month to month rate. In spite of the fact that the per-gigabyte cost has been drastically determined down, distributed storage providers have accessorial in activity costs that may manufacture the innovation dearer than clients anticipated. Cloud security keeps on being a need among clients. Providers have attempted to impact those feelings of dread by building security capacities, similar to cryptography and validation, into their administrations. There are three principle cloud-based capacity configuration models: open, non-open and hybrid.

1. Open Cloud: Public distributed storage administrations give a multi-inhabitant stockpiling setting that is most suited to unstructured .Data is keep in world information focuses with capacity learning unfurl over various locales or landmasses. Clients more often than not pay on a for every utilization premise relatively like the utility installment display.
2. Private Cloud: It gives on-premises, stockpiling administrations with an obsessive setting ensured behind an association's firewall.
3. HybridCloud: can be a blend of non-open cloud and outsider open cloud administrations with arrangement between the stages for administration. The model offers organizations adaptability and a considerable measure of learning readiness decisions.

1.1 Challenges in Cloud Computing

1. Self-mending - just if there should be an occurrence of capacity disappointment, there'll constantly be a reinforcement running while not major postponements, making the asset change appear to be consistent to the client.
2. SLA-driven - cloud is administrated by administration level assentions that enables numerous examples of single application to be repeated on various servers if require emerges; dependent on a need topic, the cloud may limit or quit working a lower level application. .
3. Multi-tenure - the cloud allows various customers to utilize steady equipment at consistent time, though them knowing it, probably incurring irreconcilable situations among clients. .
4. Service-situated - cloud grants one purchaser to utilize various applications in making its own. .
5. Virtualized - applications don't appear to be equipment particular; fluctuated projects may keep running on one machine exploitation virtualization or a few machines may run one program.

6. Linearly climbable - cloud should deal with an ascent in handling straightly; if "n" times a great deal of clients need an asset, an opportunity to complete the demand with "n" a ton of assets should be generally consistent. .
7. Data administration - dissemination, dividing, security and synchronization of data.

1.2 Security problems in Cloud

1. Relating to open and cross breed cloud situations, the loss of generally speaking administration perceivability and the related absence of control can be an issue.
2. Despite the way that as a rule, undertaking grade cloud administrations are more secure than inheritance engineering, there is as yet a potential expense as information breaks and downtime.
3. For organizations that come to depend vigorously on open and cross breed cloud stages, there is a risk that they turned out to be compelled to proceed with a particular outsider merchant essentially to hold operational limit. On the off chance that basic business applications are bolted into a solitary seller, it very well may be exceptionally hard to settle on strategic choices, for example, moving to another merchant. As a result, the seller is being furnished with the use it needs to drive the client into an ominous contract.
4. In segments, for example, social insurance and fund, where authoritative prerequisites as to capacity of private information are substantial, accomplishing full consistence while utilizing open or private cloud contributions can be more intricate.
5. When a business purchases in outsider cloud benefits as either an open or half breed cloud offering, it is likely they won't be given a full administration depiction, specifying precisely how the stage works, and the security forms the merchant works.
6. Cloud merchants furnish their clients with a scope of Application Programming Interfaces (APIs), which the client uses to deal with the cloud benefit. Tragically, only one out of every odd API is altogether secure. They may have been considered to be at first, and afterward at a later stage be observed to be shaky somehow or another. This issue is exacerbated when the customer organization has manufactured its very own application layer over these APIs. The security weakness will then exist in the client's own application. This could be an inside application, or even an open confronting application conceivably uncovering private information.
7. Responsibility for particular issues of information security should be completely characterized before any arrangement. Neglecting to do as such could prompt a circumstance where there is no plainly characterized approach to manage potential dangers and fathom current security vulnerabilities.
8. Using open or half breed cloud contributions can open a business to security vulnerabilities caused by different clients of a similar cloud foundation. It is constantly conceivable that a security helplessness caused by another client in a similar cloud will influence each client.
9. Self-recuperating - just in the event of capacity disappointment, there'll constantly be a reinforcement running while not major deferrals, making the asset change appear to be consistent to the client.
10. SLA-driven - cloud is administrated by administration level assentions that enables numerous occasions of single application to be reproduced on various servers if require emerges; dependent on a need topic, the cloud may limit or quit working a lower level application. .
11. Multi-occupancy - the cloud allows different customers to utilize consistent equipment at steady time, while them knowing it, no doubt delivering irreconcilable circumstances among clients. .
12. Service-situated - cloud grants one shopper to utilize different applications in making its own. .
13. Virtualized - applications don't appear to be equipment particular; fluctuated projects may keep running on one machine exploitation virtualization or a few machines may run one program.
14. Linearly climbable - cloud should deal with an ascent in preparing straightly; if "n" times a considerable measure of clients need an asset, an opportunity to complete the demand with "n" a great deal of assets should be generally consistent.
15. Data administration - appropriation, dividing, security and synchronization of data.

II. RELATED WORK

Normally with compelled information transmission limit and confined battery life, these issues familiarize overpowering overhead with preparing and correspondence and also a higher power usage for PDA customers, which makes the encoded look for over adaptable cloud especially troublesome. In paper TEES (Traffic and Energy saving Encrypted Search), a transmission limit and essentialness compelling mixed request plan over adaptable cloud is discussed. The proposed plan offloads the count from mobile phones to the cloud [1].To associate with convincing inquiry undertakings on these files which will be encoded, information proprietors at starting an ensured open record on the watchword set expelled from archives, by then they submit available document to the association server. Finally, information proprietors scramble their files and redistribute the relating encoded records to the cloud server [2]. A distinct survey has been coordinated on looking at strategies for different cloud store organizations are driven. As demonstrated by the survey a more capable reviewing procedure is relied upon to reduce the correspondence cost, looking at time and moreover to help successful multiuser setting and giving multi assessing task is required [3]. Reviews the state-of-art look at in cloud security. As shown by the attack levels, it separates four sorts of strikes in the cloud, i.e., arrange based ambushes, VM-based attacks, stockpiling based strikes, and application based ambushes. The countermeasures and looking at frameworks are then introduced. Also, this paper moreover discusses an inventive and promising response for cloud security by capably changing system structure [4]. Makers proposed a protected, gainful and furthermore one of a kind chase system, that backs the exact Multikeyword situated look and moreover the dynamic annihilation and also mixture of chronicles. They moreover developed a crucial catchphrase balanced twofold tree as the record, and furthermore realized an "Avaricious Depth-first Search" computation to get extraordinary capability than direct request [5].

III. PROBLEM IDENTIFICATION

There are some sensible worries in cloud based looking which is as said underneath:

1. Not worrying over the physical structure of a web searcher infers that particular parts of the utilization will be out of your control. In case a cloud-based web searcher isn't performing sufficiently brisk, you can't simply incorporate another server event or addition the RAM. If your customers are geologically appropriated, you can't simply put a generation server in another territory.
2. In the cloud, the security implies when clients visit the delicate information, the cloud administrations can keep potential foe from construing the client's conduct by the client's visit demonstrate. In trade, buyer's specific circumstance and security should be ensured and utilized suitably. In associations, security involves the utilization of laws, instruments, models, and procedures by which by and by identifiable data is overseen.
3. In versatile based cloud frameworks the propelled phones are looked with tremendous quantities of vague security risks from PCs, and diverse customary data encryption methodologies are transported in portable cloud. Regardless, versatile dispersed capacity structure achieves new challenges over the standard encoded look designs, in light of the confined enrolling and battery breaking points of PDA, and what's more data sharing and getting to approaches through remote correspondence.
4. The past methodology depends on single watchword seek approach which constrains the scan choices accessible for client in cloud.

IV. RESEARCH METHODOLOGY

4.1 Searching Process in Cloud

Mobile cloud based storageenables the cell phone clients to store and recover records or learning on the cloud through remote correspondence that enhances the data accommodation and encourages the document sharing strategy while not weakening the local cell phone assets . Truly, 2 classes of encoded seek procedures exist that may change the cloud server to play out the pursuit over the scrambled information:

- Ranked catchphrase seek
- Boolean catchphrase seek.

The hierarchical keyword search adopts the connectedness scores to represent the connectedness of a file to the searched keyword and sends the top-k relevant files to the consumer. it's additional appropriate for cloud storage than the Boolean keyword search approaches, since Boolean keyword search approaches got to send all the matching files to the shoppers, and thus incur a bigger quantity of network traffic and a heavier post-processing overhead for the mobile devices.A keyword is form of just like the Platonic ideal of a quest question; it's associate in nursing abstraction that we tend to extrapolate from multiple search queries.A search question or search term is that the actual word or string of words that a quest engine user varieties into the search box..

- In SEO, we will in general focus on these deliberations by streamlining on-page (utilizing the catchphrases in URLs, title labels, body duplicate, picture document names, meta depictions so on), by building internal connections with watchwords inside the grapple , and so forth.

- In PPC, we will in general target catchphrases by offering on them and exploitation them in our promotions and greeting pages.

- Search inquiries, on the contrary hand, are this present reality terms that people use to search out those pages through inquiry. There are unit two styles of watchword look :

- Multi-watchword look is at one time a page positions for different varieties of same catchphrase. Thinking about the enormous assortment of data clients and archives inside the cloud, it's important to allow numerous catchphrases inside the pursuit demand and return reports inside the request of their connectedness to those watchwords.

- Single-Keyword seek is before a page positions for correctly one term and not its varieties.

4.2 Proposed Approach

Actualized approach means to coordinate multi-watchword look plan and Order-Preserving Encryption Using Approximate Integer Common Divisors for enhancing the proficiency of the current work. The vector space display and the generally utilized TF X IDF show are joined in the record development and question age. An exceptional tree-based record structure and propose a "Voracious Depth-first Search" calculation to give effective multi-catchphrase positioned seek. The Order Retaining Encryption approach is used to encode the list and question vectors, and in the interim guarantee precise significance score figuring between scrambled file and inquiry vectors.

4.3 Order Retaining Encryption

It enables correlation tasks to be straightforwardly connected on encoded information, without unscrambling the operands. Hence, equity and range inquiries and in addition the MAX, MIN, and COUNT questions can be straightforwardly handled over scrambled information. Thus, GROUP BY and ORDER BY activities can likewise be connected. Just while applying SUM or AVG to a gathering do the qualities should be unscrambled. The consequences of question preparing over information encoded utilizing the methodology is correct. They neither contain any false positives nor miss any answer tuple. It handles refreshes nimbly. An incentive in a segment can be adjusted or can be embedded in a segment without requiring changes in the encryption of different qualities. It can without much of a stretch be incorporated with existing database frameworks as it has been intended to work with the current ordering structures, for example, B-trees. The way that the database is encoded can be made straightforward to the applications**.**

4.4 Greedy Depth First Search

The algorithm traverses a graph in a depth ward motion and uses a stack to remember to get the next vertex to start a search, when a dead end occurs in any iteration.



Figure 1 : Example of DFS

As in the example given above, DFS algorithm traverses from S to A to D to G to E to B first, then to F and lastly to C. It employs the following rules.

- Rule 1 − Visit the adjacent unvisited vertex. Mark it as visited. Display it. Push it in a stack.
- Rule 2 − If no adjacent vertex is found, pop up a vertex from the stack. (It will pop up all the vertices from the stack, which do not have adjacent vertices.)
- Rule 3 − Repeat Rule 1 and Rule 2 until the stack is empty**.**

4.5 Searching process in proposed approach

1. User first saves a file data along with a name assigned in cloud.
2. A Stemmer Net library is applied and stems are created for the file name.
3. The stem created is further utilized to create an hash value in order to create a OPE tree index structure. Each node to the tree contains the encrypted stem and hash value.
4. The encrypted stem and hash value are also stored in table along with file data.
5. The file and other information are encrypted in cloud using Transparent Encryption Algorithm.
6. The user inputs a single keyword as input query.
7. Stem is generated for the input query and associated hash value is also generated.
8. The stems and hash value are further locates in the binary tree.
9. If a match found then the record with associated hash value is decrypted and sent to user from cloud platform**.**

4.6 Transparent Data Encryption

Transparent data encryption ensures Azure SQL Database and Azure Data Warehouse against the risk of pernicious action. It performs ongoing encryption and decoding of the database, related reinforcements, and exchange log records very still without expecting changes to the application. Straightforward information encryption encodes the capacity of a whole database by utilizing a symmetric key called the database encryption key. This database encryption key is secured by the straightforward information encryption defender. The defender is either an administration overseen declaration (benefit oversaw straightforward information encryption) or a hilter kilter enter put away in Azure Key Vault (Bring Your Own Key). You set the straightforward information encryption defender at the server level. TDE performs ongoing I/O encryption and unscrambling of the information and log documents. The encryption utilizes a database encryption key (DEK), which is put away in the database boot record for accessibility amid recuperation. The DEK is a symmetric key anchored by utilizing an endorsement put away in the ace database of the server or a topsy-turvy key secured by an EKM module. TDE secures information "very still", which means the

information and log documents. It furnishes the capacity to follow numerous laws, controls, and rules set up in different ventures. This empowers programming engineers to scramble information by utilizing AES and 3DES encryption calculations without changing existing applications.

V. RESULTS AND DISCUSSION

5.1 Tools used for experiment

The front tool used was Asp.Net.ASP.NET is a web improvement stage, which gives a programming model, a complete programming foundation and different administrations required to develop powerful web applications for PC, and also versatile devices.ASP.NET chips away at best of the HTTP convention, and utilizations the HTTP directions and strategies to set a program to-server respective correspondence and cooperation.ASP.NET is a piece of Microsoft .Net stage. ASP.NET applications are incorporated codes composed utilizing the extensible and reusable parts or questions present in .Net system. These codes can utilize the whole chain of command of classes in .Net system**.**The database tool used was Sql Server.SQL Server is Microsoft's social database administration framework (RDBMS). It is a full-highlighted database fundamentally intended to contend with contenders Oracle Database (DB) and MySQL. Like all major RBDMS, SQL Server underpins ANSI SQL, the standard SQL dialect. In any case, SQL Server likewise contains T-SQL, its very own SQL usage. SQL Server Management Studio (SSMS) (recently known as Enterprise Manager) is SQL Server's primary interface device, and it underpins 32-bit and 64-bit conditions. SQL Server is here and there alluded to as MSSQL and Microsoft SQL Server.The programming language used was C#.C# was created by Anders Hejlsberg and his group amid the advancement of .Net Framework# is intended for Common Language Infrastructure (CLI), which comprises of the executable code and runtime condition that permits utilization of different abnormal state dialects on various PC stages and architectures. The highlights are:

- It is a cutting edge, universally useful programming dialect
- It is protest arranged.
- It is part arranged.
- It is anything but difficult to learn.
- It is an organized dialect.
- It produces effective projects.
- It can be arranged on an assortment of PC stages.
- It is a piece of .Net Framework.

The cloud platform used was Microsoft Azure.Microsoft Azure, once in the past known as Windows Azure, is Microsoft's open distributed computing stage. It gives a scope of cloud administrations, including those for register, investigation, stockpiling and systems administration. Clients can pick and look over these administrations to create and scale new applications, or run existing applications, in the general population cloud.

5.2 Dataset used for analysis

Since adhaar card pictures are not accessible uninhibitedly on the web. So we have made around a database of 100 example adhaar card pictures physically to test. These pictures where gathered from assortment of sources.

5.3 Space and Time consumption analysis

The comparative analysis of space consumption among the algorithms is as given below.

Table 1- Space consumption

	Existing	Proposed
Space	1529700	1250148
	1530500	1260138
	1629700	1344155
	1524599	1233455



Figure 2: Analysis for Space consumption reading

The above space consumption reading clearly shows that the proposed approach has less space consumption as compared to traditional existing algorithm. The comparative analysis of running time among the algorithms is as given below.

Table 2- Execution time

	Existing	Proposed
Time	76	64
	70	56
	85	76
	80	70
	76	64

The above execution time reading clearly indicates that approach proposed has less execution period in milliseconds as compared to the existing approach.



Figure 3: Analysis for execution time

The graphical analysis is more explanatory as it shows that the reading is much higher in case of improved approach, therefore the most efficient one. In the X Coordinate-Axis the performance of algorithm is denoted and in Y-Axis the execution period in milliseconds is denoted.

VI. CONCLUSION

Developing techniques for efficiently searching data and files on cloud environment has gained a lot of momentum in recent years. With ever increasing need for maintaining large amount of data and due to limited local storage, the information privacy problem is paramount in cloud storage device, so the sensitive data is encrypted with the aid of the owner earlier than outsourcing onto the cloud. We began with the presentation of an essential plan that we contrasted with past encoded scan devices for distributed computing and demonstrated their wastefulness in a portable cloud setting. At that point we built up a productive usage to accomplish a scrambled hunt in a versatile cloud. We proposed a multi-watchword seek plan to perform encoded information look over portable cloud in future. As our OPE calculation is a basic one, another expansion is to locate a great calculation which won't hurt the proficiency. Likewise an enhanced adaptation of OPE calculation was additionally actualized. Trial results demonstrate that the proposed system performed better when contrasted with past strategy. In future an enhanced strategy can be executed which builds up an arrangement of strict protection necessities for such a safe cloud information usage framework. Among different multi-watchword semantics, this strategy picks the effective similitude proportion of coordinate matching

REFERENCES

[1] Jian Li, “TEES: An Efficient Search Scheme over Encrypted Data on Mobile Cloud”, IEEE Transactions on Cloud Computing ,2015

[2] AshwiniSude, V.D.Shinde,” Survey on Multi-keyword Search in Cloud Computing”,IJIRCCE,February 2017.

[3] R.Ahila , S.Sivakumari,”A Survey : Cloud Computing Security Issues And Techniques”,IJARCS,August 2017

[4] Z. Xia, X. Wang, X. Sun and Q. Wang, "A Secure and Dynamic Multi-Keyword Ranked Search Scheme over Encrypted Cloud Data," in IEEE Transactions on Parallel and Distributed Systems, vol. 27, no. 2,

[5] Z. Fu, X. Sun, Z. Xia, L. Zhou and J. Shu, "Multi-keyword ranked search supporting synonym query over encrypted data in cloud computing,"2013 IEEE 32nd International Performance Computing and Communications Conference (IPCCC), San Diego, CA, 2013, pp. 1-8.

[6] https://www.infoworld.com/article/2652198/security/gartner--seven-cloud-computing-security-risks.html.

[7] Z. Xia, X. Wang, X. Sun and Q. Wang, "A Secure and Dynamic Multi-Keyword Ranked Search Scheme over Encrypted Cloud Data," in IEEE Transactions on Parallel and Distributed Systems, vol. 27, no. 2,

[8] Z. Fu, X. Sun, Z. Xia, L. Zhou and J. Shu, "Multi-keyword ranked search supporting synonym query over encrypted data in cloud computing,"2013 IEEE 32nd International Performance Computing and Communications Conference (IPCCC), San Diego, CA, 2013, pp. 1-8.

[9] C. Guo, Q. Song, R. Zhuang and B. Feng, "RSAE: Ranked Keyword Search over Asymmetric Encrypted Cloud Data," Big Data and Cloud Computing (BDCloud), 2015 IEEE Fifth International Conference on, Dalian, 2015, pp. 82-86.

[10] Deepali D. Rane and Dr.V.R.Ghorpade“ Multi-User Multi-Keyword Privacy Preserving Ranked Based Search Over Encrypted Cloud Data” International Conference on Pervasive Computing (ICPC), 2015.

[11] Zhihua Xia, Member, IEEE, Xinhui Wang, Xingming Sun, Senior Member, IEEE, and Qian Wang, Member, IEEE “A Secure and Dynamic Multi-keyword Ranked Search Scheme over Encrypted Cloud Data” IEEE TRANSACTIONS ON PARALLEL AND DISTRIBUTED SYSTEMS, VOL., NO.1,2015.

[12] Anju Chandran, Asso. Prof. P Krishna kumaranThampi,”Survey on Efficient Keyword Search Scheme over Encrypted Data on Mobile Cloud”,International Conference on Emerging Trends in Engineering & Management,2016

[13] https://www.wordstream.com/blog/ws/2011/05/25/keywords-vs-search-queries.

[14] https://www.quora.com/What-is-a-multi-keyword-search-and-a-single-keyword-search-What-is-the-main-difference-between-these-two