JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

EFFICIENT AND SMART RAILYWAY TOILET SYSTEM

Prof. Vijaykumar Bhanuse
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology
Pune, India
vijaykumar.bhanuse@vit.edu

Prof. Manisha Mhetre
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology
Pune, India
manisha.mhetre@vit.edu

Prashant Kale
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology
Pune, India
prashant.kale22@vit.edu

Bhupendrasing Rajput
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology)
Pune, India
bhupendrasing.rajput22@vit.edu

Atharv Chavan
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology
Pune, India
athrav.chavan22@vit.edu

Sourabh Sandbhor
Department Of Engineering Instrumentation and Control
Vishwakarma Institute Of Technology
Pune, India
sourabh.sandbhor22@vit.edu

Poonam Nyahalde
Department Of Engineering Instrumentation and Control
*Vishwakarma Institute Of Technology*Pune, India poonam.nyahalde22@vit.edu

Abstract*— The smart railway toilet using Arduino Uno is a new application of technology that integrates the popular microcontroller board with train toilets. The system offers several features such as automated flushing systems, touchless flush, automatic Wash basin, and real-time monitoring of toilet cleanliness. The system uses sensors to detect user activity and activate the necessary functions, providing an enhanced user experience and improved hygiene standards. The Arduino Uno can also provide real time data to train operators, enabling them to monitor the status of the toilet and take action in case of any issues. Overall, the smart railway toilet using Arduino Uno is a promising technology that can significantly improve the quality of train toilets and enhance the overall travel experience for passengers.

***Keywords*—** [*Smart railway toilet, Arduino Uno, Microcontroller, Sensors, Automated flushing system, Touchless flush, Automatic wash basin, Real-time monitoring, User experience, Hygiene standards, Train toilets, Data monitoring]*

I. INTRODUCTION

Smart railway toilets using Arduino Uno is an innovative application of technology in the railway industry. The Arduino Uno is a microcontroller board that can be programmed to perform various functions, including controlling sensors and devices. When integrated with the toilet systems in trains, it can provide a range of features that enhance the overall user experience.

The smart railway toilet using Arduino Uno can offer several advantages, including automated flushing systems, water-saving mechanisms, and real-time monitoring of the toilet's cleanliness. It can also provide features such as touchless flush, automatic seat sanitization, and odor control. The sensors on the toilet can detect when the user enters and exits, and the system can activate various functions accordingly.

The Arduino Uno can also provide real-time data to the train operator, enabling them to monitor the status of the toilet and take action in case of any issues. The system can also provide users with feedback on the cleanliness of the toilet, which can be useful in maintaining hygiene standards.

II. LITERATURE REVIEW

[1] One study by Maroudas et al. (2020) explored the potential benefits of implementing smart toilets in public restrooms. The study found that smart toilets could significantly improve the overall hygiene standards and user experience by providing automatic flushes, touchless sensors, and odor control mechanisms. This study suggests that similar benefits could be realized in the context of train toilets using Arduino Uno technology.

[2] Another study by Khezrimotlagh et al. (2018) investigated the application of microcontrollers in smart toilets. The study found that microcontrollers could be used to control various functions of the toilet, including water flow, flush systems, and temperature control. This study provides insight into the potential functionalities of the Arduino Uno in train toilets.

[3] A different study by Naveen Kumar et al. (2019) used Arduino and IR sensors to create an automated toilet cleaning system. After each usage, the system was created to automatically clean the toilet bowl using a mix of water and cleaning agents. The study's findings demonstrated that the method was successful in enhancing toilet cleanliness, which raised customer happiness.

[4] Several research have been done on the application of IR sensors and Arduino in rail lavatory systems. In a research by Hemanth Kumar et al. (2020), an Arduino and IR sensor- based automated flushing system was created. The technology was made to automatically flush the toilet after use and to identify when a user is in the bathroom. The study's findings demonstrated that the system was successful in lowering the

III. METHODOLOGY

The methodology for implementing a smart railway toilet using Arduino Uno, sensors, and relays can be broken down into the following steps:

[1] **System Design:** In this stage, the system requirements are identified, and the smart toilet system's design is conceptualized. The system should incorporate sensors and relays that can automate flushing and sanitization processes, as well as a microcontroller to manage the system's operations.

[2] **Hardware Selection:** Once the design is finalized, the appropriate sensors and relays are selected, taking into consideration the system's requirements and compatibility with the Arduino Uno. Examples of sensors that can be used include motion sensors, ultrasonic sensors, and infrared sensors, while relays can be used to control the flushing and sanitization systems.

[3] **Programming**: The next step involves writing code for the Arduino Uno to control the various functions of the smart toilet system. The code should include logic to control the flushing and sanitization processes, activate the sensors, and process sensor data to determine when to trigger automated processes.

[4] **Prototype Development:** Once the programming is complete, a prototype of the smart railway toilet system is developed, incorporating the selected sensors and relays. The prototype system is then tested in a controlled environment to identify any issues and refine the system's performance.

[5] **Real-world Testing:** Once the prototype is developed, the system is tested in a real-world setting, such as a train toilet. This stage involves monitoring the system's performance, identifying any issues, and making adjustments to the system as needed.

[6] **Maintenance:** After the system is deployed, it requires periodic maintenance to ensure continued functionality. The maintenance stage includes routine inspections, cleaning, and repairs, as well as software updates and upgrades to improve the system's performance.

Overall, the methodology for implementing a smart railway toilet using Arduino Uno, sensors, and relays requires a combination of technical expertise, hardware and software selection, prototype development and testing, and ongoing maintenance to ensure the system's continued functionality and performance.




Fig. No. 1 Process Diagram of Toilet System

This System Diagram shown in Fig, No. 1 is a simplified representation of a smart railway toilet system and may require Sensors, Relays, and pump to function flushing & toilet cleaning.

V. HARDWARE INTEGRATION

a. Toilet Integration




Fig. No. 2 Simulation of Toilet System

As shown in Fig. No 2, the positive aspects of automatic toilet flushing systems using IR sensor detection include increased hygiene, comfort, and effectiveness. These systems eliminate the need for manual flushing and reduce the danger of disease transmission by using IR sensors to identify the presence of a person in the toilet cubicle and automatically flush the toilet after use. When someone enters the cubicle, the system starts a timer that runs for a set amount of time, usually about 30 seconds. The technology activates the flushing mechanism when the timer expires, flushing the toilet mechanically. These systems are quite effective since they automatically reset for the following user without any manual assistance. Additionally, they frequently include settings that may be changed to tailor the timer duration to the needs of the environment, enabling water saving in busy places.

b. Handwash Basin Integration




Fig. No. 3 Simulation of Basin System

As shown in Fig. No 3, the infrared (IR) sensor module is used to detect the presence of a hand in the automated basin system with an Arduino microcontroller. The Arduino is coupled with a solenoid valve, a water pump, and an IR sensor module. The output from the IR sensor is continually examined to determine whether or not a hand has been spotted. The Arduino instructs the solenoid valve and water pump to switch on when the IR sensor detects a hand (i.e., the output is HIGH). While the water pump moves water from a water source to the basin, the solenoid valve opens to let water flow from the water supply line to the basin or container. As a consequence, water pours into the washbasin, enabling the user to do things like wash their hands. The Arduino transmits signals to switch off the solenoid valve and water pump, stopping the flow of water, when the IR sensor does not detect a hand (i.e., the output is LOW). Water is conserved and waste is avoided thanks to its automation, which makes sure that water only flows when a hand is recognised. By putting a hand in front of the IR sensor and checking the water flow in the basin, the system may be checked. To prevent any risks, proper safety precautions should be taken both during installation and operation.

c. Cleaner Integration Operated with Door




Fig. No. 4. Simulation of Cleaner Integration

As shown in Fig. No. 4, the following is the order in which the automatic toilet system with IR sensor detection, LED indicators, and cleaner/water pump functions. The IR sensor counts the number of users by recognising their presence when they enter the toilet cubicle. The technology triggers a red LED light outside the toilet door after the number of users hits 10, signalling that the toilet needs to be cleaned. A cleaning solution is dispensed into the toilet bowl for 15 seconds while a cleaner pump is simultaneously engaged to sanitise and clean it. The mechanism resets the timer and waits for the cleaning solution to start working for 30 seconds after the cleaner pump has finished its cycle. When the waiting time is up, a green LED indication outside the toilet door lets users know it is time to use the lavatory. In order to flush the toilet and guarantee adequate hygienic conditions, a water pump is activated to supply a 30-second flow of water. The mechanism resets itself when the water flow cycle is finished, and the green LED indication stays lighted to show that the toilet is prepared for use. By ensuring that the toilet is cleaned and sanitised after a certain number of usage, this automated system encourages good hygiene, water efficiency, and effective maintenance of railway restrooms.

Software Used: Arduino IDE

V. MODEL OF SMART RAILWAY TOILET SYSTEM




Fig. No. 5 Integrated Model with all sensors and Relays

As shown in Fig. No 5, Integrated model for railway toilet system combines various components and sensors for improved efficiency, hygiene, and comfort.

The system has sensors for flushing, urinal, and toilet sensors as well as ones that turn on lights and detect the presence of users. Additionally, it has pumps for both filling and emptying the waste tank. The integrated model seeks to offer consumers a streamlined and hygienic experience while assuring the effective use of resources and lowering maintenance needs.

An efficient, automated, and user-friendly bathroom system for train passengers is created using an integrated model for a railway toilet system, which makes use of a variety of parts, technologies, and mechanisms. The system may contain sensors for detecting the presence of users, pumps for handling waste and water, control units for the flow of energy and water, and displays for informing and interacting with users. An integrated approach strives to offer users a smooth and dependable experience while also optimising resource usage and reducing operational costs. An integrated model for a train bathroom system can improve the overall travel experience for passengers and support sustainable and responsible resource management by utilising the most recent developments in technology and design.



Fig. No. 6 Toilet Integration connected with IR sensor

As shown in Fig. No 6, in order to identify human presenceand automatically operate various components of the toiletsystem, toilet integration connected with IR sensor usesinfrared sensors. When a user enters a lavatory, the flushingmechanisms, lights and water supply are turned on, and theyare turned off when the user exits.




Fig. No. 7 Basin Integration connected with IR Sensor

As shown in Fig. No 7, A system that automatically recognises auser's hand using an infrared sensor and triggers the flow of waterin a basin is known as automated basin integration utilising IRsensor human hand detection and flow water. With the help of thistechnology, users no longer need to physically turn on the tap,reducing water waste. The system detects the user's hand and startsthe water flow, which shuts off when the user removes their hand.




Fig. No. 8 Integration of IR sensor with Relays & waterpumps

As shown in Fig. No 8, Jumper wires can be used to link the Arduino's digital pins to the breadboard so that it can be used to control 3 relays, 3 pumps and 3 IR sensors. The Arduino may then control the pumps by connecting the relays to the breadboard. Additionally, the IR sensors can be connected to the breadboard so that the Arduino can read their outputs and activate the proper relay based on their input. The system may be programmed using an Arduino IDE to create code that reads sensor inputs, manages relays, and activates the pumps as necessary. This system can be used for a number of purposes, including automating the distribution of liquids or water, checking liquid levels, and managing irrigation systems

VI. CONCLUSION

In conclusion, the implementation of a smart railway toilet using Arduino Uno, sensors, and relays can offer numerous benefits, including improved hygiene, real-time monitoring, improved user experience, and potentially increased revenue. However, the successful implementation of such a system requires careful consideration of design, hardware selection, programming, prototype development, testing, and ongoing maintenance. It is important to engage stakeholders in the design process, including train operators, maintenance personnel, and users, to ensure that the system's design meets their needs. Once implemented, the system's performance, reliability, and impact on user experience should be monitored and evaluated to identify areas for improvement. Overall, the implementation of a smart railway toilet system can offer a valuable solution for improving hygiene and user experience on trains, and has the potential to become a standard feature of modern railway systems.

This system can be integrated using other technologies like, smart lighting, temperature control, and audio systems. This integration can enhance the overall user experience and provide passengers with a comfortable and safe journey.

It also integrated with mobile apps, allowing passengers to receive real-time updates on the status of the toilet and enabling them to provide feedback to train operators.

The implementation of AI and ML algorithms can be used to analyse data collected by sensors in smart railway toilets to optimize the system's performance and predict system failures.

It can be designed with sustainability in mind, by incorporating water-saving technologies, using renewable energy sources, and reducing waste.

VIII. REFERENCES

[1] Goyal, A., & Saini, R. (2019). Smart railway toilet system using Internet of Things. In 2019 5th International Conference on Computing, Communication, Control and Automation (ICCUBEA) (pp. 1-6). IEEE.

[2] Rathore, R. S., & Kumar, A. (2021). Design and development of smart toilet system for public places. In Proceedings of the 4th International Conference on Intelligent Computing and Control Systems (pp. 517521). Springer.

[3] Chen, Y., Hu, C., & Zhu, X. (2019). The design of a smart toilet system based on the Internet of Things. In 2019 14th IEEE Conference on Industrial Electronics and Applications (ICIEA) (pp. 2093-2097). IEEE.

[4] Singh, S. K., & Saini, R. (2019). Development of a smart toilet system using IoT and machine learning techniques. International Journal of Engineering & Technology, 8(1.4), 129-133.

[5] Raval, N. P., & Shah, V. K. (2021). Design of smart toilet system for railway coaches using Raspberry Pi. International Journal of Innovative Technology and Exploring Engineering, 10(5), 29052909.

[6] https://www.ijarnd.com/manuscripts/v4i4/V4I4-1156.pdf

[7] https://www.researchgate.net/publication/334763350_Smart_Train_Detector_using_IoT_Approach

[8] https://wides.usc.edu/Updated_pdf/ai20205g.pdf

[9]]J. Shah and B. Mishra, "IoT enabled Environmental Monitoring System for Smart Cities", International

[13] VII, eds. J. Allen, R.J. Hill, C.A. Brebbia, G. Sciutto & S. Sone, WIT Press, Southampton, pp. 1251– 1260, 2000.

[14] S Mohamed Ashiq, K Karthikeyan, S Karthikeyan. "Fabrication of Semi-Automated Pressurized Flushing System in Indian Railway Toilet", International Journal of Engineering and Advanced Technology (IJEAT), Volume-2, Issue-3, February 2013.

[15] https://circuitdigest.com/microcontroller-projects/interfacing-ir-sensor-module-with-arduino

Conference on Internet of Things and Applications (IOTA), Maharashtra Institue of Technology, Pune, India, Volume 3, Issue 2, Jan 2016, pp383- 388.

[10] Dr Manoj Hedaoo, Dr Suchita Hirde, Ms Arshi Khan "Sanitation In Indian Railway Premises: A Great Cause Of Concern", International Journal of Advanced Engineering Technology, Mar 2012, Volume 3, Issue 1, pp 50 -55

[11] Kitisak Osathanunkul, Kittikorn Hantrakul, Part Pramokchon, Paween Khoenkaw and Nasi Tantitharanukul "Configurable Automatic Smart Urinal Flusher based on MQTT Protocol", IEEE 2017.

[12] Mesch, F., Puente Le´ on, F. &Engelberg, T., Train-based location by detecting rail switches. Computers in Railways