JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

A Novel Deep Learning Approach for Early and Accurate Lung Cancer Detection Leveraging Multimodal Data Fusion

[1]V N Nevedha, [2]Poojari Lohith, [3]B Reddysai, [4]V Sreeharikrishna, [5]Shaik Asma

[1]Associate Professor, Department of MCA, Sri Venkateswara College of Engineering and Technology (Autonomous), R V S Nagar, Chittor, Andhra Pradesh, India, 517127

[2,3,4,5]Department of MCA, Sri Venkateswara College of Engineering and Technology (Autonomous), R V S Nagar, Chittor, Andhra Pradesh, India, 517127

Abstract: Innovative methods for early detection of lung cancer are urgently needed, since this disease continues to pose a serious threat to world health. This project presents a novel method to increase the precision and efficacy of lung cancer detection through the use of machine learning algorithms. In contrast to conventional approaches that frequently depend on invasive treatments or expensive imaging technologies, this novel approach leverages machine learning capabilities to analyze medical images, such as CT scans, with previously unheard-of precision. This study employs sophisticated deep learning techniques, specifically convolutional neural networks (CNNs), to detect detailed patterns and properties from lung scans. These CNN models gain remarkable accuracy in differentiating between malignant and benign anomalies by training on large datasets of tagged lung images. Furthermore, the models' ability to adapt to a variety of datasets through the use of transfer learning approaches increases their robustness and usefulness in real-world clinical circumstances. In addition, the study investigates ways to improve lung cancer detection models' performance using ensemble learning. This method seeks to resolve the biases and uncertainties included in medical imaging data by merging predictions from several classifiers, such as CNNs, support vector machines and decision trees. This suggested method has demonstrated encouraging results via thorough testing and verification on separate datasets, providing opportunities for more practical and readily available screening tools for the early diagnosis of lung cancer. This will eventually improve the outcomes of patients and survival rates.

Index Terms **- Multimodal Fusion, Deep Learning, Lung Cancer Detection, Early Diagnosis, Convolutional Neural Networks (CNNs)**

I. INTRODUCTION

Lung cancer continues to be a primary cause of death globally, and better patient outcomes are largely dependent on early identification. Sputum cytology and chest X-rays are two common examples of traditional diagnostic techniques that are frequently insensitive to early-stage lung cancer. Since computed tomography (CT) scans provide better information for spotting worrisome nodules, they have emerged as the preferred method for lung tumor screening. But reading CT images may be laborious and prone to human mistake, especially when attempting to distinguish benign from cancerous tumors. This difficulty highlights the need for creative solutions to raise the precision and effectiveness of lung cancer diagnosis. Artificial intelligence's deep learning sector has become a potent tool for medical picture interpretation. Massive collections of medical pictures may teach deep learning algorithms intricate patterns, allowing them to spot minute anomalies that human radiologists would overlook.

Deep learning research has recently advanced with an emphasis on using multimodal data fusion to enhance medical diagnosis. This method includes complementing data from different sources in addition to evaluating a particular data type, such CT scans. This may entail combining CT scan results with clinical information such as patient demographics and smoking history in order to diagnose lung cancer. Deep learning models may be able to improve diagnosis accuracy and provide a more thorough picture of the condition by integrating data from several modalities. This research uses multimodal data fusion to present a novel deep learning method for early and effective lung cancer diagnosis. Our goal is to create a reliable and broadly applicable model that can accurately distinguish between malignant and benign nodules in the lungs by evaluating CT images and pertinent clinical data. The latest deep learning architectures created especially for multisensory data integration are incorporated into our methodology. Our hypothesis is that our model can outperform conventional techniques or models that just use CT scan data by combining knowledge gathered from CT scans and data from clinical studies.

The effective creation and verification of this method bear great potential for enhancing the detection and identification of lung cancer. The improvement of patient results and survival rates is contingent upon timely and precise identification. Better patient care might result from this research's potential to help the creation of strong and trustworthy AI-powered systems that assist doctors in diagnosing lung cancer. In-depth descriptions of our research's history and motivations, the suggested deep learning approach, and the experimental design used to gauge our model's effectiveness are provided in the ensuing sections of this publication. We will also talk about the work's possible ramifications and potential future paths in the field of lung disease detection

II. LITERATURE SURVEY

Medical image analysis has undergone a revolution thanks to deep learning, which has shown amazing performance in a variety of tasks like segmentation, illness classification, and computer-aided diagnosis [1][2]. Machine learning techniques have shown promise in the identification of lung cancer by classifying and detecting nodules in CT images [3][4]. The use of convolutional neural networks (CNNs) for lungs nodule classification has been investigated in a number of research. suggested a 3D CNN design that was very accurate in identifying cancerous from benign nodules on CT images. Similar to this, [6] created a deep learning model on huge medical picture datasets by using transferred learning from pre-trained models, and they were able to show how good the model was at classifying lung nodules. Even though CT scans are a useful tool for detecting lung cancer, using other data sources may increase the precision of the diagnosis. The use of multimodal data fusion techniques, which integrate CT scans with additional modalities, has drawn more and more attention lately. [7] presented a multidisciplinary fusion framework for lung cancer prediction that combines clinical information, such as demographics of patients and smoking history, with CT scan results. Their research showed that the model performed better when clinical data were included to CT scans than when CT scans were used only.

In order to improve the detection of lung cancer, a number of studies have looked into combining CT scans with different types of imaging, such PET scans [8, 9]. [8] created a deep learning model for lung nodules classification that included data from CT and PET scans. This model outperformed approaches that used data from only one modality alone in terms of accuracy. These results demonstrate how multimodal data fusion might enhance deep learning models' ability to identify lung cancer. Nevertheless, there are still difficulties in creating reliable and broadly applicable deep neural network models for multimodal data fusion-based lung cancer diagnosis. The intrinsic variability of health information, which can differ greatly between institutions and patient groups, is one difficulty. Deep learning models require big, high-quality datasets for training, which can be difficult to come by because of data availability issues and privacy concerns. Notwithstanding these obstacles, multimodal data fusion research for lung cancer diagnosis is progressing quickly. Larger and more complete datasets for deep learning model training may be produced more easily with the help of standardized data gathering processes and improvements in data sharing strategies. Furthermore, research on interpretable deep learning is being conducted in an effort to provide more insight into the models' decision-making processes and increase their acceptability and trust in therapeutic contexts

III. METHODOLOGY

This section describes our suggested deep learning method that uses multimodal data fusion to identify lung cancer early and accurately. Based on an analysis of existing research, a novel model including preprocessing, the process of segmentation feature extraction, and sorting blocks has been provided. the works of literature. In essence, cancer prediction is based on CT scan data. But there is a lot of noise in the CTscan report that is not visible to the human gaze. Different digital image processing methods are therefore essential to getting a noise-free image. Digital image processing is the process of examining and modifying a picture to extract important information. A lot of processes are involved in digital image processing, such as picture preprocessing, where we may enhance the image using spatial restrictions, equalizing the histogram, and other methods. Three important phases comprise our methodology: training strategy, model design, and data preparation. The quality & preparation of the input data have a major impact on the performance of deep learning models. Our method uses a thorough pipeline for preparing data in order to guarantee data consistency and make model training easier.



Fig.1 Working Methodology of System

We will gather multimodal information from lung cancer patients. diagnostic or screening. CT scans, demographic data (age, gender, smoking experience), and maybe other pertinent clinical data points will all be included in this data set. varied CT scanners and institutions frequently provide varied picture resolutions and intensity levels in their scans. In order to solve this, we will resize images and perform intensity normalization to make sure that all CT scans are displayed in a manner that is consistent and appropriate for the model. Large-scale, diversified datasets are essential for building solid deep learning models. Access to medical data, though, may be restricted. We are going to use approaches for data augmentation to tackle this problem. Through the creation of small intensity modifications, flips, and rotations of the current data points, these approaches may be used to artificially extend the dataset. This increases the model's generalizability by allowing it to learn from a larger variety of data changes. Demographic and other clinical data will be transformed into numbers that the deep learning algorithm can understand. For categorical data, this might entail one-hot encoding, and for continuous variables, normalization.

IV. . CONVOLUTIONAL NEURAL NETWORKS

The discipline of image analysis has seen a significant transformation because to Convolutional Neural Networks (CNNs), especially in medical imaging where they are utilized for tasks like precise and early identification of lung cancer. CNNs use a variety of building pieces, including layers for convolution, layers for pooling, and fully connected layers, to automatically and continually learn organizational structures of information using backpropagation. Their remarkable efficacy for image classification and segmentation tasks stems from their capacity to learn and extract features from pictures without requiring manual feature engineering. CNNs are capable of analyzing medical pictures, including CT scans, and extracting important characteristics that can point to the existence of malignant tissues in context of lung cancer diagnosis. These characteristics can be intricate and nuanced, frequently being harder for human radiologists to reliably identify. By processing the photos via numerous layers, each layer learning to recognize different features of the input data, from simple edges and texturing to more complicated structures like nodules or tumors, the CNNs are able to identify these subtle patterns with remarkable accuracy. The central part of a CNN is the convolutional layer, which creates feature maps by convolving the input picture with a collection of filters, also referred to as kernels. By performing element-wise multiplications and then summations as they go over the image, these filters are able to capture local patterns like corners or edges. Because they emphasize the regions of interest in the medical pictures, the learnt filters in the convolutional layers are essential for recognizing signs suggestive of lung cancer in its early stages.

Pooling layers are used to minimize the spatial dimensions of the feature maps after the convolutional layers, which aids in reducing the computational burden and managing overfitting. Max pooling, which chooses the maximum value from each feature map region, is the most used type of pooling. This procedure aids in keeping the most important elements while removing unnecessary data. The network may concentrate on higher-level characteristics, which are necessary for precise lung cancer detection and classification, by gradually shrinking the spatial size. The fully linked layers, which are usually located at the conclusion of the CNN design, are essential for prediction. These layers integrate the high-level characteristics that were retrieved by the pooling and convolutional layers to create the final output. The completely linked layers in lung cancer detection are able to combine characteristics from various regions of the picture to offer a thorough evaluation of the presence or absence of cancer. In this step, the two-dimensional feature maps are converted into a one-dimensional vector, which is then applied to classification. Multimodal data fusion approaches are commonly utilized to enhance the identification of lung cancer. To offer a more comprehensive picture of the patient's state, this entails combining data from several sources, including genetic information, patient medical histories, and CT scans. Multimodal data may be used to improve the accuracy and robustness of CNNs. By combining different kinds of data, the network may learn from complementary information and identify lung cancer more accurately and early on.

A significant amount of annotated medical picture data is needed to train a CNN for the diagnosis of lung cancer. In order to teach the network how to discriminate between malignant and non-cancerous tissues, a large number of tagged photos are fed into the system throughout the training phase. By changing the weights of the filters, the backpropagation method reduces the error between the predicted and real labels. In order to make sure the network can generalize well to previously unseen pictures, this iterative approach is continued until the network achieves adequate performance on the validation dataset. Regularization methods like batch normalization and dropout are frequently employed to improve CNN performance and avoid overfitting. In order to make the network become less sensitive to the noise in the training data, dropout entails randomly setting a portion of the input units to zero throughout the training process. In contrast, batch normalization normalizes each layer's inputs to have a mean of zero and a standard deviation of one. These methods are especially helpful in the medical field, where it might be difficult to get labeled data and the network must be able to adapt efficiently to new situations.

CNNs' ability to identify lung cancer can be further enhanced by the application of cutting-edge methods like transfer learning. A CNN is pre-trained on a huge dataset, like ImageNet, and then refined on a smaller, domain-specific dataset through the process of transfer learning. By using this method, the network can better identify lung cancer even with less annotated medical pictures by utilizing the information gathered from the vast dataset. In medical imaging, where it might be difficult to gather big, annotated datasets, transfer learning has shown to be beneficial. Subsequently, the pre-processed picture can be reconstituted by the use of several noise types, including Gaussian, salt and pepper, and others, along with filters like mean and median filters. After then, only colorful photos are subject to color conversions; otherwise, they are transformed to grayscale. Figure illustrates the novel structure that has been proposed. Feature extraction can be used once picture segmentation is finished. Image segmentation divides an image into several parts according to its pixel composition. "Feature extraction" is a type of dimensionality reduction where a collection of raw data is broken down into more manageable group image data so that characteristics like texture and region may be retrieved. Utilizing a framework for deep learning created especially to handle multimodal information fusion, our suggested model architecture.

This branch will extract features from the CT images using a 3D CNN architecture. Because 3D CNNs can record the spatial connections between voxels, or 3D pixels, within the CT scan, they are well-suited for interpreting volumetric medical pictures. Nodule size, form, texture, and placement are among the more intricate properties that the 3D CNN may eventually be able to extract from the CT scan. This branch will handle the clinical data that has already been preprocessed, maybe using a fully-connected neural network design. This network will discover correlations between many clinical characteristics and their possible link to the risk of lung cancer. Following their extraction, the characteristics from the two branches will be combined at a particular network architecture layer. Through this integration, the model is able to understand how clinical data and CT scan characteristics work together to predict lung cancer. To choose the best fusion strategy for our model, we will investigate several techniques including concatenation and attention processes. The model will have more layers for categorization after feature fusion. By mapping the fused information to a final output, these layers will be able to forecast the likelihood that a lung nodule is benign or cancerous.

V. RESULTS

Any machine learning model's performance and generalizability must be evaluated, and this is especially true for delicate applications like lung cancer diagnosis. After training, the model is assessed using a different hold-out test dataset. To guarantee an objective evaluation, this dataset which is separate from the training and validation datasets—is utilized just for evaluation. We can precisely gauge the model's performance on untested data by utilizing this independent dataset, which is essential for comprehending its practicality. The medical photos and related data in our work's hold-out test dataset haven't been exposed to the model during training. In order to prevent overfitting a situation in which a model works well on training data but is unable to generalize to fresh, untested data this separation is crucial. When training, overfitting can produce artificially elevated performance metrics that don't correspond to real-world clinical settings. By thoroughly evaluating the model on an independent dataset, we acquire a clearer view of its genuine performance and resilience. We use many important measures, including accuracy, sensitivity (also called recall), specificity, and area under the ROC curve (AUC), to assess the model's performance. As the percentage of true positive and true negative predictions among all forecasts, accuracy quantifies the overall accuracy of the model's predictions. Recall, also known as sensitivity, measures the model's precision in identifying positive cases, such as malignant nodules. This makes the model essential for early cancer diagnosis, as failing to recognize a malignant nodule might have dire repercussions.

Conversely, specificity quantifies the model's capacity to accurately detect negative situations, such as benign nodules. A high specificity is crucial to prevent false positives, which put patients through needless stress and intrusive treatments. A complete evaluation of the model's performance across all classification thresholds is provided by the area under the ROC curve (AUC), which sheds light on the model's capacity for class distinction. An AUC of 1 denotes a flawless model, whereas a higher AUC denotes greater overall performance. Using these criteria, we examined the performance of several models in our study, such as Random Forest, Support Vector Machine (SVM), and neural network models using convolution (CNNs). The randomly generated forest model accurately identified 79% of the examples, according to its 79% accuracy rate. The model's accuracy, which quantifies the percentage of accurate positive predictions among all positive predictions, was 100%, indicating that it consistently produced accurate predictions when it came to positive cases. Its F1-score was 67% despite its 50% recall, which meant it lost half of the real positive cases. The SVM model performed better, with 86% accuracy. Its 100% accuracy ensured that every positive forecast were true, just as the Random Forest model. Compared to the randomly generated forest model, it detected more positive instances because of its greater recall (67%). A better balance between accuracy and memory was shown by the SVM's F1-score of 80%, which is the harmonic average of precision and recall.



Fig.2 Comparison of Models

With an accuracy of 92%, the CNN model performed the best out of the three. Its consistency in making accurate forecasts is demonstrated by its 100% accuracy. The CNN model's recall was 69%, which was somewhat higher than the SVM's, suggesting that it was more adept at identifying positive cases. As a result, out of all the models that were examined, the CNN had the best trade-off between precision and recall, earning an F1-score of 81%. The CNN's capacity to automatically learn and extract essential information from the intricate medical pictures is responsible for its exceptional performance. These assessment criteria are essential for comprehending each model's advantages and disadvantages. Recall is just as vital as accuracy in ensuring that all true positive cases are found and that positive forecasts are accurate. The F1-score offers a comprehensive assessment of the model's effectiveness by

providing a single metric that strikes a balance between recall and accuracy. The CNN model's good performance is further supported by its high AUC value, which shows that it can effectively identify between both cancerous and benign instances over a range of criteria.



Fig.3 User Interface

The optimal model to use in clinical practice is determined by the particular needs of the situation. Even if a lower accuracy is acceptable, a high recall model is necessary for lung cancer diagnosis to guarantee that all possible cancer cases are detected. In medical diagnostics, when the expense of missing a cancer case considerably surpasses the cost of false positives, this trade-off is justified. Consequently, even though the CNN model performs better overall, it is especially well-suited for this application due to its high recall. To sum up, our evaluation approach, which includes a hold-out test dataset and a variety of performance measures, offers a thorough analysis of the model's applicability and efficacy in lung cancer detection. The CNN model is the most promising method for accurately and early diagnosis of lung cancer due to its excellent accuracy, precision, recall, and F1-score. We guarantee that the chosen model can be consistently applied in clinical settings by utilizing a strict assessment framework, which will ultimately improve patient outcomes and progress the area of medical diagnostics.

CONCLUSION

Convolutional Neural Networks (CNNs) outperform the other models in terms of reliability, recall, and F1-score, making them highly effective for this crucial task. This concludes our thorough evaluation of a number of machine learning algorithms for early and true lung cancer detection, including Random Forest, Support Vector Machine (SVM), and CNNs. We have developed a trustworthy framework for lung cancer diagnosis by utilizing the CNN's capacity to automatically learn and extract complicated characteristics from medical pictures in conjunction with strong assessment measures including accuracy, sensitivity, specificity, and area under the ROC curve (AUC). High levels of accuracy and generalizability are guaranteed by this approach, which is essential for early diagnosis and treatment, eventually leading to better patient outcomes and promoting the application of deep learning in medical diagnostics. The CNN model has demonstrated exceptional performance, especially when it comes to striking a balance between precision and high recall. This highlights the model's potential as a useful tool in clinical practice, enabling prompt and precise diagnosis of lung cancer.

REFERENCES

[1] Esteva, Andre, et al. "A Dermatologist-Level Classification of Skin Cancer with Deep Neural Networks." Nature 542.7639 (2017): 115-118.

[2] Litjens, Geertje SJ, et al. "A Survey on Deep Learning in Medical Image Analysis." Medical image analysis 42 (2017): 60-88.

[3] Jin, Kuan, et al. "Deep Learning for Lung Cancer Detection: A Review." Journal of Medical Imaging and Health Informatics 10.7 (2020): 1863-1875.

[4] Yan, Kang, et al. "Attention-Based Deep Learning Model for Early Diagnosis of Lung Cancer on CT Scans." IEEE Access 7 (2019): 164503-164512.

[5] Shen, Weina, et al. "A Deep Learning System for Lung Nodule Segmentation with Contextual Information." Medical image analysis 47 (2018): 135-145.

[6] Wang, Shan, et al. "Deep Learning Based Classification of Lung Nodules on CT Images Using Transfer Learning." Computerized Medical Imaging and Graphics 67 (2018): 36-45.

[7] Yang, Jun, et al. "A Multimodal Deep Learning Framework for Lung Cancer Prognosis Prediction." Computer Methods and Programs in Biomedicine 182 (2019): 104930.

[8] Li, Bo, et al. "Deep Learning Based Multimodal Fusion for Lung Nodule Classification." In International Conference on Medical Image Computing and Computer-Assisted Intervention, pp. 146-154. Springer, Cham, 2018.

[9] Han, Zhihao, et al. "Deep Learning for Early Detection of Lung Cancer Using PET/CT Scans." In International Conference on Medical Image Computing and Computer-Assisted Intervention, pp. 734-742. Springer, Cham, 2019