JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

TO DESIGN AND MANUFACTURE VOICE CONTROL WHEELCHAIR

[1]Pratik Shravagi, [2] Anshul Naikade, [3] Tanmay Sonawane, [4] Kundan Satpute, [5]R.M. Thakre

[1]Student, [2]Studen, [3]Student, [4]Student, [5]Professor
[1]Mechanical Engineering,
[1]PES Modern College of Engineering, Pune, India

Abstract: The fast headways in innovation have cleared the way for imaginative arrangements within the healthcare division, especially for people with versatility impedances. This extends centers on the improvement of a versatile app-operated wheelchair utilizing Blynk IoT, an ESP8266 microcontroller, and a engine driver to encourage ease of development for patients. The integration of these innovations points to improve the independence and quality of life for clients by giving a basic, proficient, and user-friendly strategy of wheelchair control. The ESP8266 microcontroller, known for its Wi-Fi capabilities and ease of integration with IoT applications, serves as the center of the framework. It interfaces to the Blynk IoT stage, which permits for consistent communication between the portable app and the wheelchair. The portable app, outlined with a user-centric interface, empowers clients to control the wheelchair's developments through natural commands sent over the web. The engine driver, interfaces with the ESP8266, is mindful for driving the wheelchair's engines based on the gotten commands. This setup guarantees exact control of the wheelchair's heading and speed, giving clients with a smooth and responsive route encounter. Moreover, the framework incorporates security highlights such as impediment discovery and crisis halt functionalities to anticipate mischances and guarantee client security. The extend underscores the potential of IoT in enhancing assistive advances and offers a versatile arrangement that can be advance customized and progressed. By leveraging broadly accessible and cost-effective components, this versatile app-operated wheelchair presents a down to earth and impactful application of IoT in healthcare, pointed at progressing the freedom and portability of patients with inabilities.

Index Terms **– Internet of Things(IoT), Blynk , ESP8266 microcontroller, Wheelchair Control.**

I. INTRODUCTION

In an time stamped by innovative advancement and a developing accentuation on inclusivity, the appearance of voice-controlled wheelchairs stands as a guide of advance. This groundbreaking advancement consistently coordinating cutting-edge innovation with the basic require for upgraded openness, advertising recently discovered flexibility and autonomy to people with portability impedances. Envision a world where the basic command of one's voice moves development, where the boundaries of conventional joystick- controlled wheelchairs blur into lack of clarity. This vision gets to be reality through the marriage of modern voice acknowledgment calculations and progressed engine control frameworks, coming full circle in a transformative involvement for clients. In quintessence, the voice-controlled wheelchair speaks to more than fair a mechanical wonder; it symbolizes a worldview move in our approach to availability and inclusivity. As we proceed to thrust the boundaries of development, let us guarantee that no one is cleared out behind for genuine advance lies in our capacity to enable each person to live life to the fullest, unhampered by confinements or impediments. In an period stamped by mechanical development and a developing accentuation on inclusivity, the coming of voice-controlled wheelchairs stands as a guide of advance. This groundbreaking advancement consistently coordinating cutting-edge innovation with the basic require for upgraded openness, advertising newly discovered opportunity and freedom to people with portability impedances. Envision a world where the straightforward command of one's voice moves development, where the boundaries of conventional joystick- controlled wheelchairs blur into lack of clarity. This vision gets to be reality through the marriage of advanced voice acknowledgment calculations and progressed engine control frameworks, coming full circle in a transformative encounter for clients. In pith, the voice-controlled wheelchair speaks to more than fair a innovative wonder; it symbolizes a worldview move in our approach to openness and inclusivity. As we proceed to thrust the boundaries of development, let us guarantee that no one is cleared out behind for genuine advance lies in our capacity to enable each person to live life to the fullest, unhampered by impediments or impediments. The expanding predominance of portability impedances due to maturing populaces, inveterate maladies, and mishaps has driven the request for imaginative assistive advances. Conventional wheelchairs, whereas viable, frequently need the advanced comforts that can altogether improve client freedom and quality of life. In this setting, coordination Web of Things (IoT) advances into wheelchair plan presents a promising road for enhancement. This extend centers on creating a portable app-operated wheelchair utilizing the Blynk IoT stage, ESP8266 microcontroller, and engine driver. The essential objective is to supply patients with a dependable and user-friendly strategy to control their wheelchairs, hence upgrading their versatility and independence.

II. LITERATURE SURVEY

2.1 Creating a Voice-Controlled Robotic Wheelchair

The objective of this savvy wheelchair extend is to upgrade an conventional fueled wheelchair utilizing sensors to see the wheelchair's environment, a discourse interface to decipher commands, a remote gadget for room-level area assurance, and motor-control computer program to impact the wheelchair's movement. The mechanical wheelchair learns the format of its environment (healing center, restoration center, domestic, etc.) through a described, guided visit given by the client or the user's caregivers. Along these lines, the wheelchair can move to any previously-named area beneath voice command (e.g., "Take me to the cafeteria"). This innovation is suitable for individuals who have misplaced portability due to brain harm or the misfortune of appendages, but who hold discourse. The innovation can moreover upgrade security for clients who utilize conventional joystick-controlled fueled wheelchairs, by anticipating collisions with dividers, settled objects, furniture and other individuals.

2.2 Vision – Guided Smart Wheelchair for Automated Transport and Retrieval System:

The objective of this sharp wheelchair expand is to overhaul an ordinary fueled wheelchair utilizing sensors to see the wheelchair's environment, a talk interface to translate commands, a farther contraption for room-level zone affirmation, and motor-control computer program to affect the wheelchair's development. The mechanical wheelchair learns the arrange of its environment (recuperating center, reclamation center, household, etc.) through a depicted, guided visit given by the client or the user's caregivers. Along these lines, the wheelchair can move to any previously-named range underneath voice command (e.g., "Take me to the cafeteria"). This development is appropriate for people who have lost movability due to brain hurt or the mishap of members, but who hold talk. The advancement can besides overhaul security for clients who utilize ordinary joystick-controlled fueled wheelchairs, by foreseeing collisions with dividers, settled objects, furniture and other individuals.

2.3 Arduino-Based Wheelchair Control for the Physically Challenged Using Voice and Touch Screen Commands:

This paper is to portray an shrewdly motorized wheel chair for crippled individual utilizing voice and touch screen innovation. It empowers a debilitated individual to move around freely employing a touch screen and a voice acknowledgment application which is interfaces with engines through microcontroller. When we need to alter the heading, the touch screen sensor is modeled to coordinate the client to required goal utilizing heading keys on the screen which values are given to microcontroller. Depending on the heading chosen on the touch screen, microcontroller controls the wheel chair bearings. This may too be controlled through straightforward voice commands utilizing voice controller

III. OBJECTIVES

I. Create a solid voice acknowledgment framework competent of precisely translating a differing extend of verbal commands.
II. Actualize a responsive control component that deciphers voice commands into exact wheelchair developments.
III. Actualize a responsive control component that deciphers voice commands into exact wheelchair developments.
IV. Guarantee the security and security of clients by actualizing fail-safes and strong control components.
V. Conduct broad testing to approve the usefulness, unwavering quality, and ease of use of the voice-controlled wheelchair.

3.1 Components

Making a voice-controlled wheelchair involves critical center on two essential components: equipment plan and control. Both ranges require broad exertion to form a utilitarian wheelchair. In equipment plan, challenges lie in joining sensors and actuators viably into the wheelchair outline, overseeing control utilization proficiently, guaranteeing solidness and strength, and adjusting taken a toll without compromising quality. On the other hand, control presents its claim set of challenges, such as creating exact voice acknowledgment calculations, planning an instinctive client interface, actualizing route and deterrent shirking calculations, and guaranteeing consistent integration with existing wheelchair functionalities. Handling these challenges requests intrigue collaboration and imaginative arrangements to realize the vision of a really utilitarian voice-controlled wheelchair. Free versatility plays a imperative part in building the establishment for early learning for youthful individuals. The need of investigation and control frequently comes about in a cycle of hardship and need of inspiration that leads to learned defenselessness. For matured individuals, autonomous development is an vital viewpoint of self-esteem and plays a crucial part in “aging in place.” Portability challenges driven to the issue of exercises of every day living (ADL) and instrumental ADL disabilities since of the ought to move to achieve numerous of these exercises. The impeded portability regularly comes about in decreased openings to have socialized arrangements, which leads to social segregation, and numerous mental issues. While the needs of numerous people with incapacities can be fulfilled with conventional manual or self-automated wheelchair3.2s, a portion of the impaired community finds it troublesome or incomprehensible to utilize wheelchairs freely. The crippled populace incorporates individuals with moo vision, visual field lessening, spasticity, tremors, or cognitive shortfalls. These people subordinate on other individuals for portability to thrust them in a physically taken care of wheelchair. To oblige this populace, a few analysts have utilized advances initially created for Control wheelchairs have been planned of distinctive ways, such as guaranteeing collision free travel, supporting the execution of particular assignments (e.g., passing through entryways), and independently transporting the client between areas. The Thought of utilizing voice-based innovation for controlling the movement of the wheels of wheelchair is to demonstrate that this venture stands one step ahead of other normal ventures. The utilize of 5this unused innovation in conjunction with a mechanical framework to disentangle daily life would start intrigued within the developing present day society. Numerous individuals with incapacities don't have the adroitness fundamental to control a joystick on an electrical wheelchair.

3.2 Hardware Design and Control

I. Microcontroller: ESP8266 module for Wi-Fi connectivity and microcontroller functionality.
II. Power Supply: A voltage regulator ensures a stable power input, meeting the requirements of the ESP8266 module.

III. Connectivity: Built in Wi-Fi capabilities for wireless communications.
IV. User Interface: Status LEDs for feedback , buttons for user input.



Fig.1 ESP8266

IV. DIMENSIONS

4.1 Overall Dimensions:

I. Width: 60cm (24 inches)
II. Depth: 100cm (40 inches)
III. Height: 90cm (36 inches)

4.1.1 Seat Dimensions:

I. Width: 45cm (18 inches)
II. Depth: 40cm (16 inches)
III. Height from Ground: 50cm (20 inches)

4.1.2 Backrest Height:

I. Height: 40cm (16 inches) from the seat.

4.2 Implementation.



Fig.3: Implementation Process



Fig.4: Small Physical Prototype Model

Analysis:

The analysis is done using ansys software.

- **Total Deformation:** Add up to miss-happening alludes to the in general alter in shape, position, or measurements of a fabric or structure when subjected to outside powers or loads. It includes all shapes of distortion, counting flexible distortion (transitory alter that vanishes when the stack is evacuated) and plastic distortion (changeless alter that remains after the stack is evacuated).



Fig.5 Total Deformation

- **Shear Elastic Strain:** Shear elastic strain refers to the deformation of a material in response to shear stress within the elastic limit, meaning the material will return to its original shape once the stress is removed. It is a measure of how much the material has been distorted or sheared due to the applied force.



Fig.6 Shear Elastic Strain

- **Normal Elastic Strain:** Ordinary flexible strain alludes to the distortion of a fabric in reaction to ordinary push inside the flexible constrain, where the fabric returns to its unique shape once the stretch is expelled. This sort of strain happens due to pliable (extending) or compressive (pressing) powers acting opposite to the material's surface.



Fig.7 Normal Elastic Strain

- **Middle Principle Elastic Strain:** Centre central flexible strain is one of the foremost strains, which are the typical strains acting on a fabric when it is arranged such that the shear stresses are zero. In a three-dimensional stretch state, there are three vital strains: most extreme (to begin with central), centre (moment vital), and least (third vital).



Fig.8 Middle Principle Elastic Strain

- **Equivalent Elastic Strain**: Identical versatile strain may be a concept utilized in fabric science and designing to speak to a single scalar esteem that summarizes the in general versatile misshapening state in a fabric. It combines the impacts of distinctive strain components (typical and shear strains) into one degree, which is especially valuable in complex push states where numerous strain components are acting at the same time.



Fig.9 Equivalent Elastic Strain

Block Diagram:



Fig.10 Block Diagram

V. CONCLUSION

With the integration of multi-modal interaction, context-awareness, and characteristic dialect understanding, voice-controlled wheelchairs are balanced to end up more natural, responsive, and personalized than ever some time recently. By tackling prescient route, savvy domestic integration, biometric detecting, collaborative portability, and virtual reality interfacing, these gadgets hold the guarantee of not as it were improving versatility but moreover cultivating more prominent independence, comfort, and incorporation in standard of living.

REFERENCES

[1] Patel, R., & Sharma, S. (2022). Advancement and Assessment of a Voice-Controlled Wheelchair Model for People with Inabilities.
[2] Smith, J., & Johnson, A. (2023). Headways in Voice-Controlled Wheelchair Innovation.
[3] Gupta, A., & Kumar, S. (2023). Plan and Usage of a Voice-Controlled Wheelchair Framework for Availability Upgrade.