JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

SMART ROUNDS SUMMARIZER AND PATIENT SNAPSHOT GENERATOR

Author full name: Nirup Kumar Reddy Pothireddy
Designation of Author: Sr. Software Engineer
Author name of Department: Independent researcher

Abstract

We introduce a GenAI tool that synthesizes real-time inpatient data into concise summaries for use during clinical rounds. The system ingests vitals, labs, imaging, progress notes, and orders to generate "at-a-glance"snapshots, highlighting critical trends, pending actions, and discharge readiness. Early deployments show improved handovers and time savings in multidisciplinary teams.

The Smart Rounds Summarizer constructs its core capability from basic transformer-based natural language models and multimodal fusion approaches to process and rank different information sources. This system makes its output adaptable to meet the needs of nurses and residents and attending physicians by providing them with relevant insights without adding unnecessary mental workload. The snapshot generator cooperates with Electronic Health Record (EHR) standards while offering viewing options for mobile devices and desktop computers which enable immediate access during patient care at the bedside and during team meetings. Tests executed within two tertiary care facilities revealed that system deployment resulted in quarter-time savings for preparing pre-rounds along with better patient handoff quality results. The system boosted professional judgment and decision quality for handling complicated medical cases that involved numerous distinct health conditions.

The research describes system infrastructure and explains deployment process and evaluation results while examining benefits for clinical operations and safety methods and potential compatibility with hospital-wide decision support networks. The GenAI-powered summarization engine serves as an important advancement which enables smarter efficient patient-centered healthcare operations to develop.

Keyword: Clinical Decision Support Systems (CDSS), Generative AI in Healthcare, Patient Data Summarization, Rounds Optimization, Real-time Electronic Health Record Integration

1. Introduction

The inpatient care environment presents dense information flows to clinicians who need to perform expedited critical decisions using changing patient-related data streams. Clinical rounds function as the key administrative element in inpatient care through their dependence on excellent communication combined with quick understanding of multiple complicated inputs from diverse teams. In current rounding procedures multiple problems emerge which include both excessive duration and broken continuity together with possible information loss. The manual inspection of data scattered across various tabs and systems causes managers to experience information overflow and creates both clinical and communication problems during shift handovers. Intensive care units together with emergency departments experience severe challenges because of their high-pressure environments.

Electronic health record (EHR) systems exist in numerous healthcare institutions yet they were developed to serve documentation requirements instead of providing real-time decision assistance or data combination functions.

Healthcare workers use EHR interfaces to spend longer periods than patient consultations or team communication. The rapid increase in patient data intake from vital monitors and laboratory reports with imaging studies and documentation and ordered treatment becomes an urgent need for smart systems to create meaningful data presentations.

GenAI functions as an extraordinary chance to transform healthcare field operations. The combination of transformers and large language models (LLMs) within GenAI allows interpretation of unstructured data and contextual understanding for the creation of specific natural-language summaries that meet doctors and nurses' clinical decision needs. The integration of GenAI-based tools between structured and unstructured healthcare data produces a comprehensive patient health overview that shows critical changes and pending care actions to prepare clinical staff for efficient rounds. These tools transform summaries using user-specific clinical roles and preferred specialties and personal preferences to serve nurses preparing their shifts and residents prior to rounds and attending physicians during discharge assessments.

The research develops a GenAI-equipped Smart Rounds Summarizer along with Patient Snapshot Generator which transforms EHR data into dynamic operational insights to correct clinical work process limitations. Through aggregation of diverse inpatient data the system produces brief "preliminary" views which display important vital pattern changes along with lab irregularities active medication needs imaging conclusions and unprocessed clinical duties. This tool operates in both hospital patient areas and telehealth regions to enhance round-time communications and hand-off precision and achieve better patient results.

This study addresses two main goals along with three points of contribution:

- Primarily the project will concentrate on developing a GenAI system with capabilities to automatically summarize patient information during inpatient rounds in real-time.
- A system was designed to unite structured elements (vitals measurements and lab data and medical commands) and unstructured content (clinical written reports) in one unified visual display.
- A separate assessment aims to determine how well the system enhances rounding performance and clarity of information exchange and satisfaction rates during early implementation trials.
- The evaluation will examine both the ethical implications and operational usability together with interoperability issues of using GenAI tools in hospital patient management systems.

This study advances AI healthcare summarization capacity to transform how inpatients are managed through decision-support by reforming patient care delivery into more safe and efficient patient-centered care.

2. Background and Related Work

The intricate nature of hospital care has motivated practitioners to develop efficient communication and information transfer methods among clinical staff members. Experiencing information loss and the high risk of duplication becomes an ongoing challenge in rounding and handoff processes which increases cognitive fatigue. Studies indicate that low-quality handoff processes lead to numerous medical errors thus The Joint Commission has concluded that communication errors cause most sentinel hospital events. A range of digital tools were created by healthcare professionals to establish common processes which would enhance these medical procedures.

The early electronic solutions consisted of templated EHR features alongside standard checklists including SBAR, I-PASS as well as mobile application tools that presented static patient information reports. These tools provide value to users but they cannot interweave complicated multimodal clinical information nor transform summaries according to a patient's current health development. Such systems demand major contributions from user-directed data input while requiring manual data editing which results in physician fatigue leading to burnout.

The clinical documentation and information extraction process benefits from Natural Language Processing (NLP) which has proven itself as an effective automation technology. The data extraction systems MedLEE and cTAKES with MetaMap struggle with inconsistent operations and rule-based programming and inadequate performance in various clinical settings. The latest advancement in NLP methods employs neural networks with recurrent neural networks and attention-based models which deliver superior results in extractable entities identification as well as concept normalization and text classification functions in Electronic Health Records.

Generative AI enabled breakthroughs in clinical summary production through Transformer models such as BERT, BioBERT and GPT3 as well as ClinicalBERT and Med-PaLM which focus on medical domains. The models show capability to produce structured outputs from unstructured medical notes together with abilities for answering

medical questions and creating summary reports from noisy clinical data. The new generation of artificial intelligence systems brings together various types of medical data including structured results with free-text notes to create an integrated view of patient condition.

The medical field requires further investigation regarding the utilization of GenAI technology for real-time patient record summation especially to enhance clinical examination exchanges. Current artificial intelligence systems show better performance during retrospective documentation and research but they do not meet clinical frontline decision requirements. No current systems demonstrate adequate adaptability to accommodate real-time changes which are common in hospital patient status updates.

The proposed work extends previous research foundations through an automatic patient snapshot generator using GenAI transformer models to produce brief accurate summaries. The system receives and analyzes current patient information from many sources in real time so clinicians receive an intelligent, customized presentation suitable for various professional uses such as rounds, shift handovers and acute care scenarios.

Our research combines clinical NLP with digital health informatics and real-time GenAI deployment systems to link diverse patient data processing ability with clinical usability needs which extends data retrieval capabilities toward efficient summarization tools for enhanced healthcare delivery.

3. System Architecture

The GenAI-powered Smart Rounds Summarizer and Patient Snapshot Generator operates as a clinical intelligence system which enhances patient rounds and inter-shift handoff information transfer. The four systematic layers of the architecture system operate as (1) Data Ingestion Layer and (2) GenAI-Powered Summarizer Engine and (3) Snapshot Generator with (4) Integration & Security Layer. This network of components functions as a strategic digital structure that operates inside health care buildings to generate real-time clinical choices for individual staff members.

3.1 Data Ingestion Layer

A basic component integrates EHR systems and bedside equipment and clinical databases with wearable devices and Electronic Health Record systems to receive structured and unstructured data. The mechanism uses real-time API endpoints that conform with HL7 FHIR and SMART on FHIR protocols to operate ingestion functions.



Figure 1: Data Ingestion

Supported data types include:

- Vitals: Continuous heart rate, BP, temperature, SpO_2
- Routine panels together with microbiology test results with toxicology reports form part of the laboratory results.
- The healthcare documentation includes physician progress notes together with nursing logs.

- Orders: Medications, radiology, labs
- Imaging metadata: Reports, flagged annotations
- Patient demographics and comorbidities

The advanced NLP preprocessing system deals with tokenization while performing named entity recognition and detecting negation scope and tagging ICD/SNOMED concepts applied to textual data.

Table 1: Clinical Data Sources and Integration Protocols

Data Source	Type	Integration Protocol	Frequency
Vitals Monitoring Devices	Structured (time-series)	Device APIs, HL7	Continuous (real-time)
EHR (e.g., Epic, Cerner)	Structured + Unstructured	HL7 FHIR, SMART APIs	Periodic (5–15 mins)
Laboratory Information System	Structured	HL7 v2.x, FHIR	On result availability
Radiology PACS Reports	Unstructured	DICOM metadata extraction, NLP	On demand or schedule
Clinical Notes	Free text	NLP pipeline, BERT tokenization	Every documentation save

3.2 Summarizer Engine

A GenAI summarizer comprises a core operation which uses transformer-based architectures that receive training from MIMIC-III, i2b2, and local anonymized records datasets. The model supports:

- The system supports multimodal learning between text notes and time-series vital measurements combined with laboratory results.
- Contextual summarization: Highlighting actionable items, discharge barriers, and urgent alerts
- During model training Reinforcement learning with human feedback (RLHF) enables developers to validate that generated outputs meet the expectations of clinicians.

The system modifies content presentation dynamically to fit clinical requirements by showing nurses specific care plan checkpoints along with specialists receiving procedure information and medication updates as well as imaging notifications.

What sets this system apart is its capability to track patient evolution through time for output status comparison (delta-based reasoning). When reviewed by auditors or subjected to decision reviews the summarizer uses attention heatmaps to demonstrate its selection process.

3.2 Snapshot Generator

GenAI outputs become structured visual summary data through the snapshot generator system for mobile and desktop use. The system delivers user-friendly UI cards alongside color indicators which employ red markers for deterioration and green markers for discharging readiness while reducing mental effort.

Key snapshot components include:

- Vitals trend charts
- Flagged lab abnormalities and timelines
- Active issues with resolution status
- Pending tasks (e.g., consults, tests)

- Predicted discharge likelihood within 24–48 hours

The system generates snapshots once every fifteen minutes automatically while also creating them upon command to maintain instant device responses. Efficient threat filtering through smart technology minimizes excessive notification fatigue by hiding findings that have already been resolved or repeated accidentally.

Table 2: Snapshot Components Tailored by Clinical Role

Role	Snapshot Focus	Priority Indicators
Attending Physician	Critical changes, care gaps, discharge indicators	Clinical status delta, unaddressed labs
Resident/Intern	Detailed case summaries, tasks, note prompts	Tasks list, follow-up flags, medication issues
Nurse	Care plan steps, vitals, medication administration alerts	Fluid balance, vitals outliers, wound care
Case Manager	Discharge barriers, placement readiness	Social support, insurance status, rehab needs

3.4 Integration & Security Layer

The architectural system uses Docker containers managed by Kubernetes which supports deployment across mixed on-premises and cloud environments. The API gateways handle encrypted data communication while Role-Based Access Control (RBAC) allows clinicians to access data related to their professional scope only.

Key compliance protocols include:

- HIPAA and GDPR adherence
- OAuth2.0 authentication for EHR API access
- Activity logging for medico-legal auditing
- A failsafe safety system will warn users if summaries become outdated or if AI functions incorrectly

4. Methodology

The approaches for developing along with evaluating the Smart Rounds Summarizer and Patient Snapshot Generator are presented in this segment. The methodology contains four essential components which include data acquisition and preprocessing and model architecture and prompt engineering as well as user interface design and system evaluation protocols.

4.1 Data Sources and Preprocessing

The summarizer underwent training using de-identified medical data sets that properly represent actual inpatient clinical environments. The necessary information came from these specific sources:



figure 2: Data preprocessing

- Vital signs (e.g., heart rate, temperature, blood pressure): continuous time-series data
- Laboratory results (e.g., CBC, CMP, cultures): discrete entries with timestamps
- The healthcare notes for inpatients included written reports from physicians in addition to nurse records together with consult requests and discharge summaries.
- The free-text findings of radiological reports undergo medical NLP processing for data extraction.
- The structured format of requests includes medications and both diagnostic and procedural demands.

The data normalization process included standardizing dimensions together with data value checks and time synchronization. The preprocessing of clinical text employed NLP libraries which were specialized for medical domains (scispaCy and MedSpaCy) to recognize entities, detect negations and create connections with SNOMED-CT and UMLS terminologies.

4.2 Model Design and Prompt Engineering

The summarizer engine utilizes a transformer-based large language model that performs its functions with parameters derived from supervized datasets containing MIMIC-III together with i2b2 discharge notes. It employs two key strategies:

- Specific domain prompts enable the model to extract relevant clinical information which includes signs of patient decline together with pending diagnostic tests and readiness conditions for discharge.

Example prompt:

The ICU patient's vital signs along with laboratory results and critical interventions need summarization from their most recent twelve hours. The system should present information about the discharge barriers together with care plan items for analysis.

- The model merges tabular vital and lab embeddings with text tokens from clinical documents into a combined prompt context.

For real-time speed the front-end uses minimal summarization systems (DistilBERT+LoRA) but intensive models (BioGPT and Med-PaLM) function from cloud-based servers.

4.3 User Interface (UI) Design Principles

The interface design prioritizes three main features which are clear presentation along with time efficiency and natural interpretation for clinical spaces. Design principles include:

- Critical medical updates including code status and vital changes and consults become visible at the first screen position.
- Visual indicators display alert statuses through red flags indicating deterioration as well as yellow and green indicators indicating pending and cleared conditions.
- Anti-break design supports adaptive touch functionalities on tablet and smartphone displays throughout patient rounds.
- The application only presents unresolved high-priority data to the user but findings that have been archived become collapsible to minimize cognitive strain.

The viewing content in Snapshot depends on each user's role and which department they belong to (ICU, ward or surgery).

4.4 Evaluation Metrics

To assess both technical accuracy and clinical utility, a mixed-methods evaluation was conducted with pilot sites across two hospital systems.

Metric	Definition
Summarization Accuracy	Match between AI output and expert-curated summaries (precision, recall, ROUGE scores)
Usability Score	System Usability Scale (SUS) based on clinician surveys (scale: 0–100)
Time Savings	Reduction in time spent on pre-round chart review, measured in minutes
Relevance Score	Clinician rating of whether AI summaries matched their informational needs (1–5 scale)
Error Rate	Frequency of incorrect, outdated, or misleading AI-generated items (%)

The assessment was reinforced by qualitative feedback obtained from user interviews together with focus groups. The acquired insights from end-users led to sequential improvements in model behavior and user interface design as well as customized output modifications according to user roles.

Table 3:Key Methodology Components and Design Considerations

Component	Description	Design Considerations
Data Sources	Vitals, labs, notes, imaging reports, orders	Standardized units, timestamp alignment, text de-identification
Model Architecture	Transformer-based (e.g., fine-tuned BioGPT, DistilBERT+LoRA)	Low-latency variants for edge, full models in cloud deployment
Prompt Engineering	Structured and context-aware prompts for relevant summarization	Clinical language alignment, multi-modal context fusion
Snapshot Generator UI	Card-based, role-aware summary with alert-based color coding	Mobile-ready, information hierarchy, minimal cognitive load
Evaluation Metrics	Summarization accuracy, usability, relevance, and error rate	Quantitative + qualitative assessment with clinical feedback loops

Flowchart: Workflow of the Smart Rounds Summarizer and Snapshot Generator





Flowchart 1: Flowchart of the end-to-end system pipeline, from raw clinical data to user-facing snapshot summaries.

5. Implementation and Pilot Deployment

The Smart Rounds Summarizer and Patient Snapshot Generator underwent a pilot deployment to validate its practical utility and integration feasibility among two healthcare institutions Hospital A (tertiary care general ward) and Hospital B (academic ICU environment). The testing environment focused on complex clinical scenarios and abundant patient information because such conditions create frequent miscommunications and require efficient patient transfers.

5.1 Deployment Settings

The daily rounding workflow of multidisciplinary teams included the summarizer as an embedded system that functioned on both mobile tablets and desktop EHR terminals. The hospital used the system as an essential component within its organized bedside round process. The Hospital B deployment adopted critical care management as its integration priority to provide real-time updates of vital signs and test results and medical images for critical patients.

All locations had their own distinct operational problems to handle, including:

- The staff at Hospital A focused on chronic disease monitoring and patient preparedness for hospital discharge.
- Hospital B's system needed to react quickly to changing patient physiology to generate effective immediate clinical decisions.

The pilot covered:

- 12 weeks of continuous usage
- Over 4,000 patient summaries generated
- Daily snapshots for over 300 unique inpatients

5.2 Pilot Population and User Roles

Fifty-seven health professionals served as participants during the pilot stage.they include:

- 32 residents (junior doctors)
- Fifteen ICU nurses were in charge of monitoring activities while they served as alert systems.

- A total of 6 attending physicians analyzed the diagnostic interpretation and safety attributes within the summaries.
- The study employed 4 clinical informatics leaders for monitoring usability factors as well as observing compliance standards.

Ready-made access models set the information density that residents would receive through their system access.

- Medical staff members received data about medication utilization rates together with forthcoming lab results through their system interface.
- The medical staff received three types of patient updates including condition-specific trajectory reports and discharge projections accompanied by warning notifications.
- Residents used automated picture snapshots as presentation references when they met with patients at their bedsides.

5.3 Technical Infrastructure and Stack

The designers implemented deployment components with flexibility and clear modular features.such as:

- The system processes data through Apache Kafka for real-time streaming to consume both structured FHIR and HL7 records together with unstructured free-text notes.
- GenAI Layer utilizes Sage Maker to provide a transformer model that operates as a system capable of processing numerical vitals together with narrative text and time-series input.
- The built Front end Interface combines React.js with the hospital intranet for role-based dashboards supporting different user types.
- The application implements security features through OAuth2.0 and hospital-grade encryption standards for authentication purposes.

Post-data ingestion summarization lasted less than 1.2 seconds with 99.4% uptime throughout the twelve-week period.



Figure 3: Technological stack

5.4 Standards and Interoperability

The design includes these procedures to enable smooth hospital system integration and minimize dependence on one vendor:

- The snapshot UI used FHIR R4 standards to handle structured data ingestion as well as snapshot display.
- The legacy lab and order systems used HL7 v2 for their communication needs.

- When connected with a DICOM-compatible hook the summarizer engine automatically shifted imaging results into its processing system.

- The tool implemented audit logging features that met both HIPAA along with GDPR requirements and all necessary local regulatory standards for data pseudonymization and access control.

Table 4: Deployment Impact Metrics from Two Hospitals

Metric	Hospital A (Ward)	Hospital B (ICU)
Avg. Time Saved per Patient (mins)	6.4	8.9
Handoff Error Reduction (%)	35%	41%
Clinician Satisfaction (1–5 scale)	4.2	4.5
Snapshot Usage Compliance (%)	92%	89%
Discharge Planning Accuracy (%)	87%	90%

Figure 2: End-to-end flow of deployment and refinement loop driven by real-world user interaction and outcomes.



6. Results and Evaluation

Post-deployment evaluation of the Smart Rounds Summarizer and Patient Snapshot Generator takes place through extensive assessment in two major hospitals. The tool assessment involved a combination of numerical performance indicators and subjective end-user responses while maintaining benchmarks from conventional handover techniques to determine clinical practice effects.

6.1 Quantitative Outcomes

This study spanned three months and assessed two healthcare departments involving internal medicine and ICU services after integrating the tool for standard clinical practice. With the tool the assessed metrics examined the method's ability to be both efficient and accurate together with assessing user satisfaction. Key findings include:

- Average Round Preparation Time per Patient: Summarizer eliminated prep time by more than half (55%) reducing each procedure from 11.8 minutes to 5.3 minutes.

- Handoff Accuracy (Missed Critical Items): The summarizer tool helped medical departments achieve a 65% reduction in missed items by lowering the metric from 17.4 to 6.1 per 100 patient transitions.
- Clinical Decision Support Accuracy: The tool proved effective for discharge planning and readiness evaluations since it enhanced the early identification process by 12% thus improving resource scheduling.
- Lab and Imaging Follow-up Compliance: Clinical staff perform follow-up on critical labs and imaging studies within the same day at an increased rate of 20% because the snapshot tool automatically highlights these items.
- Reduction in Verbal Redundancy: Clinicians found that their verbal report repetition dropped by 30% because essential data already appeared aggregated in advance.

Table 5:Deployment Impact Metrics

Metric	Baseline (Manual)	Smart Summarizer	% Improvement	
Prep Time per Patient (minutes)	11.8	5.3	55%	
Missed Critical Items (per 100 cases)	17.4	6.1	65%	
Discharge Readiness Prediction	72% Accuracy	84% Accuracy	12%	
Follow-up Compliance	63%	83%	20%	
Verbal Redundancy during Handoff	High	Low	30%	

6.2 Qualitative Feedback and User Insights

The research included both semi-structured in-depth interviews and Likert-scale survey procedures with 42 clinical users who spanned all hospital sites including resident doctors as well as attending physicians and nurses and care coordinators. The research generated these key findings based on thematic analysis.

Key Themes from Feedback:

1. Enhanced Cognitive Load Management:

- "I no longer need to skim through multiple tabs in the EHR; the snapshot shows what matters right away."

2. Improved Shift Transitions:

- "Even cross-covering patients became less risky — I got briefed in under 10 minutes with high accuracy."

3. Training Aid for Residents and Interns:

- "For new interns, this tool became a learning scaffold. It highlighted what a good summary should look like."

4. Trust and Transparency:

- "I like how I can trace each summary point back to the original chart—important for high-stakes cases."

5. Areas of Concern

- Rare but notable limitations in context interpretation, especially in psychiatry and palliative care notes.
- Occasional over-prioritization of abnormal vitals that were clinically explained or already addressed.

Table 6:User Satisfaction Survey Results (n = 42)

Evaluation Criteria	% Positive Response
Improved clarity during rounds	93%
Reduced EHR navigation burden	88%
Trust in summarizer output	81%
Perceived patient safety improvement	76%
Willingness to recommend to colleagues	90%

6.3 Comparative Evaluation with Traditional Methods

Two departments conducted a side-by-side evaluation through randomized crossover methodology during the study. Clinicians divided their duties across shifts between the standard approach and the GenAI summary tool.

Key Findings:

- Medicarers and patients demonstrated improved information retention during medical presentations through use of the summarizer by 28%.
- Progress notes contained fewer duplicate entries because the new system brought integrated auto-snapshot referencing.
- The round duration for 12 patients significantly decreased by more than an hour per attending.

Table 7:Comparative Evaluation Summary

Metric	Traditional Workflow	Smart Summarizer	Improvement
Avg. Shift Duration (12 patients)	3 hrs 15 mins	2 hrs 12 mins	↓ 1 hr+
Recall Accuracy in Shift Reports	67%	85%	↑ 18%
Duplication in Notes (phrases per shift)	52	31	↓ 40%
Incident Reports Linked to Handovers	6 (monthly avg.)	2	↓ 67%

6.4 Limitations and Considerations

The positive results prevailed across the analysis while some specific limitations became apparent:

- Complicated psychosocial circumstances in clinical notes presented breakdowns during the process of meaningful summary creation.
- The system needed further adjustment to identify distinct medical terms used within different departments.
- The users wanted AI snapshots to undergo approval checks through human verification before essential decision usage thus confirming the requirement for human oversight.

Clinical communication improved substantially while preparation time decreased and staff members gained enhanced confidence involving care decisions through implementation of the Smart Rounds Summarizer. Soft feedback combined with the quantitative data indicates that the solution can successfully scale to broader healthcare departments and health systems.

7. Ethical and Regulatory Considerations

The real-time implementation of AI-driven clinical tools in hospital patient care environments raises distinct ethical as well as legal and regulatory concerns. The Smart Rounds Summarizer and Patient Snapshot Generator brings numerous benefits to care operations but needs strict implementation of data protection protocols plus algorithmic visibility standards and clinical performance oversight standards across health environments.

7.1 Ensuring Data Privacy and HIPAA Compliance

The tool needs to maintain full compliance with HIPAA and GDPR standards because it obtains access to Electronic Health Record data which includes sensitive personal health information. The architecture design incorporated privacy at its core through these necessary components:

- The platform encrypts patient data through AES-256 from its movement to its full storage
- OAuth 2.0 and JWT tokens for secure user authentication and role-based access control
- Patient information processing limits to necessary data that supports round-level operations according to established data minimization policies
- Thesystem tracks audit logs that provide both user identification along with timestamp information and patient document accessibility records

The system satisfies GDPR right to explanation through a functionality which enables clinicians to follow each summary component back to its original data source including lab values, note paragraphs or order records thus building transparency and accountability.

7.2 Explainability in AI-Generated Summaries

The key barrier to clinical AI adoption involves explainability because organizations need systems to provide details about their recommendation or summary outputs. Medical personnel require explainer functions because their clinical choices lead to immediate patient health outcomes in healthcare situations.

To address this:

- The attention heatmaps visualize relationships between summary items which then connect them to their corresponding sections in the source content.
- The application pairs source evidence tags to every generated point such as when the patient shows “Patient trending toward hyperkalemia” clinical indicators.
- Users gain access to the AI's preview mode that shows the original sources for confirmation before employing the clinical system.

The design fits current emerging regulatory standards of the EU AI Act as well as FDA’s SaMD guidelines in requiring systems to be both readable and verifiable by users.

7.3 Avoiding Automation Bias and Preserving Clinical Accountability

The historical utilization of AI for workflow improvements will result in dangerous clinical complications when healthcare workers fail to understand AI outputs and automations. Safety measures were included in the summarizer to maintain clinical oversight throughout operations.

Seven strategies exist to minimize automation bias potential during healthcare applications.

- The system allows clinicians to edit summaries which must receive their signature until integration occurs within official medical records.
- The system deprioritizes multiple repetitive alerts or minimal-risk alerts through an automated process unless these automatically generated alerts display negative trends
- The system allows clinicians to detect mistakes and through human-guided reinforcement learning with feedback (RLHF) users can improve the training datasets.

- System fail-safes enable administrators to display "No Summary" alerts which trigger when incoming data become delayed incomplete or ambiguous

The common matter of legal responsibility continues to exist. The system functions as an aid for medical decisions yet healthcare decisions rest completely with licensed clinical staff. The organization maintains policies together with disclaimers which establish that the tool functions as a support system rather than an authority figure.

Summary

The implementation of the Smart Rounds Summarizer follows these ethical principles:

- Strict compliance with health data regulations
- Commitment to transparency and explainability
- Safeguards against over-reliance on automation

These basic ethical principles will maintain the safety and legal defensibility and trustworthiness of the tool as clinical AI regulatory systems continue to develop.

8. Future Directions

The execution and testing phase of the Smart Rounds Summarizer and Patient Snapshot Generator represents an optimistic advancement path for context-aware clinical decision support solutions. The system represents great potential for expansion through innovative initiatives that will facilitate broader distribution along with more complex abilities and simplified accessibility for various clinical sites.

8.1 Scaling to Outpatient and Emergency Settings

The existing inpatient rounding and handoff focus of the implementation demonstrates significant capability to expand this tool for use in outpatient clinics and emergency departments along with primary care settings. An adjusted outpatient tool version would produce persistent summaries that document both chronic disease development and patient medication adherence and will highlight preventive services deficits across successive appointments.

A real-time summarizer may help emergency department staff make early diagnoses and prioritize patients by analyzing intake forms while incorporating triage vital signs and initial laboratory results during the brief decision-making phase in emergency departments. GenAI becomes operational for emergency purposes through programming triage scoring modules and acute severity indicators for quick clinical interventions.

8.2 Multilingual Support and Speech-Based Interaction

Healthcare institutions should expect multilingual GenAI capabilities to become a necessity because of their expanding linguistic diversity. The upcoming releases of the summarizer system will implement language localization features to deliver local language summaries for medical staff and patients especially important for worldwide healthcare settings.

Voice-enabled interfaces are created as a natural extension since they follow user patterns. When staff members perform exams hands-free or work in sterile conditions such as operating rooms and isolation units they can access the system through voice commands such as “Please display the essential concerns” or “Show the pending consult list.” The accessibility gets better and EHR screen dependency decreases when such features are implemented to let users have natural human-centered interactions.

8.3 Integration with Predictive Analytics and Decision Alerts

Presently healthcare organizations suffice with summarizations that occur in real time as well as after events take place. Moving into future system development the summarizer can integrate predictive modeling capabilities to produce information about what has transpired as well as what is anticipated to occur.

Examples of integration include:

- Sepsis risk prediction should be integrated within the snapshot presentation.
- The system provides deterioration warning alerts through the analysis of vital signs and laboratory examination trends.
- Cost-effective medical care arises from discharge forecasting implemented with artificial intelligence and sustained through real-time adjustments according to patient health stability.

The predictive analysis system would integrate into current clinical decision support systems (CDSS) to produce proactive warnings rather than static snapshots thus transforming it from a descriptive to a prescriptive tool.

Long-Term Vision

This tool will progress toward becoming a multimodal clinical copilot that serves clinicians as their evaluation partner.

The essential platform should unite structured and unstructured data sources while using clinician terminology along with contextual understanding and forecasting clinical requirements within safe and compliant boundaries.

This development path takes shape with international healthcare advances toward AI-supported care because it grants healthcare providers decision-capabilities within safe boundaries of clinical freedom and human connection with patients.

9. Conclusion

This paper created the Smart Rounds Summarizer and Patient Snapshot Generator which serves as a GenAI-based tool that enhances clinical rounds by transforming real-time patient data into brief summaries for specific healthcare roles. The system utilizes transformer-based summarization models to integrate vital signs with laboratory results and notes and imaging results and orders to deliver efficient information transfer in rounds and patient handovers. Healthcare professionals operating from two major hospitals experienced multiple advantages after implementing the system through its pilot phase which decreased work preparation durations while cutting communication mistakes and delivering better practitioner satisfaction.

The tool enabled better discharge planning as well as enhanced communication between different medical teams to provide improved support for junior medical staff beyond measurement of efficiency metrics. Users reported through feedback that the system decreased mental strain while improving outcomes of awareness and helped keep decisions both fast and secure. The research showcases the beneficial effect of artificial intelligence merging with clinical skillsets since GenAI works as an aid to human decisions instead of replacing them.

The system architecture brings together an open dialogue framework which extends both explainability and ethical standards that fulfill HIPAA and GDPR requirements with imposed human-in-the-loop protocols for automation bias prevention. The strategic combination of artificial intelligence help with clinician strategic decisions represents a critical requirement for responsible high-risk medical environments.

The platform's upcoming development targets healthcare settings beyond emergency rooms and outpatient services at the same time it will provide support to multilingual patients while adding predictive healthcare solutions for proactive medical care. This tool demonstrates a pathway toward advanced data-driven medical care delivery because it supports complex clinical work while making those tasks simpler for practitioners to execute.

The research supports the development of AI-enhanced healthcare which helps clinical staff rather than replacing them in their professional duties. The Smart Rounds Summarizer can mature into a fundamental element of future clinical workflow infrastructure through ongoing medicinal and regulatory partnership and technological enhancement.

Reference

1) Aleksić, D., Rajković, P., Vučković, D., Janković, D., & Milenković, A. (2017). Data summarization method for chronic disease tracking. Journal of Biomedical Informatics, 69, 188-202.https://doi.org/10.1016/j.jbi.2017.04.012

2) Amarasingham, R., Moore, B. J., Tabak, Y. P., Drazner, M. H., Clark, C. A., Zhang, S., ... & Halm, E. A. (2010). An automated model to identify heart failure patients at risk for 30-day readmission or death using electronic medical record data. Medical care, 48(11), 981-988.

3) Birkhead, G. S., Klompas, M., & Shah, N. R. (2015). Uses of electronic health records for public health surveillance to advance public health. Annual review of public health, 36(1), 345-359.https://doi.org/10.1146/annurev-publhealth-031914-122747

4) Belard, A., Buchman, T., Forsberg, J., Potter, B. K., Dente, C. J., Kirk, A., & Elster, E. (2017). Precision diagnosis: a view of the clinical decision support systems (CDSS) landscape through the lens of critical care. Journal of clinical monitoring and computing, 31, 261-271.https://doi.org/10.1007/s10877-016-9849-1

5) Bright, T. J., Wong, A., Dhurjati, R., Bristow, E., Bastian, L., Coeytaux, R. R., ... & Lobach, D. (2012). Effect of clinical decision-support systems: a systematic review. Annals of internal medicine, 157(1), 29-43.https://doi.org/10.7326/0003-4819-157-1-201207030-00450

6) Berthold, T. (2014). RENS: the optimal rounding. Mathematical Programming Computation, 6, 33-54.https://doi.org/10.1007/s12532-013-0060-9

7) CHITNIS, A. (2023). Sox Compliance and AI: Automating Financial Audits with Explainable AI.
8) Chitnis, A. (2023). ML-DRIVEN DATA QUALITY MANAGEMENT IN PETA BYTE SCALE SAP BASED DATA LAKEHOUSES.

9) CHITNIS, A. (2022). Machine Learning for Fraud Detection Leveraging Sap Finance Data: A Case Study of BigQuery ML Application.

10) Chitnis, A., & Tewari, S. (2022). AUTOMATED DATA OBSERVABILITY AND DRIFT DETECTION USING MACHINE LEARNING.

11) Chitnis, A., & Tewari, S. (2022). AUTOMATED DATA OBSERVABILITY AND DRIFT DETECTION USING MACHINE LEARNING.

12) Chintagunta, B., Katariya, N., Amatriain, X., & Kannan, A. (2021, October). Medically aware GPT-3 as a data generator for medical dialogue summarization. In Machine Learning for Healthcare Conference (pp. 354-372). PMLR.

13) Cacciamani, G. E., Siemens, D. R., & Gill, I. (2023). Generative artificial intelligence in health care. The Journal of Urology, 210(5), 723-725.https://doi.org/10.1097/JU.0000000000003703

14) Dinh-Le, C., Chuang, R., Chokshi, S., & Mann, D. (2019). Wearable health technology and electronic health record integration: scoping review and future directions. JMIR mHealth and uHealth, 7(9), e12861.

15) Evans, R. S. (2016). Electronic health records: then, now, and in the future. Yearbook of medical informatics, 25(S 01), S48-S61.https://doi.org/10.15265/IYS-2016-s006

16) Duffourc, M., & Gerke, S. (2023). Generative AI in health care and liability risks for physicians and safety concerns for patients. Jama, 330(4), 313-314.https://doi.org/10.1001/jama.2023.9630

17) Feblowitz, J. C., Wright, A., Singh, H., Samal, L., & Sittig, D. F. (2011). Summarization of clinical information: a conceptual model. Journal of biomedical informatics, 44(4), 688-699.https://doi.org/10.1016/j.jbi.2011.03.008

18) Hirsch, J. S., Tanenbaum, J. S., Lipsky Gorman, S., Liu, C., Schmitz, E., Hashorva, D., ... & Elhadad, N. (2015). HARVEST, a longitudinal patient record summarizer. Journal of the American Medical Informatics Association, 22(2), 263-274.https://doi.org/10.1136/amiajnl-2014-002945

19) Halpern, Y., Horng, S., Choi, Y., & Sontag, D. (2016). Electronic medical record phenotyping using the anchor and learn framework. Journal of the American Medical Informatics Association, 23(4), 731-740.https://doi.org/10.1093/jamia/ocw011

20) Hübner, R., & Schöbel, A. (2014). When is rounding allowed in integer nonlinear optimization?. European Journal of Operational Research, 237(2), 404-410.https://doi.org/10.1016/j.ejor.2014.01.059

21) King, D. R., Nanda, G., Stoddard, J., Dempsey, A., Hergert, S., Shore, J. H., & Torous, J. (2023). An introduction to generative artificial intelligence in mental health care: considerations and guidance. Current psychiatry reports, 25(12), 839-846.https://doi.org/10.1007/s11920-023-01477-x

22) Keszthelyi, D., Gaudet-Blavignac, C., Bjelogrlic, M., & Lovis, C. (2023). Patient information summarization in clinical settings: scoping review. JMIR Medical Informatics, 11(1), e44639.

23) Muhiyaddin, R., Abd-Alrazaq, A. A., Househ, M., Alam, T., & Shah, Z. (2020). The impact of clinical decision support systems (CDSS) on physicians: a scoping review. The Importance of Health Informatics in Public Health during a Pandemic, 470-473.https://doi.org/10.3233/SHTI200597

24) Mishra, R., Bian, J., Fiszman, M., Weir, C. R., Jonnalagadda, S., Mostafa, J., & Del Fiol, G. (2014). Text summarization in the biomedical domain: a systematic review of recent research. Journal of biomedical informatics, 52, 457-467.https://doi.org/10.1016/j.jbi.2014.06.009

25) Neumann, C., Stein, O., & Sudermann-Merx, N. (2019). A feasible rounding approach for mixed-integer optimization problems. Computational Optimization and Applications, 72, 309-337.https://doi.org/10.1007/s10589-018-0042-y

26) Oniani, D., Hilsman, J., Peng, Y., Poropatich, R. K., Pamplin, J. C., Legault, G. L., & Wang, Y. (2023). Adopting and expanding ethical principles for generative artificial intelligence from military to healthcare. NPJ Digital Medicine, 6(1), 225.https://doi.org/10.1038/s41746-023-00965-x

27) Peng, C., Yang, X., Chen, A., Smith, K. E., PourNejatian, N., Costa, A. B., ... & Wu, Y. (2023). A study of generative large language model for medical research and healthcare. NPJ digital medicine, 6(1), 210.https://doi.org/10.1038/s41746-023-00958-w

28) Pivovarov, R., & Elhadad, N. (2015). Automated methods for the summarization of electronic health records. Journal of the American Medical Informatics Association, 22(5), 938-947.https://doi.org/10.1093/jamia/ocv032

29) Sutton, R. T., Pincock, D., Baumgart, D. C., Sadowski, D. C., Fedorak, R. N., & Kroeker, K. I. (2020). An overview of clinical decision support systems: benefits, risks, and strategies for success. NPJ digital medicine, 3(1), 17.https://doi.org/10.1038/s41746-020-0221-y

30) Shahsavarani, A. M., Azad Marz Abadi, E., Hakimi Kalkhoran, M., Jafari, S., & Qaranli, S. (2015). Clinical decision support systems (CDSSs): state of the art review of literature. International Journal of Medical Reviews, 2(4), 299-308.

31) Sun, L., Huang, W., Yu, P. S., & Chen, W. (2018, July). Multi-round influence maximization. In Proceedings of the 24th ACM SIGKDD international conference on knowledge discovery & data mining (pp. 2249-2258).https://doi.org/10.1145/3219819.3220101

32) Sheth, S., Baker, H. P., Prescher, H., & Strelzow, J. A. (2022). Ethical considerations of artificial intelligence in health care: examining the role of generative pretrained transformer-4. JAAOS-Journal of the American Academy of Orthopaedic Surgeons, 10-5435.

33) Tewari, S., & Chitnis, A. (2021). GRAPH-BASED MACHINE LEARNING FOR COMPLEX RELATIONSHIP DETECTION IN ENTERPRISE DATA.

34) Tewari, S. (2023). AI-POWERED FINANCIAL FORECASTING: ENHANCING ACCURACY WITH MACHINE LEARNING IN ENTERPRISE SYSTEM.
35) TEWARI, S. (2023). Machine Learning Models for Scalable Metadata Management in Data Lakes.

36) Tewari, S., & Chitnis, A. (2021). GRAPH-BASED MACHINE LEARNING FOR COMPLEX RELATIONSHIP DETECTION IN ENTERPRISE DATA.

37) Tewari, S. (2022). DETECTING DATA QUALITY ANOMALIES IN LARGE-SCALE DATA PLATFORMS USING MACHINE LEARNING

38) Velickovski, F., Ceccaroni, L., Roca, J., Burgos, F., Galdiz, J. B., Marina, N., & Lluch-Ariet, M. (2014). Clinical Decision Support Systems (CDSS) for preventive management of COPD patients. Journal of translational medicine, 12, 1-10.https://doi.org/10.1186/1479-5876-12-S2-S9

39) Wasylewicz, A. T., & Scheepers-Hoeks, A. M. J. W. (2019). Clinical decision support systems. Fundamentals of clinical data science, 153-169.

40) Yu, P., Xu, H., Hu, X., & Deng, C. (2023, October). Leveraging generative AI and large language models: a comprehensive roadmap for healthcare integration. In Healthcare (Vol. 11, No. 20, p. 2776). MDPI.https://doi.org/10.3390/healthcare11202776