JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue

JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)

An International Scholarly Open Access, Peer-reviewed, Refereed Journal

A REVIEW ON THERMAL ANALYSIS OF CYLINDER HEAD GASKET

[1]SK. RAMJANVALI, [2]Mr. G.S.R.N. MALLESWARA RAO,
[3]D. LEELA RAMA KUMAR,[4]P. OBEDU

1,3,4 UG Students in Mechanical Engineering Dept, NRI Institute of Technology,Vijayawada, Andhra Pradesh,India

2 Associate Professor in Mechanical Engineering Dept, NRI Institute of Technology,Vijayawada, Andhra Pradesh,India

Abstract: The research aims to redesign a four-cylinder engine's cylinder head gasket using multiple layers of steel and asbestos to ensure optimal compression and prevent leaks. The study uses ANSYS to conduct thermal analysis on the gasket, comparing different materials and determining the superior one. The gasket should withstand temperature generated by combustion and different loading conditions. The project aims to improve the efficiency of automobile engines in sealing combustion gases and preventing leaks. The gasket model was designed using SOLIDWORKS, ANSYS, CATIA different materials were applied. The study aims to improve design and reduce production time for powertrain components, reducing health risks associated with asbestos fibers. Such the blown head gasket can cause extensive damage to an engine, leading to repairs or replacements. Steel, copper, and the heat-transfer characteristics and efficiency of polymer materials were examined. The project's goal is to use Multiple Layers Steel (MLS) and asbestos substitutes to change the gasket's composition and design for a four-cylinder engine. A thermal analysis test was performed on the cylinder head gasket to identify failures and compare different materials.

IndexTerms - Brake pad, coconut shell, abrasive, friction, molding, composite materials

INTRODUCTION

A mechanical seal known as a gasket covers the gap between two or more mating surfaces, usually to stop leaks occurring into or out of the joined objects as they are compressed. In a mechanical assembly, this deformable substance is utilized to generate a static seal and keep it in place under a variety of operating circumstances. When gaskets are used to fill imperfections, they enable "less-than-perfect" mating surfaces on machine parts. The most frequent method for making gaskets is cutting from sheet materials. It is essential to choose the right gasket material for the application given the possible financial and safety consequences of defective or leaking gaskets. Asbestos may be present in gaskets designed for particular uses, like high-pressure steam systems. Nevertheless, because of the health risks connected to When it is practicable, non-asbestos gasket materials are utilized to prevent asbestos exposure. Generally speaking, it is preferable for the gasket to be composed of a somewhat yielding material that allows it to flex and firmly cover the space it is intended for, even with minor flaws. For some types of gaskets to work well, a sealant must be placed directly to the gasket surface. Certain (piping) gaskets are built completely of metal and rely on a seating surface to create the seal; the spring properties of the metal are used in this way. This is a common occurrence in certain metal gasket systems or "Ring joints" (RJ). The R-con and E-con compressive type joints are the names given to these joints. Certain gaskets are applied and allowed to cure on site. These resources are referred to as formed-in-place gaskets.

LITERATUREREVIEW

Przemysław Jaszak, [1] Semimetals, or serrated gaskets, are essential in applications where great tightness and dependability are required. Leakage testing entails utilizing a suction tube to find helium leaks and placing the gasket joint under a glass cover with dial gauges. A discrete model of expanded graphite was developed by analyzing its properties. The lowest pressure (37.1 MPa) was discovered in the serration recesses, and the highest pressure (182.1 MPa) was noted at the serration ridges next to the bolts. This pressure distribution improves the sealing effectiveness of the gasket by offering a wide region of high pressure, which is helpful. Standard core designs, like G1, show notable radial and circumferential anomalies in the contact pressure distribution. Inconsistent sealing may result from this abnormality. Analytical Leakage is studied using models that consider the physical-chemical properties of gases, material qualities, geometric considerations, and other types of loads, such as thermal and mechanical ones. To sum up, in harsh conditions, serrated gaskets are necessary for high-performance sealing. Their capacity to keep a trustworthy seal is greatly impacted by their design and material properties.

Ze-Nian Wang et.al., [2] Evaluates the water swelling performance of Water Swelling Polyurethane (WSP) and Water Swelling Rubber (WSR) using pH, solution concentration, and loading pressure. The data provides a quantitative evaluation of WSP and WSRP's swelling capacity, allowing for better understanding of their mechanisms. The study also provides a reference for material selection for WSR and WSP. The WSP material was prepared by adding TDI and prepolymer, while the WSRP was obtained by adding sodium polyacrylate, prepolymer, and WSR.

Chang-Chun Lee et.al., [3] For engine design, analytical instruments and experimental techniques are essential, especially when it comes to gasket sealing. In order to save time and money when developing a new engine, proper testing and analysis methods are crucial. Saving time for the real adjustments requires the completion of structural and thermal evaluations. For computing results under loading circumstances like hot firing and hot assembly, heat transport analysis is essential. Three load phases are included in the structural analysis of an engine: assembly loading, thermal loadings, and gas pressure. By locating the gasket's weakest point of contact pressure, the study examines the effectiveness of gasket sealing. It focuses on hot firing, hot assembly, and cold assembly. The findings indicate that while pre-stressing force increases, gasket sealing capacity decreases and contact pressure increases. By using a unique design with minimal engine components, proper thermal stress could increase gasket sealing efficiency, but the gasket's sealing However, the gasket's ability to seal falls inside the design criteria's safety factor.

Atefeh Heidarian et.al., [4] Conductive composite materials are crucial in the electronics and information industries, with a growing demand for high-performance electromagnetic shielding materials. Conductive silicone rubbers (CSRs) are used in various applications such as electrostatic dissipation of charge, rubber contact switches, pressure sensors, force sensors, surface heaters, electromagnetic interference shielding, and gas sensors. These materials exhibit excellent plasticity, corrosion resistance, low density, high thermal conductivity, and a wide range of electrical conductivities. Nickel-coated graphite particles offer good thermal conductivity, making them suitable for applications involving heat transfer or thermal management. The electrical conductivity and shielding effectiveness of silicone rubber are influenced by the loading content of nickel-coated graphite particles. A suitable distribution of fillers in the polymer matrix results in good and uniform electric conductivity in gaskets. The shielding effectiveness property depicts the variation in shielding effectiveness (SE) of conductive gaskets within the frequency range of 1200–2600 MHz.The composite's electromagnetic impedance decreased due to reduced volume resistivity, resulting in higher impedance mismatch to air. Increased filler loadings increased compact structure, facilitating interfacial polarization and intensifying electromagnetic loss.

Chenjie Gong et.al., [5] Highway, railway, and subway tunnels are facing numerous leaks due to natural or man-made factors, causing significant economic losses. With the large-scale development of urban underground space and metro tunnel construction, researchers have begun to pay close attention to tunnel waterproof problems. New testing technologies and structures have been introduced to address challenges such as high hydrostatic water pressure, fire, sandy leakage, seismic load, and deformation of segmental rings. Reinforced concrete casting is challenging to ensure smoothness in in-use segments, making it difficult to determine contact behavior between gaskets and rubber. Test results are unreliable for double-layer gaskets in deep drainage shield tunnels under high external pressure and variable internal pressure. Common materials used in gasket rubber are elastic and water-swelling rubber. Researchers have reviewed material properties, material selection, and aging mechanisms of gasket rubber materials. They have also studied the material

property damage of joint gaskets in high-temperature scenarios. Numerical simulation analysis focuses on accurately reproducing compression deformation processes in grooves. Recent research focuses on simulating joint gasket leaking failure processes and developing a thermal mechanical coupling finite element model for reinforced concrete and fiber-reinforced segment joints in fire.

Dr. CH . Shashikanth et.al., [6] A gasket is a mechanical seal that prevents leakage between mating surfaces during compression. In an automobile engine, a cylinder head gasket is inserted between the head and block to seal cylinders for maximum compression and prevent leakage of coolant or engine oil. The gasket's thermal characteristics can be improved using an advanced femitool. Modern head engines typically use MLS gaskets. This paper analyzes the multilayer cylinder head gasket of a single cylinder diesel engine using nonlinear analysis and ANSYS 15 software. Four materials were selected: Stainless steel, Ceramic8D, FR-4 Epoxy, and Steel 1008. The analysis focuses on thermal expansion, thermal stress, temperature deformation, total heat flux, and thermal error. Ceramic8D is a hard, corrosion-resistant, and brittle material that can withstand high temperatures. FR-4 Epoxy is a flame-retardant printed circuit board base material with good adhesion to copper foil. Carbon steels, containing mostly carbon, have excellent weldability and are used in various applications. Stainless steels, which contain at least 10.5% chromium and less than 1.2% carbon, are known for their corrosion resistance and mechanical properties.

Bhumireddy Ravindrareddy et.al., [7] Internal combustion engines use fossil fuel combustion with an oxidizer to expand high-temperature and pressure gases. The engine block, which includes cylinders, coolant passages, oil galleries, crankcase, and cylinder heads, is the main structure. Modern head engines use MLS gaskets, coated with rubber-like coatings like Viton. Elastomer-bonded soft materials like Kevlar fibers, carbon fiber, and pyrosic ceramic glass fiber materials are used today. SolidWorks is a 3D parametric design tool used to create various items, including toys, hoover cleaners, cell phones, furniture, electrical assemblies, marine equipment, and aeroplane components. FEA programs offer objective functions for minimization or maximization, including mass, volume, temperature, strain energy, force, displacement, velocity, acceleration, and synthetic. Finite Element Analysis (FEA) is a numerical method used to deconstruct complex systems into small, user-designated elements. It involves using sample elements such as rods, beams, plates, and shear panels. Structural analysis uses linear and non-linear models, vibration analysis tests against random vibrations, shocks, and impacts, and heat transfer analysis models the conductivity of the material. ANSYS is a general-purpose FEA software package used for post-processing. Steady-state thermal analysis can be linear or nonlinear.

Varunraj Varatharaj et.al., [8] Gaskets are mechanical seals used to prevent leakages between surfaces under load. They come in various designs, such as sheet, solid material, double-jacketed, and flange gaskets. They are made from materials like rubber, Teflon, polytetrafluoroethylene, neoprene, fiber glass, and silicon. The cylinder head gasket serves to prevent combustion gas leakage and prevent coolant or engine oil from flowing into the cylinder. The material selection is crucial as it must withstand high temperatures and different loading conditions. Stainless steel, polytetrafluoroethylene (PTFE), pyrolylite, carbon fiber, and kevlar are selected for this analysis due to their high thermal and structural properties. The gasket is stationary and fixed between the cylinder block and cylinder head using bolts. The combustion pressure varies depending on the rate of combustion and temperature. A steady-state analysis is performed to determine the total heat flux and directional heat flux of the materials. Transient thermal analysis is used to determine temperatures, heat flow rates, heat fluxes, and thermal gradients caused by thermal loads. Deformations over time cause weak spots in objects, affecting pressure and temperature, causing material elasticity loss. The cylinder head gasket, subjected to pressure and temperature changes, shows color variation and stress levels. Corners and areas around holes have higher stress values due to pressure and hole impact.

S.Karthikeyan et.al., [9] Automobile engine design and development involve complex processes involving various analytical tools and experimental methods. Modern calculation methods allow for precise stress and fatigue strength evaluation. Contact behavior occurs between the cylinder head and gasket and bolts, and FEM is more effective than boundary element methods. Load cases include assembly loads, combustion peak pressure, and thermal stresses. The pre-stressing force of bolts is crucial for numerical simulations. Montegory provides six approaches to describe bolt pre-stressing force. This research focuses on gasket sealing efficiency and heat transfer analysis, considering both hot assembly and hot firing. The cylinder head is modeled using solid parabolic tetrahedron elements and the upper part of the crankcase. The tightening force of cylinder head bolts is introduced as a preload at beam elements. The proposed formulation estimates convection coefficients and surrounding temperatures for computing nodal temperatures in all FEM model regions. In cold assembly,

the gasket sealing is considered motionless, with the maximum source of loading being the pre-stressing of bolts. Parametric analysis is implemented to determine the maximum contact pressure on the gasket surface. Cold starts are simulated using assembly loading and gas pressure, with the distribution of contact pressure and least effective gasket sealing being the same. Hot assembly uses pre-stressing force and thermal loading to simulate thermal balance reached by gas bursts. The hot firing process simulates spark plug firing, with gas pressure added to applied loadings.

R.Sathish et.al., [10] the head gasket, also known as the cylinder head gasket, is crucial for ensuring maximum compression between the engine block and the cylinder head, preventing internal leakage. It transfers gases and heat, and its excellent seal between surfaces is crucial for equipment performance. Materials used for this part include multiple layer steel, graphite, or asbestos. Solid copper, composite, and elastomeric materials are used for gasket manufacturing. Analyzing the thermal expansion, stress, and temperature deformation of these materials helps determine which material is better and cost-effective. The process involves applying temperature around the edges and applying all DOF on the outer side.

Maloth Sai Gopal Nayak et.al., [11] A gasket is a mechanical seal that prevents leakage from or into joined objects while under compression. In an automobile engine, a cylinder head gasket is inserted between the head and block to seal the cylinders, ensuring maximum compression and preventing leakage of coolant or engine oil. The gasket material should have good flexibility, low density, high tensile strength, excellent adhesion properties, and excellent wear resistance. The most widely used materials are copper and asbestos combination, fiber-based composite materials, graphite in various densities, and a combination of aluminum and fiber. The gasket's condition is typically investigated by checking compression pressure with a pressure gauge or leak-down test. The gasket's thermal characteristics can be improved using advanced tools. Four materials were selected for analysis: Stainless steel, Ceramic8D, FR-4 Epoxy, and Steel 1008. Ceramic8D is hard, corrosion-resistant, and brittle, while FR-4 Epoxy is flame-retardant and suitable for standard applications. Carbon steels contain mostly carbon as the alloying element, with excellent weldability and AISI 1008 carbon steel. Stainless steel, known for its corrosion resistance and mechanical properties, can be enhanced with elements like nickel, molybdenum, titanium, niobium, and manganese, giving it its name.

R.Abik .al., [12] Cylinder head gaskets play a crucial role in ensuring maximum compression between the engine block and the cylinder head, preventing internal leakage. They are commonly made of multiple layer steel, graphite, or asbestos. The composite cylinder head gasket is made of graphite or asbestos and is easy to be blown out. A thermal analysis test was conducted on a four-stroke engine cylinder head gasket to identify failures and compare gasket materials. The analysis used commercial FEM software, ANSYS, and PRO-E software for gasket diagrams and temperature values. Structural steel is commonly used for the gasket. Nonlinear analysis was performed to reduce bore distortion and achieve optimal contact pressure. The study considered the multilayer cylinder head gasket of a single cylinder diesel engine, using CRE-O 2.0 and ANSYS 15 software. The analysis analyzed the thermal expansion, thermal stress, and temperature deformation of carbon steel, stainless steel, and chromium. The results showed that the chosen material was good and cost-effective.

N. Ramadevi et.al., [13] The efficiency of engine gasket sealing and stress/strain behavior of cylinder heads under various loading conditions using contact theory and thermal stress analysis. Gaskets between the engine block and cylinder head in an engine seal cylinders for maximum compression and prevent leakage of coolant or engine oil. The project aims to modify the material and design of the gasket for a four-cylinder engine. The gasket materials used include Multiple Layers Steel (MLS) and asbestos, which are used due to health risks. Alternatives include elastomer-bonded soft materials like Kevlar fibers, carbon fiber, and pyrosic ceramic glass fibers. The project uses the commercial FEM software ANSYS to perform a thermal analysis test on the cylinder head gasket of a four-stroke engine. The results show that the efficiency of sealing depends on the pre-stressing force of hold-down bolts, without considering thermal stresses resulting from temperature distribution in the cylinder head. The design and development of automobile engines are complex processes that consider harsh environments and the environment. Gas leaks from engines affect horsepower output efficiency and pollute the environment. Gaskets provide a gas tight seal between cylinders, water jackets, oil passages, and ambient air, liquids, and gases. They must withstand pressures and prevent leakage of coolant or combustion gases. Gaskets in diesel engines are often used to prevent fluid and gas leakage, but they wear out with constant usage and heating and cooling.

Kanumuri Rajesh et.al., [14] MLS gaskets use two types of beads: full bead and half bead. The full bead is used to equalize dynamic sealing gap oscillations between the cylinder head and cylinder block at high combustion pressures, while the half bead seals against coolant and oil in areas far away from the cylinder, at bolt holes, and at outer surfaces. The bead stiffness is influenced by geometry, steel quality, sheet thickness, and production process. Engine head gasket design is complex, balancing sealing potential versus overall durability. Factors such as bolt clamping force, deck surface characteristics, peak cylinder pressures, engine temperatures, fluid and gas chemistries, and compressed gasket thickness are important. Gasket layer beads are small, single springs with suitable stiffness that create a larger spring when assembled. The layout of the beads in adjacent layers can be classified as series or parallel, depending on the dynamics of the bolted joint, cyclic loading, and thermal distortion of the engine assembly. Analytical methods are needed in the design phase of a MLS gasket to optimize gasket contact stresses and minimize dynamic head motion. The Axisymmetric Method is a method used to analyze gasket assemblies, focusing on single areas of the multilayered gasket during cold clamping cases.

Abhilash J et.al., [15] numerical simulation techniques to standardize the procedure for analyzing the gasket sealing efficiency of a 4-stroke, 4-cylinder gasoline engine. The FE Model used was based on the 2005 model, which had a 4-cylinder head and was CAD modeled using SolidWorks 2013. The study adapted the results of thermal analysis, the spark plug area had the highest temperature in the cylinder head. The structural exploration was divided into three parts assembly loading, thermal loading, and gas pressure. the efficiency of gasket sealing in vehicles under different loading conditions. The weakest contact pressure was found at the elevated portion of the inner ring between two neighboring combustion chambers. The study also examined cold assembly, cold starts, hot assembly, and hot firing conditions. The results showed that the sealing capacity of the gasket decreased significantly due to the opposite direction of gas pressure compared to the pre-stressing force of the bolt. The study also conducted a comparative study for various stopper designs and found a new type of stopper design that worked satisfactorily under minimum contact pressure criteria. The research opens opportunities for further testing before commercializing the new stopper design.

Abhijeet V. et.al., [16] The impact of bolt tightening strategies on the sealing performance of the cylinder head gasket. The study uses numerical analysis to estimate the CHG contact pressure distribution, focusing on a 4-cylinder inline engine off highway application. The complete assembly consists of the cylinder head, 17-cylinder head bolts, the multi-layered gasket geometry, and the engine block. The gasket properties are converted into specific CGASK elements with multi-linear load-deflection curves. The assembly load analysis focuses on the gasket thickness direction pressure and bore deformation. The gasket pressure value decreases from 45° to 90° angular positions due to the location of the cylinder bolts far away from the bridge area between adjacent cylinder bore apertures. The contact pressure on the gasket is compared with Fuji Film results, which captures the contact pressure distribution of other bead areas in the gasket. Piston ring conformability is determined in terms of percentage sealing of the ring to the liner bore.

Satish Anande et.al., [17] Cylinder head gaskets are crucial components of petrol or diesel engines, forming a seal between the cylinder head and block. They prevent leaks and ensure maximum compression. Contact pressure distribution is checked for different loading conditions, using finite element method calculations. Parametric analysis is performed using pretensioning force on bolts, and mesh generation is done in ANSYS software. Material properties must be approximated in FEM, as there is variation in Young's modulus. Modification of the gasket is used to increase contact pressure and decrease bore distortion. A modified gasket is used, and experimental validation is done using Fuji film, a pre-stressing sensitive film. Bore gauge is used for bore distortion validation. The contact pressures on the gasket and bore distortion are obtained using FEA using CAE tool ANSYS, with a percentage deviation less than 10% between actual and simulated results.

D.Vinod Kumar et.al., [18] the Pro/E model provided by China Engine Corporation to investigate the efficiency of gasket sealing in a gasoline engine with 4 cylinders and 4 strokes. The study considers only one cylinder head for convenience. The material properties of the components include aluminum alloy, steel, and carbon-steel. The internal part of the gasket is in contact with different components with dissimilar material characteristics. The weakest contact pressure on the gasket is used to investigate gasket sealing efficiency. The results show that the weakest contact pressure on the gasket appears at the raised location of the inner ring between two adjacent combustion chambers, due to the greatest distance between the bolts and the gasket. The maximum contact pressure on the gasket surface at the inlet part is slightly different from the exhaust part due to structural asymmetry.

Mahammadrafik J. et.al., [19] Scholars have examined the effects of multiple elements, including as inertia force, vibration force, thermal load, mechanical load, fatigue load, and fuel gas load, on the performance of cylinders and cylinder heads. They discovered that heat transfer and weight reduction were enhanced when aluminum alloys were used in place of cast iron sleeves. Additionally, they discovered that the cylinder head's nose bridge—which connects the inlet and exhaust valves—was brittle. Using Finite Element analysis, the researchers were also able to improve the construction of the nose bridge and other components of the cylinder head. In order to learn more about how to affect the motorcycle's coolant side's heat transfer coefficient (HTC), they also used nuclear boiling. The study looks into the short-term cyclic response of temperature transients in an air-cooled, four-stroke, direct-injection diesel engine's combustion chamber walls. After comparing the theoretical and experimental findings, a novel optimization criterion based on Lagrange conditions is created. In order to ascertain the temperature distribution, the study also conducts thermal analysis on the cylinder head using the FEM program. A new twin-cam, 16-valve cylinder head and block are also the subject of the study, which looks into the assembly and firing loads on them. It observes the maximum amount of heat dissipation achievable by giving the fins the proper length, thickness, and number. The study comes to the conclusion that thermal mechanical fatigue prediction requires design iterations.

WANG Long et.al., [20] A finite element model of a diesel engine, complete with the cylinder head gasket and other parts, is shown in this study. A cylinder head, engine block, cylinder head bolt, and other parts are included in the model. A subdivision quadratic element mesh is used to generate the mesh, with 120 nodes placed circumferentially and 6 nodes arranged radially and thickly. The gas explosion pressure inside the cylinder and the bolt preload on the cylinder head bolt make up the mechanical stress on the combined structure. By applying the thermal boundary conditions to the cylinder head and cylinder liner, heat transfer is used to determine the cylinder head gasket's temperature field. The analysis focuses on the temperature field distribution, where the exhaust valve is located in the positive direction. Under thermal-mechanical coupling conditions, the cylinder head gasket's stress value is larger, meaning that the heat load on the gasket is more than the cylinder's explosion pressure and equal to the bolt on the gasket.

Amir Ghasemi,et.al., [21]An hybrid neural network based on PLSR and DNN is used to construct an operating state prediction model for cylinder gaskets. The mapping layer receives the output of the feature selection layer as input, and the feature selection layer chooses four normalized operational factors for optimization. The primary procedure entails multiobjective optimization of the gasket's maximum deformation, maximum stress, and maximum temperature. The algorithms PLSR, DNN, ABC, and GWO are used to find the ideal operating factors. The algorithm's effectiveness is demonstrated by the enhanced maximum temperature, maximum coupling stress, and maximum deformation, together with decreased thermal stress load and deformation.

Shaiksai Malik et.all., [22] In order to ensure adequate sealing of the coolant, oil, and combustion gas passageways, the head gasket is an essential sealing component between the cylinder block and head. In order to maintain the assembly's sealing at different engine speeds and loads, it must endure high pressures and temperatures during the combustion process. Because of their greater sealing resistance, improved emission control, and increased durability, multi-layer steel head gaskets are used in the heavy duty diesel and internal combustion engine industries. The body of the MLS cylinder head gasket is made of low stiffness steel, and the gasket is made of many layers of steel. About 60–80% of the stress caused by bolt loading is absorbed by the stopper area, which is the first line of defense against leaks. This affects load distribution, head lift off, bore distortion, brinelling, and fretting. The approach that is axisymmetric. The gasket deflection and stresses at particular cross sections of the gasket assembly are found using the axisymmetric approach. 304 stainless steel is used to make the fire rings, while 301 stainless steel is used to make the gasket layers.

Noshirwaan Aibada et.al., [23] Because of their longevity and corrosion resistance, metallic gaskets are utilized in a wide range of applications. A variety of materials, including titanium, nickel, aluminum, gold, copper, inconel, stainless steel, and rhenium, can be used to make them. Rhenium is utilized for its stability and high boiling point, while stainless steel is used for its resistance to corrosion and tensile strength. Gold is utilized for wafer level packing and encapsulation; it is flexible and chemically stable but costly. Because of its excellent sealing qualities and malleability and heat conductivity, copper is a common material for gaskets. Aluminum can be used in systems operating at vacuum pressures because it is a soft, ductile metal with good heat and current conduction capabilities. Because of titanium's superior strength to weight ratio and high melting point, which qualifies it for fluid sealing at high temperatures. Non-metallic gaskets can be made to fit any shape or size and are utilized in applications with minimal to high pressure and temperature. Gaskets

made of polymeric materials, like silicone rubber, polytetrafluoroethylene, pyroclast, and chloroprene, provide excellent sealing and remarkable resistance to corrosion. Hybrid gaskets offer excellent sealing performance and strength by combining metallic and non-metallic components. They are divided into categories such as rubber/asbestos, HDPE/polyaniline, glass filled PTFE, stainless steel/graphite, diamond/rhenium, and stainless steel/graphite. High temperature applications require graphite/teflon, whereas rubber-coated stainless steel provides superior sealing capabilities.

Ke CAO et.al., [24] An essential part of the combustion chamber, the gasket is vital to the combustion process. For the purpose of computing compression ratios, its thickness and diameter are essential. For a good seal, multilayer steel plates coated with RFC101D are utilized. The goal of the research is to investigate thickness fluctuation and compute tighter thickness using the FEA approach. In order to determine the gasket's contact stress, macroscopic simulations are performed, treating the stainless stopper plate and cylinder block as rigid entities. The cylinder head is composed of aluminum alloy AC4B-T6, while the gasket is composed of stainless steel 0Cr18Ni9. The Mooney-Rivlin model is used in the simulation to examine the microscopic deformation behavior of coatings. For the fluororubber material in the simulation, CAX4R elements are used, maintaining a high-quality mesh.

Amir Ghasemi Making [25] ensuring that the sealing pressure at the interfaces between gasket components is higher than a threshold value is the main goal of PIP gasket FEA. The material that makes up the gasket is thought to be completely incompressible and displays nonlinear hyperelastic behavior. Three main procedures are needed to find the sealing pressure distribution for the PIP gasket: 2D FEA plane strain analysis, 3D FEA, and experimental test. All FEA numerical simulations, which show instantaneous elastic response up to enormous strains like rubber, are conducted using the ABAQUS finite element program. The strain energy potential is used to describe the mechanical response of materials that are hyperelastic. The PIP gasket has been examined for lowest sealing and material break strain at MMC condition in a two-dimensional model. pressure in the 3D model at the LMC condition. Gasket elements in ABAQUS are used in the MLS gasket FEA to streamline modeling without sacrificing the foundation of nonlinear response. For an MLS head gasket, an engine thermal study is required, and minimum sealing pressure in various areas is predicted using a FEA structural/sealing analysis. MLS gasket failure usually results from a complete embossment or fatigue crack. Gasket durability is assessed using a 2-D axisymmetric multi-layer model.

M.Srikanth et.al., [26] The nonlinear reaction of the gasket's materials complicates the modeling of diesel engine cylinder head gasket joints, which is covered in this work. A head gasket joint model is constructed and assembled using ABAQUS finite element analysis, which takes into account both mechanical and thermal loads. In order to protect against air, coolants, combustion, and engine oil at their respective maximum working temperatures and pressures, the gasket must keep the seal surrounding the combustion chamber under these conditions. To produce a gasket that keeps the essential sealing qualities for the duration of the engine, a variety of metals, composites, and chemicals are used. Internal combustion engine sealing is dominated by stainless steel cylinder head gaskets (CHG), which are becoming more and more significant. To create composites, such as carbon fiber reinforced polymer, which is stiff and has a high strength-to-weight ratio, carbon fibers are frequently mixed with other materials. For increased heat tolerance, carbon fibers and graphite can also be mixed. Heat shields, insulating panels, and exhaust pipes are examples of structural components that use ceramic matrix composite materials (CMC) or composite materials using glass, metal, and synthetic matrices. Racing tires were the first product to incorporate the synthetic fiber known as Kevlar, which is a para-aramid.

T. Y. Chen et,al., [27] The MLS cylinder head gasket design is intricate because sealing potential and feature durability must be balanced. Tolerance stack-ups, which assess engine feature sizes and placements as well as sealing feature geometry, are the initial phase. Engineers work to control the embossment spring stiffness, which is essential for the part to function properly. Finding the right forms and arrangements for both static and dynamic functional requirements is a challenge. By analyzing bolted joints and their responses to different situations, sealing professionals can optimize the gasket before testing it in 3-D finite element analysis. The main cause of gasket failure is head lift.

Harry Willis et.al., [28] The second approach is a "trial and error" procedure in which engine components are simulated using a computer model and metallographic sections are contrasted. In order to do the study, engine component temperatures, pressures, and the stresses that arise on the flange must be compared. Vickers hardness, flange thinning, wire cross section thickness and width, and material grain size measurements are

used in the analysis of field engine head gaskets. To find the steel's yield strength, ultimate strength, elongation, initial hardness, and final hardness, a tensile test is applied to the flange material. A high BMEP engine, bench testing, laboratory dynamometer tests, and other controlled laboratory tests are compared with the metallographic examination of field failures. The findings imply that cylinder condition affects flange cracking. According to finite element analysis, a gasket flange is thinning, necessitating precise material qualities. Because of the steel's plastic deformation, the end of the flange experiences the highest stress. Steel and thin graphite sheets are laminated together to form the gasket body. Usually, the gasket body is depicted as an elastic-plastic substance. The top of the liner has the highest temperature, which leads to thermal deformation and liner growth.

Made Gatot Karohika et.al., [29] The design of corrugated metal gaskets (CMG) utilizing a mold press is the main topic of this study. SUS304 serves as the core material for the three layers of sheet metal that make up the gaskets. Three softer materials make up the layer materials, and three levels are used to calculate the working hardening coefficient. Simulation modeling, FEM software, and MSC. Marc is used to examine the gasket model. The two steps of the model are simulation formation and simulation tightening. It is assumed that the material behaves as in the bilinear strain hardening isotropic model, with an elastic-plastic reaction and a local tangent to the curve. The equilibrium equation is solved using the Newton-Raphson method. Leaks can be effectively prevented by the convex portion of the gasket, and the contact surface increases with the Using peak 3 and 2 for contact width and stress, this study examines the contact surface and contact stress of three-layer gaskets. The simulation findings indicate that contact breadth rises as tightening force increases. The maximum and lowest contact width slopes are found in gaskets with work hardening values of Eh1 = E1/150 and Eh1 = E1/50, respectively. If the effective normal stress on the gasket is greater than the internal pressure test, the gasket continues to function well.The gasket with work hardening coefficients Eh1 = E1/50 exhibits the highest average contact stress tendency in the 400-MPa mode. Because the effective normal stress on the gasket is 48 times higher than the internal stress at tightening force of 80 KN, or about 480 MPa, the gasket continues to perform well.

V.Arjun et.al., [30] One Cylinder In an internal combustion engine, the gasket, often known as the head gasket, is located between the engine block and the cylinder head or heads. It is the most important sealing component in any engine because it seals the cylinders to maintain maximum compression and prevent coolant or engine oil from leaking into the cylinders. Because it is a component of the combustion chamber, it must have the same strength requirements as other combustion chamber components. When examining the state of a head gasket, one can usually use a pressure gauge to measure the compression pressure, or even better, perform a leak-down test. If the engine is water-cooled, one can also look for any signs of combustion gasses in the cooling system. oil in the coolant and high coolant loss that doesn't seem to be related, or the presence of hydrocarbon gasses or carbon monoxide in the cooling system's expansion tank may also indicate issues with the head gasket. The presence of something that looks like mayonnaise in the oil, which is frequently visible on the dipstick or oil filler cap, is a reliable indicator of head gasket failure in water-cooled engines. This material could mix with the coolant in other ways; thus, its existence does not prove that the head gasket failed.

S.-S. Cho et.al., [31] The full-bead, half-bead, and stopper components of the MLS gasket are arranged in a stacked configuration with a spacer between the function layers. The gasket is represented as a single, uniformly thick sheet, with each bead's placement matching the contact pressure found in an actual gasket. The unit width of the bead line aids in evaluating the gasket bead. Based on their dimensions, half-beads are divided into three categories and further into interacting and isolated beads. The bead model can be used to calculate the compression behavior of the stacked beads. Pressure-overclosure curves for a range of maximum bead loads are used to determine the compression behavior of each type of bead. The new bolt model produces roughly identical numbers to the old one, and the bolt load increases linearly with pressure. Try something. If, while the engine is running, the minimum contact pressure between the stopper and the beads is greater than the critical sealing pressure, the gasket sealing performance is guaranteed.

William Attard et.al., [32] The gasket less interface was created to stop combustion gas leaks in motorsport applications and other situations where engines are operated at high pressure and temperature. To seal combustion gasses between the cylinder head and block assemblies, no special gasket or parts are needed. This is done by the barrel and liner assembly, which carries out its functions related to heat transfer and piston motion. The gasketless interface may seal cooling water, lubrication oil, and combustion gas in the same way that a traditional head gasket would. In addition to being employed separately to limit cooling water and oil,

O-ring seals have the temporary ability to seal combustion gas in the event of an interface failure. An analysis using thermal FEM was conducted to ascertain the effect of the gasketless design on the surface. temperatures of the exhaust blow-down and the cylinder head and liner at maximum pressure. Because of the gasket's limited thermal conductivity, the findings of the gasket model demonstrate a significant temperature difference across the gasket surface.

Pavan P.et.a, [33] The analysis's goal was to ascertain how the pressure distribution of the cylinder head bolt tension on the gasket surface for the current design. Usually thin, gaskets are composed of materials such as steel, rubber compounds, and composites and serve as sealing elements between structural components. ANSYS provides a range of components for modeling gaskets, such as a material choice for the gasket that takes thickness behavior into account. Compression curve equations provided the material behavior of the gasket, enabling a more thorough examination of the gasket. Like litmus paper, Fuji pre-scale pre-stressing sensitive films produce high resolution pressure variations throughout contact areas. The amount of pressure used directly affects the image's color intensity. Fuji film was inserted between the valve plates and the cylinder heads during the experimental examination, which produced agreeable FEA results. To guarantee that the gasket pressure is sufficient to sustain the difference pressure across the suction and discharge plenum, adjustments were made. Costs, development time, and compressor dependability could all be decreased with future design.

Fabio Bruzzone et.al., [34] divides its approach into geometry-independent and geometry-dependent methodologies to investigate the impact of geometrical parameters on the compressive gasket behavior. Since geometry's contribution is integrated with the material contribution, geometry-independent approaches are not dependent on geometry in a direct manner. Through-thickness behavior is defined by the Abaqus code's 'gasket' finite element (FE) as a loading-unloading curve. A thorough modeling of the gasket cross section or experimental study can yield the force-displacement relation. It is thought that the axisymmetric FE model offers the best balance and allows for high computational efficiency. The fundamental Coulomb friction model controls the tangential behavior, and a strict pressure-overclosure relation reduces the amount that the slave surface can penetrate the master surface. Additionally, the investigation looks at how thickness affects clamping force and elastic recovery, demonstrating that the clamping force is nearly constant and rises with thickness.

Didik Nurhadiyanto,et.al., [35] The design of a gasket in high-temperature and high-pressure settings utilizing SUS304 material is the main objective of this work. Forming and tightening simulation are the two simulation phases that comprise the gasket model. We evaluate the optimum design gasket in both elastic and plastic environments. For gasket design modeling, the forming effect is taken into account in the simulation analysis. Preprocessing, optimization, automatic meshing, and parameterization are the four processes that go into creating the virtual gasket model. The reduction of clamping load is the basis for determining the ideal design. Utilizing a helium leak measurement tool, the study assesses leak quantity as well. Leak measurement is done using the vacuum method with the maximum detection ability. A general-purpose flange with a 25A diameter and 20 K pressure was employed in the test. It is possible to anticipate axial load accurately. by directly measuring the axial load by integrating strain gauges into the bolts.

Moch Agus Choiron, et.a., [36] In this work, a SUS304 gasket with circumferential beads is used in high-temperature and high-pressure settings. Software for the finite element method (FEM) analysis and tensile testing were used to validate the gasket material. Using MSC. Marc, the contact width was measured with the flange taken to be stiff. In order to minimize clamping load, the study integrates optimization design based on expanding contact width and taking contact stress into account. The impact of every design parameter was assessed, and the ideal design for a new metal gasket in the 25A size was predicted, using the Taguchi DOE method. The analysis shows that the improved design at No. 1 offers a notable improvement over the original design even at low clamping loads, highlighting the value of advanced design language (ALD) and upfront engineering.

Jun Okano,et.al., [37] To compare the new gasket design with the old design, a number of validation tests were conducted on it. To define the new bead design structure, a different approach was used to assess the gasket contact pressure and FEA was used to do stress analysis calculations. To find out more about the real seal performance of the gasket's combustion gas seal section, cylinder pressurizing tests were carried out. Tests using coolant immersion were done to see how well the coating worked. The real movement of the cylinder head against the block was measured using thermal shock tests. In low bolt axial force conditions,

the new shim bead design was found to have a larger maximum gas pressure than the old semi-stopper design. A 0.08mm thickness increase over a 0.06mm thickness demonstrated improved seal performance. The pressurizing test of the cylinder using the new shim bead design outperformed the old semi-stopper design in terms of seal performance, as demonstrated by the real gasket test flange.

Li Wei-min [38] This work uses a three-dimensional solid model to compute finite element values for a complex engine cylinder head and cylinder gasket. Because SolidWorks is the model's foundation, intercepting the composite structure is made simple. Under preload conditions, the research takes into account displacement, contact, and load boundary conditions. The composite construction needs to be able to sustain high pressure and high heat load during an epidemic. Three processes are involved in the investigation of the thermal-mechanical coupling stress field: thermal analysis, structural analysis, and structural analysis. For the composite structure, the thermal solid element is chosen, and the characteristics of the material are established. Under preload conditions, the free grid partition method with a degenerate hexahedral element is applied. The finite element calculation requires a model translation from thermal analysis to structural analysis unit. To solve structure stress, the finite element model must be converted from thermal analysis to a structural analysis unit. For mechanical stress under preload circumstances, the properties of materials, elastic modulus, thermal expansion coefficient, and Poisson's ratio are defined. The definition of the load, contact, and displacement conditions that make up the boundary conditions of structural analysis. Equivalent stress and explosion pressure are applied to the load boundary conditions, and the model node points are subjected to temperature load and steady-state thermal analysis results.

Frank Popielas,et.al., [39] In order to prepare a multi-layer system for multi-layer steel engine gaskets, it is necessary to optimize bead design, analyze loading and unloading situations, and assemble previously calculated pieces into simplified structures. After that, this data is exported for a 2D-axi-symmetric multi-layer model simulation, which captures residual stress and distorted shape caused by manufacturing operations. Additionally examined is the elements' fatigue life under operational circumstances. Because of their intricate geometric designs and high compressive stresses, multi-layer steel engine gaskets require time-consuming thorough modeling for internal stress analysis. The sole method for handling this issue is two-dimensional axisymmetric analysis, which offers details on how engine hardware behaves and interacts with various gasket layers. Information on stress and strain distribution, load-deflection curves, layer interactions, gasket-hardware interactions, contact pressure, and stress are all provided by the simulations. and strain amplitudes, spring travel, consistency of bead compression, effects of temperature and coating, and tolerances. Designing essential engine parts, such as head gaskets, requires an understanding of coolant behavior in the coolant jacket since these parts affect the engine's durability and temperature distribution. It is essential to comprehend the sealing system, which consists of the cylinder head, block, gasket, and bolts, in order to design a new gasket. The one-cylinder model has a 3D version that supports several layers.

Chiranjeevi Krishnappa,et.a., [40] In order to analyze engine components, compressible Navier-Stokes equations for mass, momentum, and energy must be solved. Additionally, a two-equation turbulence model called Realizable $\kappa - \varepsilon$ must be used. The CAD modeling data for the three-dimensional wireframe was imported in the STL format. The engine's coolant flow is 120 LPM, and a polyhedral meshing technique is used to build the water jacket. The thermal study of the engine is carried out independently to determine the temperature distribution throughout the structure. The engine structure temperature is predicted using the FEA program (ABAQUS), which is then utilized for fatigue study, bore distortion, and gasket sealing. GT Power is used to compute the gas side temperatures and heat transfer coefficients. The MLS head gaskets are made of two to five steel sheets that have been exposed to significant nonlinear deformation and are sandwiched between sealing material. The inquiryMajor loading circumstances during engine operation, such as cold assembly, hot assembly, and cold firing, are taken into account in the gasket sealing investigation. For the purpose of precisely and consistently predicting durability analysis, head gasket sealing analysis, and bore distortion, the anticipated temperature distribution is ideal.

CONCLUSION

According to the study, spiral patterns are more accurate at predicting piston ring conformability and bore deformation when used for cylinder head gaskets. In a 600 cc diesel engine, the FEA approach was utilized to calculate contact pressures on cylinder head gaskets and bore distortion; the real and simulated results showed a percentage difference of less than 10%. The gasket sealing capacity is dependent on bolt pre-stressing and thermal stress/strain, according to the paper's finite element study of the cylinder head structural analysis. With the highest total coordination coefficient is the ideal design approach. The study optimizes cylinder gasket state parameters and operating factors using FEM, orthogonal experimental design, HNN, and GWO. Additionally, the research focuses on examining gaskets' minute deformation. crushed by blocks and cylinder heads, including both microscopic and macroscopic modeling. By concentrating on FEA techniques for forecasting sealing pressure and durability, the study offers a superior option for automotive engine design and development.

REFERENCES

1. Przemy sławJaszak The elastic serrated gasket of the flange bolted joints , International Journal of Pressure Vessels and Piping 176 (2019) 103954, Received 7 April 2017; Received in revised form 24 July 2019; Accepted 4 August 2019 E-mail Journal of Pressure Vessels and Piping 176 (2019) 103954, https://doi.org/10.1016/j.ijpvp.2019.103954, Available online 07 August 2019.
2. Ze-Nian Wang a, Shui-Long Shen, Annan Zhou c, Hai-Min Lyu Experimental data of water swelling characteristics of polymer materials for tunnel sealing gasket, Published by Elsevier Inc. This is an open access article under the CC by license 2352-3409/©, https://doi.org/10.1016/j.ijpvp.2019.103954 , 2020.
3. Chang-Chun Leea, Kuo-Ning Chianga, Wen-King Chenb, Rong-Shieh Chen Design and analysis of gasket sealing of cylinder head under engine operation conditions, Finite Elements in Analysis and Design 41 (2005) 1160 – 1174, doi: 10.1016/j.finel.2004.12.007,7 April 2005.
4. Atefeh Heidarian, Hamed Naderi-Samani, Reza Shoja Razavi, Mahsa Nejad Jabbari, Ehsan Naderi-Samani, Mohammad Gavahian jahromi Study of nickel-coated graphite/silicone rubber composites for the application of electromagnetic interference shielding gaskets, published by Elsevier Ltd. 20242949-8228/© 2024 Received 26 September 2023; Received in revised form 20 December 2023; Accepted 20 December 2023.
5. Chenjie Gong, Yuanye Wang, Wenqi Ding, Mingfeng Lei and Chenghua Shi Waterproof Performance of Sealing Gasket in Shield Tunnel A Review, Multidisciplinary Digital Publishing Institute A Review, A Review. Appl. Sci. 2022, 12, 4556. https://doi.org/10.3390/app12094556 ,A Appl. Sci. 2022.
6. Dr.Ch.Shashikanth, associate professor, P.Anitha, associate professor are developed "Modeling And Thermal Analysis Of Head Engine Gaskets ", journal of nonlinear analysis and optimization(jnoa), ISSN : 1906-9685, page no -1728-1740, vol. 13, issue. 2: 2022.
7. Bhumireddy Ravindrareddy, Dr. K Venkata Subbaiah, M Shiva Teja, 4 M Durga Prasad, Y Chiranjeevi, B Mahesh Babu, a"design and Analysis Of Cylinder Head Gasket", ZKG international(zkgi), volume :VIII issue: I, ISSN: 2366- 1313,page no:849-861, MARCH 2023.
8. Varunraj Varatharaj, Pavan B, Darshan K N, Vishnu K.R "Structural and Thermal Analysis of Cylinder Head Gaske", International Journal of Scientific & Engineering Research Volume 12, ISSN 2229-5518, Page No: 13-17, Issue7, July-2021.
9. S.Karthikeyan, P.Sakthivel M.E. Student "Design and Structural Analysis of Aluminum Cylinder Head Gasket under Engine Operation", International Journal of Engineering Development and Research (IJER), Volume 3, Issue 2 | ISSN: 2321-993,Page no:530- 533, © 2015 IJEDR.
10. Sathish, C.Vasanthakumar, Sushil S John, S Yogeshwaran4 "Design And Analysis Of Four Storke Petrol Engine Gasket", International Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395-0056 Volume: 05 Issue: 08 | IRJET | Impact Factor value: 7.211 | ISO 9001:2008 Certified Journal | , Aug 2018 www.irjet.net p-ISSN: 2395- 0072, © 2018, Page 685.
11. Maloth Sai Gopal Nayakdr., D. Damodara R. "Design and Thermal Analysis of Head Engine Gasket by Varying Its Materials", Journal of Engineering, ISSN:0377-9254, Page 219 -227, Vol 13 Issue 11,2022.
12. R. Abik, A. AntoJeberson, K. AshifIbrahim, Balamurugan, R. Prabaharan, "Selection and Optimization of Gasket Materials", International Journal of Innovative Research in Science, Engineering and Technology Vol. 9, Issue 2, February 2020 Copyright to IJIRSET DOI:10.15680/IJIRSET.2020.0902099 14026, ISSN(Online): 2319-8753 ISSN (Print): 2347-6710, Page no: 14026-14030, Vol. 9, Issue 2, February 2020.

13. N.Ramadevi, raju ambati, s. Sushma. Bolamreddy babu reddy, Dr.K.Sammaiah , "Modeling Of An Engine Gasket By Using Catia Software", International Journal Of Current Engineering And Scientific Research (IJCESR), ISSN (PRINT): 2393-8374, (ONLINE): 2394-0697, DOI: 10.21276/ijcesr.2017.4.5.3.Page no:17-20, Volume-4,Issue-5, 2017.
14. Kanumuri Rajesh, Shaiksai Malik, Dr. D. Vijaya Ganapathy, "Finite Element Analysis Of Head Gasket", International Journal of Pure and Applied Mathematics 3975-3987 ISSN: 1314-3395. Page no:3975-3988, Volume 120 No. 6 ,2018.
15. Abhilash J. Nair, C. Lakshmikanthan "Head Gasket Failure Analysis", International Journal of Applied Engineering Research ISSN 0973-4562 pp 38187-38191 © Research India Publications. Page no: 38187-38191, Volume 10, Number 17 2015.
16. Abhijeet V. Marathe, G. Venkatachalam & Neelkanth V. Marathe (Cylinder Head Bolt Tightening Strategies in Case of Multi-Cylinder Engines and Its Effect on Gasket Sealing Performance, Bore Deformation and Piston Ring Conformability, Australian Journal of Mechanical Engineering, DOI: 10.1080/14484846.2018.1523292.ISSN: 1448-4846 (Print) 2204-2253, 2022.
17. Satish Anande M. Tech Mechanical-CAD/CAM, T, Amit ChaudhariManager-R&D, GreavesCotton Limited, Dr. M.K. RodgeAssociate Modification in Design of Cylinder Head Gasket for Reduction in Bore Distortion and To Achieve Optimum Contact Pressure. Journal of Mechanical Engineering and Technology (IJMET), pp.278–284, Article Id: Ijmet_07_05_028.ISSN Print: 0976-6340 and ISSN, Volume 7, Issue 5, September–October 2016. DOI: 10.1051/matecconf/20168002001 NUMIFORM 2016.
18. D.Vinod Kumar M.Tech(CAD/CAM) , V.Sreenivasulu , P . Divakara Rao, Dr.C.Udaya Kiran, Y . Vijaya Kumar Professor Design and Analysis of Gasket Sealing of Cylinder Head under Engine Operation Conditions. International Journal of Innovations in Engineering and Technology. ISSN: 2319-1058, Volume 2 Issue 3 – June 2013.
19. Mahammad rafik J. Meman, Amit B. Solanki, Akshay J. Parmarare Design, Modeling and Analysis of Structural Strength of Cylinder and Cylinder Head of 4-stroke (10 H.P.) C.I. Engine. International Journal ofAdvanced Engineering, Management and Science (IJAEMS)Infogain Publication. ISSN: 2454-1311, Vol-2, Issue-4, April- 2016.
20. Wang Long, Zuo Zhengxing, Cheng Ying, Zhu Xinran Research on the Coordination and Matching of Cylinder Head Gasket Strength and Sealing Performance. Journal of Physics: Conference Series.1885 (2021) 02/2015, doi:10.1088/1742-6596/1885/2/022015, ICAMMT 2021.
21. Yi Dong, Jianmin Liu, Yanbin Liu, Xinyong Qiao, Xiaoming Zhang, Qi Kang, and Tianqi Wang professor are developed. The Optimization Research of Diesel Cylinder Gasket Parameters Based on Hybrid Neutral Network and Improved GreyWolf Algorithm, doi:10.1088/1742-6596/1885/2/022015, 2020.
22. Shaiksai Malik, Kanumuri Rajesh, Dr. D. Vijaya ganapathy Head Gasket Finite Element Model Correlation International Journal of Pure and Applied Mathematics No. 6 2018, 3965-3974 ISSN: 1314-3395, june 5, Volume 120, 2018.
23. Noshirwaan Aibada, M. Ramachandran, Krishna Kumar Gupta, P. P. Raichurkar Review on Various Gaskets Based on the Materials, their Characteristics and Applications, nternational Journal on Textile Engineering and Processes Vol. 3, Issue 1 January 2017.
24. Ke Cao, Yixi Zhao,a and Sun Jin1 "Simulation on microscopic deformation behavior of engine gasket" ,Matec Web of Conferences 80, 02001 (2016) DOI: 10.1051/matecconf/20168002001 Numiform 2016.
25. Amir Ghasemi is developed by Computer Aided Simulations in Automotive EngineGasket Sealing, 2012 SAE International ings Meadow Campus,ISSN 0148-7191, Monday, September 17, 2018.
26. M. Srikanth, B. M. Balakrishnan International Journal of Machine and ConstructionEngineering Cylinder Head Gasket Analysis to Improve its Thermal Characteristics Using Advanced Fem Too, 2012 SAE International ings Meadow Campus, ISSN (Online): 2394 – 3025, Monday, September 17, 2015.
27. T. Y. Chen, Jim Zwick, Bhawani Tripathy and Gary Novak are developed by 3D Engine Analysis and MLS Cylinder Head Gaskets Design SAE International by University of British Columbia, ISSN 0148-7191, Thursday, August 02, 2018.
28. Harry Willis, Annette Stasiak, and Mark Shuster Dana, Coy Herald Automated Analysis, MikeReeves Caterpillar Tractor,Finite Element Analysis and Metallographic Analysis to Understand Field Forces on an Industrial Head Gasket SAE International by University of British Columbia, ISSN 0148-7191,Wednesday, September 26, 2018.

29. Made Gatot Karohika, Shigeyuki Haruyama, Nyoman Gde Antara, Nyoman Budiarsa, Made Dwi Budiana Penindra, Tersedia online di: http://ejournal.undip.ac.id/index.php/teknik , doi: 10.14710/teknik. v41n1.26125 Copyright © 2020, TEKNIK, p-ISSN: 0852-1697, e-ISSN: 240-9919. TEKNIK, 41 (1), 2020, 16.
30. V. Arjun, Divili, Mr. V.V. Ramakrishna, Divili, Andhra Pradesh, Indi a. And Mr. S. Rajasekhar,Thermal Analysis of an Engine Gasket At Different Operating Temperatures . International Journal &Magazine Engineering Technology, Management and Research, Volume N0: 2(2015), ISSNo:2348-4845, December 2025.
31. S.-S. Cho1, C. S. Shin1, C. S. Lee, H. Chang and K. W. Lee Assessment of an engine cylinder head-block joint Using finite element analysis, international Journal of Automotive Technology, DOI 10.1007/s12239−010−0010−8, Vol. 11, No. 1, pp. 75−80 ,2010.
32. William Attard and Harry C. Design and Development of a Gasket less Cylinder Head / Block Interface for an Open Deck, Multi Cylinder, Highly Turbocharged Small Engine, 2006 SAE International 2006-32-0036, 2006.
33. Pavan P. Jorwekar Kirloskar,Yogesh V. Birari Kirloskar, M . Nadgouda Kirloskar,Cylinder Head Gasket Contact Pressure Simulation for a Hermetic Compressor , Purdue University Purdue e-Pubs International Compressor Engineering Conference , C071 Page 1 -C071Page 5,Paper 1795 , 2006 .
34. Fabio Bruzzone, Cristiana Delprete and Carlo Rosso Modelling Strategy and Parametric Study of Metal Gaskets for Automotive Applications, Computer Modeling in Engineering & SciencesDOI:10.32604/cmes.2020.011023, ,14 April 2020; Accepted: 23 June 2020.
35. Didik Nurhadiyanto, Moch Agus Choiron, Ken Kaminishi, Shigeyuki Haruyama Optimization of New 25A-size Metal Gasket Design Based on Contact Width Considering Forming and Contact Stress Effect, International Scholarly and Scientific Research & Innovation, Vol:6 2012-03-28,6(3) 2012.
36. Moch Agus Choiron, Shigeyuki Haruyama, and Ken Kaminishi Optimum Design of New 25A-size Metal Gasket Considering Plastic Contact Stress, International Journal of Modeling and Optimization, Vol. 1, No. 2, June 2011.
37. Jun Okano, Nobuhide Kobayashi, Isao Nagano, and Toshiya Tabata an Example of Optimal Cylinder Head Gasket Design for Light Weight High Performance Engine, Society of Automotive Engineers, Copyright © 2013 SAE International and Copyright © 2013 KSAE doi:10.4271/2013-01-2642, August 04, 2018.
38. Li Wei-min FEA of Solid Stream Coupling Field formed by Automobile Engine Cylinder head and Cylinder Head Gasket, Advanced Materials Research Vols 299-300 (2011) pp 1161-1166 Online: 2011-07-27 2011.
39. Frank Pop ielas, Colin Chen, Rohit Ramkumar, Harald Rebien, and Hans Wald vogel Victor Reinz, Dana Corporation CAE Approach for Multi-Layer-Steel Cylinder Head Gaskets – Part 2, SSN 0148-7191, Copyright © 2003 SAE Internationa August 05, 2018.
40. Chiranjeevi Krishnappa, Mohan Makana, and Mandar M. Kulkarni Thermo-Mechanical Analysis of the Cylinder Head and Cylinder Block - CAE Approach, SAE International Copyright © 2013 SAE International, doi:10.4271/2013-01-2798Downloaded from SAE International by Birmingham City Univ, Monday, August 20, 2018, Monday, August 20, 2018.