JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

Skin Afflictions Unveiled: Classification of Dermatological Diseases using ConvolutionNeural Networks

Jageti Padmavathy

(Assistant Professor)

Department of Computer Science Engineering G.Narayanamma Institute of Technology and Science

Abstract:- With the development of computer technology, accurate and quicker findings may be produced, and patients can be treated as necessary. More people have skin conditions than other illnesses. Skin conditions can be brought on by viruses, germs, allergies, fungal infections, and more. An effective method to pinpoint specific types of skin illnesses has been proposed by a recent study. The development of automated techniques is required to improve the precision of skin disease diagnosis. Therefore, image processing methods aid in the beginning development of automated dermatology screening systems. We suggesteda method for identifying skin conditions based on image processing. Check the skin photograph you uploaded for signs of skin illness. This technique uses image analysis to determine the type of disease by taking a digital photograph of the affected skin area. Our suggested method is easy, quick, and doesn't call for pricey equipment. Any device with internet connectivity can use it. For successful identification, accurate skin disease detection and classification are crucial, and image processing with the use of machine learning algorithms can be used to accomplish this.

Keywords:- Convolutional Neural Networks, Artificial Networks, Image Processing, Deep Learning.

I. INTRODUCTION

Deep learning is a machine's ability to replicate human intellect when it comes to learning, thinking, and problem solving. Machine learning (ML), a branch of artificial intelligence, has already demonstrated promising uses in assisting humans in a range of medical fields. Deep learning (DL), a type of machine learning (ML), has been discovered to perform well when it comes to analyzing medical pictures. DL, like human thinking, produces complex judgements by stacking numerous simple reasoning functions in a deep structure. Convolutional Neural Networks (CNN) are one of the most successful deep learning (DL) techniques for image processing.

An artificial neural network called a CNN can identifyand isolate particular patterns in localized data. A convolutional pooling layer and further layers are shared by all of the modules. Additional layers are added on top of that, such as a rectified linear unit (also known as a "ReLu") and, if required, batch normalization. The final component of a conventional neural multi-layer network is composed of layers that are completely coupled. These modules are typically built upon one another to create a deep model that can incorporate information from 2D or 3D images and take into account layoutand spatial factors. It is essential for CNN networks to have precise estimations of the hyper parameters in the convolutional layer in order to solve the convolutional phase reduction.The output volume is determined by the number of filters, and each filter is trained to scan the input data at the neighborhood level for a particular feature. The convergence of the filter around the input volume can be observed by specifying a phase. A CNN with many convolutional layers is trained, but some areas, especially those close to the edges, are wasted.

II. LITERATURE SURVEY

This essay examines the crucial problem of identifying and categorizing skin diseases with an emphasis on the creation of a computer-aided technique for early diagnosis. Given that skin disorders are the fourth most common non-fatal disease burden globally, the authors stress the significance of early identification. The project described in the paper uses deep learning and image processing methods, more especially Convolutional Neural Networks (CNN) and Artificial Neural Networks (ANN), to categorize skin conditions from image data.

The authors highlight the diversity of human skin types and the range of potential skin abnormalities, which can sometimes be indicative of underlying diseases. The project aims to provide an early warning tool that can inform users about potential skin diseases they may be suffering from, thuscircumventing the need for physical clinic visits and manual diagnosis.

The dataset that was utilized to train the neural networks is thoroughly described in the publication. The Department of Dermatology at the Medical University of Vienna in Austria and a number of additional colleagues provided the photos for the dataset.A well-known set of dermatoscopic images of skin lesions used for training and assessing machine learning models in the fields of dermatology and computer vision is called the HAM10000 (Human Against Machine with 10,000 Training Images) dataset. The "HAM10000" included it when it was first introduced.

The authors detail the methodology employed in the project, which involves two approaches: traditional method and deep learning. The traditional method uses ANN for image categorization, with the authors noting that ANN was foundto be the best technique for feature extraction. However, the results from the ANN classifier were not satisfactory, leading the authors to experiment with the other deep learning approach.

In CNN, the authors re-train a pre-trained model, specifically MobileNet, to suit their requirements. MobileNet, with its lightweight architecture and fewer trainable parameters compared to other models like Resnet and VGG, reduces the computation and recognition time significantly. The results from the MobileNet classifier were found to be much more satisfactory than those from the CNN classifier, with a training accuracy of 89.9% and a validation accuracy of 73.8%.

In conclusion, the paper presents a compelling case for the use of deep learning techniques in skin disease detection and classification. The authors' work contributes to the broader goal of leveraging technology for early disease detection, potentially leading to more effective treatments and improved patient outcomes. However, further research and testing are needed to validate the model's effectiveness in real-world scenarios.

[1] Algorithms for deep learning and machine learning can recognise intricate patterns in photographs and extract relevant information from them.Deep learning has made progress and produced positive outcomes for picture recognition. Unlike conventional image identification algorithms, which necessitate feature engineering, deep learning can automatically mine the fundamental nonlinear relationship in medical images. Additionally, the extraction efficiency is good. Deep learning is adaptable and simple to change, making it easier to adapt the technology to various disciplines and applications.

[2] Traditional approach of model training
Convolutional neural networks' primary application is image categorization. CNN is useful for face recognition, object identification and categorization, video analysis, and a variety of other tasks. The CNN classifier takes the input image and reduces its size to the desired size of 224x224. The first convolutional layer (CL) is followed by the BatchNormalization layer (BNL) and the MaxPooling layer (MPL), and so on until the final fully connected layer is reached.

[3] Model training with Transfer Learning (TL)
This is a technique that allows us to retrain a previously taught model to meet our needs. This means that a model developed for one purpose can be used as the foundation for another model developed for a different task. This allows the model to learn more quickly while also reducing the number of computations. One such pre-trained model is MobileNet.

[4] CAD system for identification and classification
is a common method for disseminating knowledge that can help skin professionals make final decisions.Pre-processing, segmentation, feature extraction, and classification are the main techniques for image analysis that are frequently used in CAD systems.The classification stage of the CAD system is in charge of making inferences from the features that have been extracted in order to produce a diagnosis for the input image. On the training samples, the classification model is created using machine learning methods.

[5] Classification of Skin diseases using SVM
A Support Vector Machine is just a machine learning method that can distinguish between two or more classes. Different kernels are utilized as hyper planes to discriminate between the classes, resulting in classification. The accuracy and precision of the SVM are mostly determined by the Kernel and the boundary values defined. In order to produce better

results, an appropriate Kernel must be used. A "Linear kernel" is commonly utilized. Linear kernels are employed when the classes to be separated share few characteristics. The linear kernel is also one of the simplest kernels accessible.

[6] Classification based on DenseNet and ConvexNet
DenseNet is a traditional image classification model thatsuggests a more aggressive dense connection method, in which all preceding layers' feature maps are utilized as inputs for each layer, and its own feature maps are used as inputs for all subsequent layers. It has four sub-versions, and the DenseNet model has been upgraded with deeper network layers. The dense connection strategy promotes feature reuse in the network, thereby delaying the gradient disappearance problem, and it can perform better on most image classification tasks. The vanishing gradient problem was used to demonstrate the architecture's robustness.ConvNeXt was used to modify the existing model andincorporate some of the most recent ideas and technology into theexisting modules in order to improve the model's classification performance. It has five variants. The main backbone network is divided into four stages, each of which is made up of numerous blocks, and ConvNeXt was used to change the block ratio in eachstage to 1:1:3:1. It substituted a 3 x 3 depthwise convolution for the 3 x 3 convolution.

[7] Targeted Ensemble Machine Classification Approach for Supporting IoT Enabled Skin Disease Detection
A two-phase "Targeting Ensemble Machine Classify Model (TEMPM)" technique was presented as part of a unique classification procedure to generate enhanced classification results in skin disease diagnosis. The study looked into several combinations of the three preprocessing techniques—color featuring, model transfer, and data balancing—that worked on condition photographs using only Keras (a neural network library) GPU APIs.
Classification and Regression Trees (CART)
CART is an algorithm that uses Classification and Regression Trees. A classification tree is an algorithm with a fixed or categorical target variable. The technique is then used to determine which "class" a target variable is most likely to fall into. These are simple binary classifications in which the category dependent variable can have just one of two mutually exclusive values. A regression tree is an algorithm in which the target variable is identified and the algorithm is used to forecast its value.

[8] Classification of Skin Disease using Ensemble Data Mining Techniques
Decision Tree (DT)
Supervised Machine Learning includes Decision Trees. Decision trees are built using an algorithmic approach that identifies alternative ways to segment a data set based on certain conditions.The objective is to create a model that uses fundamental decision rules deduced from data attributes to forecast the value of a target variable. A decision tree can be used in decision analysis to visually and explicitly describe decisions and decision making.
Random Forest (RF)
The random forest classifier can be used for classification as well as regression. The missing values will be handled by the random forest classifier. When the forest has more trees, the random forest classifier will not overfit the model. Random Forest can also model classifiers for categorical values.

[9] Skin disease detection and segmentation using dynamic graph cut algorithm and classification through Naive bayes classifier
To divide a graph, graph cut methods are employed. The graph is a collection of data represented by pairs that are linked to one another. The constituents are referred to as nodes or vertices, while the links are referred to as arcs or edges. A graph is typically represented by the phrase G = (V, E), where V represents the vertex set and E represents the edges identified between the vertices.The suggested system is a modified graph cut method that is more effective than traditional graph cut algorithms because of its flexibility in minimizing groups of similar functions that are also decipherable in polynomial time.
New instances are solved by referring to previous experiences rather than doing a new computation, which significantly reduces the running time. One dependable probabilistic approach for labeling employs random fields, which can handle and represent complex hidden variable interactions in a straightforward and exact manner.

[10] Skin disease classification using AdBoost
Using AdaBoost, it is possible to accurately classify several types of skin diseases by training a strong classifier by fusing several weak classifiers. Each iteration, or round, of the AdaBoost algorithm trains a subpar classifier and provides it a weight based on how well it performs.Play around with hyperparameters like the selection of a weak classifier and the quantity of boosting rounds. The AdaBoost algorithm's performance may be affected by several variables. To determine the best set of hyperparameters, use methods like cross-validation.The power of the AdaBoost algorithm resides in its capacity to concentrate on difficult samples by assigning them larger weights and successfully merging the predictions of numerous weak classifiers into a solid final judgment. However, circumstances may still have an impact on how well it performs.

[11] Skin lesion classification system using a K-nearest neighbor algorithm

One of the simplest picture classification algorithms is nearest neighbor classification. As a result, based on the spaces in the test image, the nearest point from the learning set is labeled whenit is taken into account. For many data points within a picture, the Euclidean distance measurement is typically employed by default in KNN, and each pixel is assigned a value.Once traits have been extracted, they are immediately fed into classifiers or machine learning algorithms to be divided into two classes. There are two steps or portions to the complete procedure. While the second is used to compare the photographs to the training dataset, the first is used for training.

III. PROPOSED SYSTEM

In order to diagnose skin illnesses, image processing is used in the first stage and a machine learning algorithm is used in the second stage. Due to changes in the distinctive characteristics of the skin, such as color and texture, skin diseases are challenging to diagnose in the primary stage and other phases.

Deep learning for skin disease prediction. The primary goal of this project is to forecast skin diseases as accurately as possible. Early skin disease diagnosis is made possible by deep learning algorithms. Feature extraction has a significant role in the classification of skin disorders.The need for manual data reconstruction and feature extraction is reduced when using Deep Learning algorithms for categorization.

Convolutional neural networks (CNNs), in particular, excel at automatically extracting pertinent characteristics from raw data using deep learning models. These models can automatically identify intricate patterns and correlations in photos for the classification of skin diseases without the use of manually created feature engineering. This is especially useful when working with complex and subtle visual data, such as skin photographs. Deep learning is a dynamic field, and continual research and development have led to better architectures and methodologies. This implies that the most recent developments can help your classification system for skin diseases.

The proposed technique for classifying skin diseases makes use of the CNN algorithm, which comprises gathering photos of skin diseases from medical facilities, cleaning the images to reduce noise and artifacts, and enhancing their quality. Users can input and evaluate photos using the system's user interface, which can subsequently be used to swiftly and precisely identify skin lesions for classification.

Different modalities are used to gather, acquire, and preserve the dermatoscopic images from various populations. The 10015 dermatoscopic images that constitute the final dataset. There are seven distinct classes:

- Melanocytic nevi
- Melanoma
- Benign keratosis-like lesions
- Basal cell carcinoma
- Actinic keratoses
- Vascular lesions
- Dermatofibroma

CNNs are made to automatically recognise nested features in photos. Convolutional layers, which identify low-level characteristics like edges and textures, and deeper layers, which learn more complicated and abstract aspects, are among the layers that make up these systems. The complicated patterns visible in photos of skin diseases must be captured using this hierarchical feature extraction technique.CNNs are inherently translation-invariant, meaning they can identify features regardless of their position in the image. This property is beneficial for recognizing skin lesions or disease-related patterns, which can appear at different locations within an image.

CNNs use weight sharing, where the same set of learned parameters (filters) is applied to different parts of the input image. This reduces the number of parameters in the network, making it computationally efficient and reducing the risk of overfitting, especially when working with limited medical image datasets.CNNs use local receptive fields, which means that each neuron in a convolutional layer is connected to a limited region of the previous layer. This allows the network to focus on local features and patterns, which is particularly useful for capturing fine-grained details in skin disease images.

Pre-trained CNN models, such as those trained on large image datasets like ImageNet, can be fine-tuned for skin disease classification tasks. This leverages the knowledge alreadyencoded in the pre-trained weights and significantly speeds up the training process while improving performance, even whenyou have limited medical image data.CNNs can be scaled to handle images of different resolutions without significantly altering their architecture. This flexibility is advantageous when working with various medical imaging modalities and image sizes.

IV. MODULES



Fig 1: Architecture Diagram

- *MODULE 1: DATA COLLECTION AND PREPROCESSING*

The data collection and preparation module takes skin disease images from medical facilities and preprocesses them to enhance their quality and get rid of noise and artifacts in order to classify them using the CNN algorithm. A variety of sources, including hospitals and clinics, are used to collect images of skin lesions, which are then captured in digital format for later examination.

Images are preprocessed to ensure excellent quality and repeatability of outcomes during classification. Image scaling, normalizing, and filtering are some of the techniques used to remove noise and artifacts and improve image contrast and quality. To ensure that the images are uniform and of high quality, which improves the accuracy of the image classification model, several preprocessing techniques are required.

The photos are then preprocessed and saved in a manner that will allow the image classification model to further analyze them.This module makes sure that the input data is accurate and reliable, enabling the image classification model to correctly classify skin lesion images according to the disease.

- *MODULE 2: TRAINING OF THE MODEL*

The training model of CNN method is used to categorize skin lesion images using preprocessed skin lesion pictures. The CNN model is a deep convolutional neural network trained on a large dataset of images. We can increase the categorization accuracy of skin sickness images by modifying the model.

The CNN model's layers are utilized to train the model after preprocessing the skin images. The pooling layer minimizes the amount of computations required during training.CNNs have layered architectures that work together to process and categorize pictures.A collection of learnable filters are applied to the input image by a convolutional layer, the firstlayer of a CNN.

The output of each and every filter produces a feature map as its final product, which shows the presence of various features throughout the input image's various spatial regions. By choosing the highest value inside a given region, MaxPooling is a well-liked pooling technique to downsample the feature maps.The CNN can simulate complicated interactions between the input image and the learned features thanks to the nonlinearity introduced by activation functions. Rectified Linear Unit (ReLU) activation functions are frequently utilized and add non-linearity by returning the maximum of zero and the input value.

Fully connected layers allow the network to learn global patterns and make predictions by connecting every neuron in the previous layer to every neuron in the following layer. Flattened into a 1-dimensional vector, the output of the last convolutionalor pooling layer is used as the input for the fully connected layers.The fully connected layers classify data using the learned characteristics and output probabilities or predictions for various types of skin diseases.

During training, the CNN learns the optimal weights and biases for the filters and connections through backpropagation and gradient descent optimization. The goal of the model's training is to minimize the discrepancy between predicted outputsand ground truth labels. The model is trained using a labeled dataset of skin disease images.

By iteratively adjusting the parameters and updating the model's weights, the CNN gradually improves its ability to classify skin diseases accurately. Once trained, the CNN can be used to classify new, unseen skin disease images by feeding themthrough the network and obtaining the predicted class probabilities.

By adjusting the model's hyperparameters, such as learning rate, batch size, and number of epochs, efficiency can be increased. Cross-validation approaches may be used to assess the model's performance on the validation set, whichmay then be used to guide hyperparameter tweaking for the optimal outcomes. The model is then archived and used subsequently to classify skin conditions.

- *MODULE 3: PREDICTION OF THE OUTPUT*

The output prediction module of the CNN algorithm makes classification predictions about the type of disease present in images using the trained model. Following preprocessing of the images, the data is entered into the model, and a classification is determined using the data. At the moment of the prediction, the data is examined and presented to the user. One option is to offer a straightforward user interface that shows the predicted category and likelihood score for each image.

The change in the loss function value over the course of training is shown by the loss rate graph. The loss function, which is minimized during training, quantifies the discrepancy between predicted and actual values. The loss rate is shown on the y-axis, and the number of epochs is shown on the x-axis. The loss rate graph shows how the loss goes down as the model gets better at forecasting the future.

By analyzing both the accuracy and loss rate graphs, you can gain insights into the model's training progress. Ideally, the accuracy should increase, while the loss rate shoulddecrease with each epoch. If the accuracy plateaus or the loss rate fails to decrease, it may indicate that the model has reached its learning capacity or is overfitting the training data.

These graphs offer useful data for evaluating the model's performance, deciding on the ideal number of training epochs,

spotting potential problems like overfitting or underfitting, and making the required corrections to increase the model's precision and generalization skills.

The accuracy graph displays the CNN classifier's performance over a series of training epochs. It displays the development over time of the accuracy metric, which gauges the proportion of properly predicted samples. The y-axis displays the accuracy percentage, and the x-axis displays the number of epochs. Typically, as the model learns and refines its predictions, the accuracy tends to rise.

V. RESULT

The trained model is used in the CNN algorithm's output prediction module to provide diagnostic categorization based on images of skin lesions. Skin image files are supplied to the model after being preprocessed to facilitate data-driven classification.

Results for skin Disease prediction Using CNN:

Epoch Number	Validation Accuracy	Validation Loss
1	0.2168	2.8294
5	0.3579	1.6755
10	0.4350	1.4441
15	0.4996	1.2911
20	0.6446	0.9725
25	0.7189	0.7810
35	0.8950	0.2839
40	0.9129	0.2376
50	0.9514	0.1240

table : Epoch table of CNN classifier

The accuracy and loss during training at various period numbers are probably listed in Table . Based on the validation loss, this table aids in monitoring the advancements and improvements produced by the CNN classifier. Finding epochs where the model had increased performance in terms of validation loss allows you to get insight into the training process and indicate areas for future model development.It is crucial to remember that the acquired accuracy figures can vary based on a variety of factors, including the difficulty of the problem, the caliber of the dataset, the design of the model, and the selection of the hyperparameters.



VI. PERFORMANCE ANALYSIS

According to the performance analysis for classifying skin lesion images using the CNN algorithm, the model successfully detected skin disorders with good accuracy, precision, and recall. The model's excellent accuracy reveals both its effectiveness in categorizing images of skin diseases and its ability to provide precise comprehensive skin disease categorization monitoring.



V. REFERENCES

1. Akyeramfo-Sam, Samuel & Philip, Acheampong & Yeboah, Derrick & Nartey, Nancy & Nti, Isaac kofi. (2019). A Web-Based Skin Disease Diagnosis Using Convolutional Neural Networks. International Journal of Information Technology and Computer Science. 11. 54-60. 10.5815/ijitcs.2019.11.06.

2. Balaji, V.R., Suganthi, S.T., Rajadevi, R., Kumar, V. Krishna, Balaji, B. Saravana, Pandiyan, Sanjeevi. "Skin disease detection and segmentation using dynamic graph cut algorithm and classification through Naive Bayes classifier," Measurement, Volume 163, 2020, 107922, ISSN 0263-2241.

3. Kumar Patnaik, Sourav, Singh Sidhu, Mansher, Gehlot, Yaagyanika, Sharma, Bhairvi, Muthu, P. "Automated Skin Disease Identification using Deep Learning Algorithm."

4. Seth, D., Cheldize, K., Brown, D. "Global Burden of Skin Disease: Inequities and Innovations." Curr Derm Rep 6, 204–210 (2017).

5. Soliman ALKolifi ALEnezi, Nawal. "A Method Of Skin Disease Detection Using Image Processing And Machine Learning," Procedia Computer Science, Volume 163, 2019, Pages 85-92, ISSN 1877-0509.

6. Verma, Anurag Kumar and Pal, Saurabh and Kumar, Surjeet. "Comparison of skin disease prediction by feature selection using ensemble data mining techniques," Informatics in Medicine Unlocked, Volume 16, 2019, Pages 100202, ISSN 2352-9148.

7. Yu, H. Q., Reiff-Marganiec, S. "Targeted Ensemble Machine Classification Approach for Supporting IoT EnabledSkin Disease Detection" in IEEE Access, vol. 9, pp. 50244-50252, 2021, doi: 10.1109/ACCESS.2021.3069024.