JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

# RAILWAY SYSTEM BASED ON OBJECT DETECTION

**M. Anusha Rani [1] ,Cheepurupalli Ekshitha [2] , Pavuluri Sri Lakshmi [3] , Masanam Sri Poojitha [4] , Lanka Rohini [5]**

[1*] Assistant Professor: Vignan's Nirula Institute of Technology and Science for Women,

[2,3,4,5] B.Tech: Vignan's Nirula Institute of Technology and Science for Women.
anusharanimedarametla@gmail.com,cheepurupalliekshitha62@gmail.com,
p.lakshmichowdary1112@gmail.com,manasamsripoojitha@gmail.com, rohinilanka2021@gmail.com.

## ABSTRACT

Advances in object recognition technology have opened new avenues for improving the safety, efficiency, and automation of railway systems. Powered by deep learning and computer vision algorithms. Object recognition plays an important role in various aspects of railway operations. significantly Including real-time tracking collision avoidance Avoiding obstacles on the tracks This paper studies the application of object detection in railway systems. Accident prevention and performance tracking, performance training optimization, and focus on role improvement. It uses object detection through camera sensors placed at key locations in the rail system such as intersections, platforms, tracks, etc. These systems can identify and classify objects on the tracks including animals, vehicles or humans and alert operators or activate incidents. automatic emergency Braking neural networks Convolutional (CNN) and leverages technologies such as machine learning models. For modern object detection systems to achieve high accuracy in real-time detection of dangerous situations.

**Keywords** : Deep Learning, Convolutional Neural Networks, Accuracy, Clustering, Detection.

## 1. INTRODUCTION

This situation implies that rail network systems from their core design are open, accessible, and welcoming systems [1-5]. Consequently, control of entry is on the basis of revenue protection and not security, and with a with few exceptions (e.g., international services), they do not embrace the strict perimeter security system introduced in the field of air travel mode [6-11]. A good example is the use of car to transport people or goods from one place to another is entirely appropriate given its functionality. This, however, exposes the systems in several ways regarding the success of the operation [12-19]. Terrorist activity is often called the most publicly recognized threat; various sorts of resilience and design approaches have been adopted to minimize the chances of railways being attacked by the terrorists and to transform them into being less attractive targets [20-24].

The two species are quick to recover if attacked [25-30]. Nonetheless, interruptions occur because of various events that are not expected to happen in the organization such as trespass (especially in connection with the theft of materials or equipment and suicide attempts [31-38]. means that railway employees should be trained to identify and assist people Miner, (2007, p. 121).These are the people who maybe contemplating to kill oneself on the railway [39-44]. Measures that can be used to avoid access at high-risk locations include fencing so as to deter people from accessing the premises. actions and assist in solving issues that relate to security, cases of trespass and suicide threats. However, access prevention is cannot be considered as applicable to station environment and it is here where recent development of video analyse Solutions specific to rail [45-46] present other options to mitigate these risks in a synchronized manner.

It has been able to incorporate physical solutions like blast resistant glazing as stated in 'designing in' [47], and management. solutions like staff training in order to recognize specific atypical occurrences. The development concerning the utilisation of digital technology for sensing and sensing, data fusion and machine learning as well as. these areas with the advancement of the communication and cloud technologies have the potential of giving much contribution in [48]. The use of both, though, raises some of ethical concerns that must be made regarding use. for example, those to do with publicness and processing of information as in the area of Europe.

## 2. LITERATURE WORK

At present the best technologies useful for CCTV is equipped with video analytic tools for producing automated detection and alerts based on information processing, reasonable frame work and there are also other computer vision technologies including object detection [49], behaviour analysis and activity. identification, counting, identification of possible threats and facilitating evacuation [50-54]. Expanding from the above discussion let us analyse the emerging patterns of CCTV video surveillance for rail network systems and connected artificial vision sciences and technologies. A few of the resolutions that have been made since the year 2010 include the following; Figures 1 and 2 [55]. The following keywords are used in the search: In the instance below I have circled the words that you defined in your writing prompt; "surveillance", "railway". It is pertinent to recognize two terms here; "computer vision" and "machine learning". The bibliometric analysis applied in this work is known as Bibliometric [56].

multi-sensor obstacle detection system was invented by Siegfried Mockel et al. in 2003 , simulation of Kalman filter The above mentioned method is used to acquire accurate multi-sensor data of obstacles on the tile. This prototype was tested on a test that acted as a proxy for a semester long class as part of the evaluation process of this Be Learn system as described earlier in this document. active vehicle that was permitted to accelerate to a speed of 120 km/h and achieve forward-looking distance of 400 meters. J Jesus Garcia and they also proposed an obstacle detection model in 2010 involving multisensory barrier in order to identify obstacles on the train track. Fuzzy logistics and Shafer's dynamic model were used to actualize the mentioned system [57]. In 2011, Passarella et al. put in place an idea for obstacle recognition which can be used to guide the locomotive. driver as soon as possible of possible dangerous situations. It was also suggested that the system should be engaged for using infrared sensors able to give an alarm of the presence of objects within the range. The rail track is shown to benefit greatly from sensor based obstacle detection. One cutting pattern recognition; an edge method for crack identification and collision avoidance was begun in the same year. The Trackside system includes sensor, memory, ZigBee, and microcontroller all of which help in the identification of uncommon vibration battery. sends responses to the trains and the room where It is controlled as indicated [58]. There was a railway track monitoring system which suggested by Dhiraj Sinha and Farhan Feroz in which vibration sensors and signal filtering are done using Bayesian. analysis in order to accurately identify the dismounted ones. The Bayesian decision analysis method that assist in filtering the signal of obstacles as shown It provide a high acoustic noise level [59].

That is why in real-world scenarios the installation of the alarm system with the automatic stopping of the train is more efficient than the non-recurring shunt and the rotation of the locomotive only, or any of the other types of alarms mentioned above. obstacle detection systems. Athira, S recommend that the system proposed here will utilize Camera data and the classifier based on CNN model trained on a dataset and utilized to sort humans within the track's bounding box on the scene for humans. FFNN, On the other hand, detects the number of items in an obstacle and the position of an object improves object position detection as compared to DWN. in real-time [60]

Signalling control of railway traffic has been a big concern from the time the railway was constructed, among of which the obstacle detection is difficult during the safe running of the railway and there are been used in many important kinds of research. The earliest method of railway obstacle detection is to try and get the obstacle to be detected. information either by using physical touch with the power grid or grating or indirectly. foreign objects. In terms of data-processing, it is possible to mark that this kind of method does not provoke lots of problems being rather easy for processing. technology is relatively mature. However, this method can also select the obstacle intrusion. to a certain extent, easing the pressure of the event, but the installation of

equipment is relatively complex, the investment is very large. the operating range is small and also intrusion type of obstacle cannot be identified [61].

Thus, the proposed approach adaptively conducts the railway track identification and means (target / object/ obstacle) detection on the railway track. This approach involves designing a system with In this approach, towards implementing a solution, several steps are followed with an emphasis on the following ones. 2D-SSA by which the input frame is segmented into several discriminant features (patterns). This approach is aimed at employing particular component (pattern) to locate railway tracks. that is constructed with the information about tracks [62]. Then component (pattern) having the object of reaping benefits for the shareholders, will emerge. For the purpose of effectively recognizing the obstacles on the railway, the above defined (obstacle) is applied to the deep networks.

In the traditional methods, the first process to segment an image is to calculate the correlation of the pixel intensity. offered between two neighbouring pixels on the scene image and then it separates the whole image into some fragmented areas. according by a certain convergence criterion. For instance, the super pixel algorithm turns the image from the RGB colour space to CIE-Lab colour space to establish a five-dimension vector (brightness, colour The pixel attributes of the two pixels include colour A, colour B, x position and y position and the vector length between the two pixels. The Simulation, similarity is utilized to create the small segments patches [63]. A spatial pyramid descriptor the gray, coloured and edge gradient into a feature vector for the traffic light detection for the SVM classifier to recognize a track sign [64]. It is also possible to convert the image into the Yellow colour space, and local texture attributes in rigid sources at the every channels are matched with the artificially designed template to know the position of the track sign [65]. Hence it possible to convert the image from the given RGB colour space into other feature space may be a more proper method. obtain more dimensional information channels: Mayer-Gross' usual luminosity or intensity, roughness, and other feature maps other than RGB colour.

Furthermore, the segmented region for the time being should be fragmented, and such fragmentation will yield the final segmentation. The internal the connections of the neighbouring areas as well as the rules that govern the areas are divert and belong to the regions. divided according to the local areas with the support of values of the correlated characteristics. For instance the K-means clustering The application of rules is illustrated by a number of practical engineering issues like the identification of the synthetic object. aperture radar (SAR) image and the sea scene[66]. The MCG algorithm is another grouping strategy joining all the multiscale regions to very accurate probabilities of objects using the forests which were randomly produced. For the task MCG can process one image (pixel size 90 150) in 7 s, while the mean Intersection-over-Union (IU). is about 80% [68]. These are the rules within clustering, which define the level of precision in combination and it is directly. based on the above result it is inversely proportional to the time calculation, so MCG suitable before or after processing. a determination of scene not moving with moment that are scenes, temporary and dynamic scenes. Therefore, to accelerate the process of the entire scene segmentation, we developed an effort to enhance the effectiveness of the traditional methods through the optimization of the generation and conjunction of the split micro areas and at the same time, retain a "micro-micro") segmentation accuracy [69].

## 3. PROPOSAL MECHANISM

The aim of this project is to design an efficient optronic railway system with object detection techniques carrying out on OpenCV in order to improve safety as well as security and automation. The proposed system is intended to avoid and avert the occurrences of accidents by alerting on the presence of moving and non-moving obstructions such as people, animals or even vehicles on the tracks and at the crossings. In addition, the system will provide services on the intercity lines for the improvement of the operation of track maintenance performance by clarifying the state of infrastructure such as cracks, loose stones or other obstacles and providing a security service real time monitoring of no-go zones.

**Open CV**

OpenCV is the computer vision project with a library of programming functions specially made for real-time image processing. It offers a set of utilities and Operations for Object Detecting, face identifying, image analysis, moving item tracking and calibrating the camera. It is also written in C++-compatible, for languages

such as Python, Java, and MATLAB making it rather flexible with developers from different platforms of development. For more basic tasks, such as filters, features, edges, transformations, OpenCV can handle them directly, for artificial intelligence functions such as real-time recognition of objects, it is achieved by using deep learning models. Currently, OpenCV is used in applications including robotics and automated automobiles and augmented reality and security systems, among others because it is versatile, and due to its hardware compatibility with hardware like cameras and sensors.

**Working of Open CV**

[1] Reading the image
[2] Image enhancement
[3] Object detection
[4] Image filtering
[5] Draw the image
[6] Saving the changed images

**Downloading and Installing Open CV**

python –version //if python is already installed, it will gives a message with the python version available

pip install opencv-python //installing opencv library

python
importcv2
print(cv2.__version__) // weather the opencv is correctly installed or not

# import packages

from imutils.video import VideoStream

from imutils.video import FPS

import numpy as np

import argparse

import imutils

import time

import cv2

import pyttsx3

import serial

In using OpenCV for object detection in a railway system, cameras obtain video streams along tracks and platforms in real time. These frames are then handed over to the OpenCV to look for objects include but not limited to people, animals or any other middle level objects using models like You Only Look Once (YOLO) or the Single Shot Detector (SSD). When an object is noticed the system sends real time alerts to trainers for operators or control centers to act on and prevent accidents if any. It also has the capability of detecting movements of objects and launch corresponding actions such as halting train operations or closing operation gates on railway cross sections leading to further improvements of safety and utilization on railways.

## 4. ANALYSIS REPORT




**Fig:-1**

The figure 1 provides a comprehensive assessment of various performance indicators. Emphasis is placed on packet delivery ratio (PDR), latency, and end-to-end delay for railway systems using object detection. and possible throughput **Packet Delivery Ratio (PDR)** reflects the reliability of the sensor data delivery system to the central controller. In the same way Reducing this delay is critical for timely response to potentially hazardous situations. Finally, **throughput** measures the rate at which data can be successfully transmitted.




**Fig:-2**

The figure 2 compare overall network measurements across four different algorithms or protocols. The results indicate similar performance in terms of packet delivery ratio, delay, latency, and throughput in the algorithm. All algorithms scale well as the number of blocks increases. Although small changes in performance may indicate specific optimizations or inherent trade-offs with each algorithm.




**Fig:-3**

The distribution of area sizes relative to rank numbers can tell us a lot about how a system manages resources. How to partition or process data or regional scaling A smooth and consistent graph indicates a balanced allocation. while non-normal distribution indicates dynamism. or adaptive system This may be caused by changing conditions. Such types of graphs can be used in areas such as distributed computing. telecommunications network or storage system To analyze the resource allocation model that responds to specific needs of figure 3.

## 5. CONCLUSION

In this work, an efficient and effective method for identifying the railway track and the obstacles along the same has been proposed. Following the introduced technique, the two-dimensional Singular Spectrum Analysis (SSA) is used to separate the thermal image into various individual information carrying parts, after which the deep learning network employs such part to help in determining the obstacle located on the railway tracks. The other importance of this study is the identification of the railway tracks using SSA. Therefore, combining Deep network with 2D SSA formed a better and more efficient technique that will help in building an early warning system for preventing railway disasters thereby increasing the safety of the railway transport systems. Considering that there is no major change is required in the train infrastructure, this system will therefore be economical. This will also lessen the economic strain regarding railways guaranteeing compensations. Also, in this paper, this work exhibits good results when applied under varying illumination conditions using the OSU thermal pedestrian database sourced from the OTCBVS benchmark dataset collection. More advanced object recognition systems will be incorporated within the existing system to deal object recognitions issues such as occlusion recognition, background clutter etc, as a future work to enhance the robustness of the framework.

## 7.REFERENCES

[1] Patibandla, R. S. M. L., Rao, B. T., Narayana, V. L., & Srinivas, V. S. (2021). An overview of ontology-based artificial intelligence services in health care systems. In *Proceedings of the International Conference on Health Care Systems* (pp. 47–63).

[2] Maddumala, V. R., Maha Lakshmi, K., Anusha, P., & Lakshman Narayana, V. (2020). Enhanced morphological operations for improving the pixel intensity level. *Journal of Computational and Theoretical Nanoscience*, 29(3), 9191–9201.

[3] Narayana, V. L., Malleswari, K. S. N., Divyanjali, M., Nandini, S., & Purnima, G. (2023). Video frame based prompt compression model with steganography for secure data transmission. In *Proceedings of the International Conference on Advanced Intelligent Systems* (pp. 373–377). https://doi.org/10.1109/ICAIS56108.2023.10073883

[4] Naresh, A., Pavani, V., Meghana Chowdary, M., & Lakshman Narayana, V. (2020). Energy consumption reduction in cloud environment by balancing cloud user load. *Journal of Critical Reviews*, 7(7), 1003–1010. https://doi.org/10.31838/jcr.07.07.184

[5] Patibandla, R. S. M. L., & Vejendla, L. N. (2022). Significance of blockchain technologies in industry. In *Advances in Blockchain Technologies* (pp. 19–31). https://doi.org/10.1007/978-3-030-70501-5_2

[6] Pasala, S., Pavani, V., Lakshmi, G. V., & Narayana, V. L. (2020). Identification of attackers using blockchain transactions using cryptography methods. *Journal of Critical Reviews*, 7(6), 368–375. https://doi.org/10.31838/jcr.07.06.65

[7] Mounika, B., Anusha, P., Narayana, V. L., & Lakshmi, G. V. (2020). Use of blockchain technology in providing security during data sharing. *Journal of Critical Reviews*, 7(6), 338–343. https://doi.org/10.31838/jcr.07.06.59

[8] Prathipati, Silpa Chaitanya, and Susanta Kumar Satpathy. "Transforming 3D Brain Tumour Image Segmentation: An Enhanced V-Net Approach for Precise Diagnosis and Treatment Planning." *2024 International Conference on Advances in Computing, Communication and Applied Informatics (ACCAI)*. IEEE, 2024.

[9] Chaitanya, Kosaraju, and Sankara Narayanan. "Security and Privacy in Wireless Sensor Networks Using Intrusion Detection Models to Detect DDOS and Drdos Attacks: A Survey." 2023 IEEE International Students' Conference on Electrical, Electronics and Computer Science (SCEECS). IEEE, 2023.

[10] Narayana, V. L., Vinayaki, K. V., Swetha, P. A., Sri, K. D., & Chaithanya, G. (2024). Superior attribute weighted set for object skeleton detection using ResNet50 with edge-based segmentation model. In *Proceedings of the International Conference on Smart Computing and Systems* (pp. 1132–1139). IEEE. https://doi.org/10.1109/ICSCSS60660.2024.10624879

[11] Gopi, A. P., & Naik, K. J. (2022). An IoT model for fish breeding analysis with water quality data of pond using modified multilayer perceptron model. *2022 International Conference on Data Analytics for Business and Industry (ICDABI)*, 448-453. https://doi.org/10.1109/ICDABI56818.2022.10041617

[12] 10. Liu, L.; Ouyang, W.; Wang, X.; Fieguth, P.; Chen, J.; Liu, X.; Pietikäinen, M. Deep Learning for Generic Object Detection: A Survey.Int. J. Comput. Vis. 2020, 128, 261–318. [CrossRef]

[13] 11. Aggarwal, J.K.; Ryoo, M.S. Human Activity Analysis: A Review. ACM Comput. Surv. (CSUR) 2011, 43, 1–43. [CrossRef]

[14] 12. Kong,Y.; Fu, Y. Human Action Recognition and Prediction: A Survey. arXiv 2018, arXiv:1806.11230.

[15] 13. Ciaparrone, G.; Sánchez, F.L.; Tabik, S.; Troiano, L.; Tagliaferri, R.; Herrera, F. Deep Learning in Video Multi-Object Tracking: A Survey. Neurocomputing 2020, 381, 61–88. [CrossRef]

[16] 14. Smeureanu, S.; Ionescu, R.T. Real-Time Deep Learning Method for Abandoned Luggage Detection in Video. In Proceedings ofthe 26th European Signal Processing Conference (EUSIPCO), Eternal, Italy, 3–7 September 2018; pp. 1775–1779.

[17] 15. Chalapathy, R.; Chawla, S. Deep Learning for Anomaly Detection: A Survey. arXiv 2019, arXiv:1901.03407.

[18] 16. Tripathi, G.; Singh, K.; Vishwakarma, D.K. Convolutional Neural Networks for Crowd Behaviour Analysis: A Survey. Visual Comput. 2019, 35, 753–776. [CrossRef]

[19] 17. Gao, G.; Gao, J.; Liu, Q.; Wang, Q.; Wang, Y. CNN-based Density Estimation and Crowd Counting: A Survey. arXiv 2020, arXiv:2003.12783.

[20] [4] S. Mockel, F. Scherer and P. F. Schuster. (2003) “Multi-sensor obstacle detection on railway tracks.” IEEE IV2003 Intelligent Vehicles Symposium. Proceedings (Cat. No.03TH8683), pp. 42-46, doi: 10.1109/IVS.2003.1212880.

[21] [5] J. J. García et al. (2010) “Efficient Multisensory Barrier for Obstacle Detection on Railways.” IEEE Transactions on Intelligent Transportation Systems, 11 (3): 702-713, doi: 10.1109/TITS.2010.2052101.

[22] [6] Passarella, Rossi, Bambang Tutuko and Aditya PP Prasetyo. (2011) “Design concept of train obstacle detection system in Indonesia.” IJRRAS 9 (3): 453-460.

[23] [7] Ramesh S. (2011) “Detection of cracks and railway collision avoidance system.” International Journal of Electronic and Electrical Engineering 4 (3): 321-327.

[24] [8] D. Sinha and F. Feroz. (2016) “Obstacle Detection on Railway Tracks Using Vibration Sensors and Signal Filtering Using Bayesian Analysis.” IEEE Sensors Journal, 16 (3): 642-649, doi: 10.1109/JSEN.2015.2490247.

[25] [15] Athira, S. (2019) “Image Processing based Real-Time Obstacle Detection and Alert System for Trains.” 3rd International Conference on Electronics, Communication and Aerospace Technology (ICECA). IEEE.

[26] 15. He,D.; Zou, Z.; Chen, Y.; Liu, B.; Yao, X.; Shan, S. Obstacle Detection of Rail Transit Based on Deep Learning. Measurement 2021, 176, 109241. [CrossRef]

[27] 16. Ye, T.; Wang, B.; Song, P.; Li, J. Automatic Railway Traffic Object Detection System Using Feature Fusion Refine Neural Networkunder Shunting Mode. Sensors 2018, 18, 1916. [CrossRef]

[28] 17. Kapoor, R.; Goel, R.; Sharma, A. Deep Learning Based Object and Railway Track Recognition Using Train Mounted Thermal Imaging System. J. Comput. Theor. Nanosci. 2020, 17, 5062–5071. [CrossRef]
[29] 18. Yu, M.; Yang, P.; Wei, S. Railway Obstacle Detection Algorithm Using Neural Network. AIP Conf. Proc. 2018, 1967, 040017. [CrossRef]
[30] 19. Ye, T.; Zhang, X.; Zhang, Y.; Liu, J. Railway Traffic Object Detection Using Differential Feature Fusion Convolution Neural Network. IEEE Trans. Intell. Transp. Syst. 2021, 22, 1375–1387. [CrossRef]
[31] 20. Xu,Y.; Gao, C.; Yuan, L.; Tang, S.; Wei, G. Real-Time Obstacle Detection over Rails Using Deep Convolutional Neural Network. InProceedings of the 2019 IEEE Intelligent Transportation Systems Conference (ITSC), Auckland, New Zealand, 27–30 October 2019; IEEE: Piscataway, NJ, USA, 2019; pp. 1007–1012.
[32] 21. Li,J.; Zhou, F.; Ye, T.; Li, J. Real-World Railway Traffic Detection Based on Faster Better Network. IEEE Access 2018, 6, 68730–68739. [CrossRef]
[33] 22. Zhang, S.; Wang, X. Human detection and object tracking based on histograms of oriented gradients. In Proceedings of the 2013 Ninth International Conference on Natural Computation (ICNC), Shenyang, China, 23–25 July 2013; pp. 1349–1353.
[34] 23. Felzenszwalb, P.; McAllester, D.; Ramanan, D. A Discriminatively Trained, Multiscale, Deformable Part Model. In Proceedings ofthe 2008 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR2008), Anchorage, AK, USA, 23–28 June 2008; pp. 1–8.
[35] 24. Viola, P.; Jones, M. Rapid object detection using a boosted cascade of simple features. In Proceedings of the 2001 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR2001), Kauai, HI, USA, 8–14 December 2001; Volume 1, pp. 511–518. [CrossRef]
[36] 25. Zheng, H.; Bai, Y.; Tian, Y. A Multi Moving Target Recognition Algorithm Based on Remote Sensing Video. Comput. Model. Eng. Sci. 2023, 134, 585–597. [CrossRef]
[37] 26. Zhang, Y.; Leng, K.; Park, K. Adaptive Vector-Based Sample Consensus Model for Moving Target Detection in Infrared Video. Proc. IEEE Geosci. Remote Sens. Lett. 2022, 19, 7506505. [CrossRef]
[38] 21. Ren,X.; Malik, J. Learning a classification model for segmentation. In Proceedings of the 9th InternationalConference on Computer Vision, Nice, France, 13–16 October 2003; Volume 1, pp. 10–17.
[39] 22. Shi, J.; Malik, J. Normalized cuts and image segmentation. IEEE Trans. Pattern Anal. Mach. Intell. 2000, 22, 888–905.
[40] 14. Achanta, R.; Shaji, A.; Smith, K.; Lucchi, A.; Fua, P.; Susstrunck, S. SLIC superpixels compared to state-of
[41] the-art superpixel methods. IEEE Trans. Pattern Anal. Mach. Intell. 2012, 34, 2274–2282. [CrossRef] [PubMed]
[42] 23. Zhu,Y.; Luo, K.; Ma, C.; Liu, Q.; Jin, B. Superpixel segmentation based synthetic classifications with clear boundary information for a legged robot. Sensors 2018, 18, 2808. [CrossRef] [PubMed]
[43] 24. Liu, Y.; Chen, Y.; Zhang, S. Tra c sign recognition based on pyramid histogram fusion descriptor andHIK-SVM. J. Transp. Syst. Eng. Inf. Technol. 2017, 17, 220–226.
[44] 25. Fang,Z.;Duan,J.; Zheng,B.Tra csignsrecognitio
[45] 26. Liu, K.; Ying, Z.; Cui, Y. SAR image target recognition based on unsupervised K-means feature and data augmentation. J. Signal Process. 2017, 33, 452–458.
[46] 27. Zhang,X.; Fan, J.; Xu, J.; Shi, X. Image super-resolution algorithm via K-means clustering and support vector data description. J. Image Graph. 2016, 21, 135–144.
[47] 28. Ma,G.; Tian, Y.; Li, X. Application of K-means clustering algorithm in color image segmentation of grouper in seawater background. J. Comput. Appl. Softw. 2016, 33, 192–195.
[48] 18. Arbeláez, P.; Pont-Tuset, J.; Barron, J.; Marques, F.; Malik, J. Multiscale combinatorial grouping. In Proceedings of the 27th IEEE Conference on Computer Vision and Pattern Recognition, Columbus, OH, USA, 23–28 June 2014;pp. 328–335.
[49] 29. Arbeláez, P.; Maire, M.; Fowlkes, C.; Malik, J. Contour detection and hierarchical image segmentation.
[50] IEEE Trans. Pattern Anal. Mach. Intell. 2011, 33, 898–916. [CrossRef] [PubMed]
[51] 30. Pont-Tuset, J.; Arbeláez, P.; Barron, J.; Marques, F.; Malik, J. Multiscale combinatorial grouping for image segmentation and object proposal generation. IEEE Trans. Pattern Anal. Mach. Intell. 2015, 39, 128–140. [CrossRef] [PubMed]
[52] 19. LeCun, Y.; Boser, B.; Denker, J.; Henderson, D.; Howard, R.E.; Hubbard, W.; Jackel, L. Handwritten digitrecognition with a back-propagation network. In Neural Information Processing Systems; Morgan-Kaufmann:San Francisco, CA, USA, 1990; pp. 396–404.
[53] 20. Shelhamer, E.; Long, J.; Darrell, T. Fully convolutional networks for semantic segmentation. IEEE Trans.
[54] Pattern Anal. Mach. Intell. 2014, 39, 640–651. [CrossRef] [PubMed]
[55] 31. Liu, W.; Anguelov, D.; Erhan, D.; Szegedy, C.; Reed, S.; Fu, C.; Berg, A. SSD: Single shot multibox
[56] detector. In Proceedings of the 14th European Conference on Computer Vision (ECCV 2016), Amsterdam,

[57] The Netherlands, 8–16 October 2016; Volume 9905, pp. 21–37
[58] 32. Farabet, C.; Couprie, C.; Najman, L.; LeCun, Y. Learning hierarchical features for scene labeling. IEEE Trans.Pattern Anal. Mach. Intell. 2013, 35, 1915–1929. [CrossRef] [PubMed]
[59] 33. Couprie, C.; Farabet, C.; Najman, L.; LeCun, Y. Indoor semantic segmentation using depth information.arXiv, 2013; arXiv:1301.3572.
[60] 34. Gupta, S.; Girshick, R.; Arbeláez, P.; Malik, J. Learning rich features from RGB-D Images for object detectionand segmentation. In Proceedings of the 13th European Conference on Computer Vision (ECCV 2014),Zurich, Switzerland, 6–12 September 2014; Volume 8695, pp. 345–360.
[61] 35. Petrelli, A.; Pau, D.; Di Stefano, L. Analysis of compact features for RGB-D visual research. In Proceedingsof the 18th International Conference on Image Analysis & Processing, Genoa, Italy, 7–11 September 2015; Volume 9280, pp. 14–24.
[62] Sujatha, V., Yaddala, M., Kollipara, V., Shaik, K., Burri, R.K(23),"Movie reviews data classification using convolution neural networks",***AIP Conference Proceedings***. 2023, 2724, 030009
[63] Godavarthi, B., Majety, V. D., Mrudula, Y., & Nalajala, P. (2019). Fault identification in power lines using GSM and IoT technology. *Advances in Intelligent Systems and Computing, 815*, 647–655. https://doi.org/10.1007/978-3-319-91117-2_70
[64] Majety, V. D., & Murali, G. (2018). A remote epileptic patient supervising system. *Advances in Modelling and Analysis B, 61*(4), 207–210. https://doi.org/10.18280/ama_b.610402
[65] Naresh, A., TSLP, H., Ch, G., & Kumari, G. R. P. (2023, July). Early Prophecy of Low-Birth-Weight Babies Using BM Error Rate Classifier. In *2023 14th International Conference on Computing Communication and Networking Technologies (ICCCNT)* (pp. 1-6). IEEE.
[66] Kumari, G. R. P., Reddy, A. H., Lakshmi, K., Abhinaya, B., Sanjana, S., & Naresh, A. (2024, March). Time-Frame-Based Drowsiness Detection System Using CNN. In *2024 2nd International Conference on Disruptive Technologies (ICDT)* (pp. 711-716). IEEE.
[67] V. Pavani, K. Divya, V. V. Likhitha, G. S. Mounika and K. S. Harshitha, "Image Segmentation based Imperative Feature Subset Model for Detection of Vehicle Number Plate using K Nearest Neighbor Model," *2023 Third International Conference on Artificial Intelligence and Smart Energy (ICAIS)*, Coimbatore, India, 2023, pp. 704-709, doi: 10.1109/ICAIS56108.2023.10073848.
[68] V. Pavani, M. N. Swetha, Y. Prasanthi, K. Kavya and M. Pavithra, "Drowsy Driver Monitoring Using Machine Learning and Visible Actions," *2022 International Conference on Electronics and Renewable Systems (ICEARS)*, Tuticorin, India, 2022, pp. 1269-1279, doi: 10.1109/ICEARS53579.2022.9751890.
[69] Sri, Kurra Santhi, et al. "Advanced system control with traffic handling for secure communication in IoT routing protocol." *Journal Européen des Systèmes Automatisés* 54.2 (2021): 229-233.