JETIR.ORG ISSN: 2349-5162 | ESTD Year : 2014 | Monthly Issue
JOURNAL OF EMERGING TECHNOLOGIES AND INNOVATIVE RESEARCH (JETIR)
An International Scholarly Open Access, Peer-reviewed, Refereed Journal

Driver Drowsiness Detection System (Using Eye Aspect Ratio & Mouth Aspect Ratio)

[1]Sunny Mehar, [2]Vivek Pradhan, [3]Richa Shukla
[1]Research Scholar, Department of Computer Science and Engineering, Chhattisgarh Swami Vivekanand Technical University, Bhilai (C.G), India
[2]Assistant Professor, Department of Computer Science and Engineering, Chhattisgarh Swami Vivekanand Technical University, Bhilai (C.G), India

Abstract

The intelligent and sophisticated Driver Drowsiness Detection System was created to reduce traffic accidents brought on by drivers' inattention or fatigue. Using a real-time camera, the system continuously tracks the driver's facial movements and evaluates the duration and frequency of eye closure. It can identify when the driver's eyes stay closed past a predetermined threshold by using image processing to calculate the Eye Aspect Ratio (EAR). The device immediately sounds an alarm to warn the driver and avert a potential collision when it detects tiredness. This technique offers a quick, effective, and non- intrusive solution to guarantee road safety and lower driving-related human error.

For precise facial landmark detection and efficient image processing, the suggested model makes use of Python modules like OpenCV, dlib, and NumPy. It is an affordable, dependable option that is simple to install in automobiles. This device contributes significantly to safer roads and the saving of many lives by preventing sleepy driving and issuing appropriate warnings. All things considered, the Driver Drowsiness Detection System makes a substantial contribution to the advancement of road safety and contemporary intelligent car technology.

Keywords: *Driver Drowsiness Detection, Eye Aspect Ratio (EAR), Mouth Aspect Ratio (MAR), OpenCV, dlib, Python, Computer Vision, Image Processing, Fatigue Detection, Alert System.*

INTRODUCTION

In recent years, driver weariness and sleepiness have emerged as significant contributors to traffic accidents, particularly while driving long distances on highways. Numerous studies and surveys indicate that driver fatigue or inattention is a major contributing factor in a significant portion of auto accidents. Fatigue causes a driver to become less attentive and react more slowly, which might result in risky delays in making decisions. Such events frequently result in fatalities, underscoring the critical need for efficient driver monitoring and alert systems.

Modern computer vision techniques can be utilized to automatically identify tiredness as a solution to this problem. The degree of weariness can be predicted by examining the driver's facial behavior, including eye closure duration, blinking frequency, and yawning. These changes in face features are observed by the Driver Drowsiness Detection System using real-time video input from a camera. The device instantly sounds an alarm to warn the motorist if it notices that the driver is yawning

frequently or has their eyes closed for extended periods of time.

A key component of this method is the idea of Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR). While MAR aids in the detection of yawning, EAR is used to gauge the degree of eye opening. Algorithms for detecting face landmarks are used to determine both of these characteristics. The algorithm determines that the driver is probably sleepy or exhausted when EAR drops below a predetermined level or MAR rises above a predetermined value. This technique offers an effective, non-intrusive, and economical way to improve road safety and prevent collisions.

Python and robust libraries like OpenCV, dlib, and NumPy are used in the system's development. These tools make it possible to track the driver's facial emotions in real time using quick and precise image processing. This technology is appropriate for practical uses in automobiles due to its straightforward hardware and precise software. In order to improve accuracy and adaptability to various lighting conditions, camera angles, and driver postures, future versions may incorporate sophisticated machine learning algorithms.

For more intelligent reactions, such automated braking, seat vibration alerts, or message notifications to emergency contacts in the event of persistent drowsiness, this system can also be connected with IoT-based car systems. By putting such hybrid models into practice, safety standards will be further raised and human error-related traffic accidents may be decreased.

Furthermore, sleepiness detection technologies can be a vital transition technology in the expanding field of autonomous and semi-autonomous cars. They guarantee that the system can assess alertness and take necessary remedial action even when drivers are only partially in charge. Therefore, this research advances both the future of intelligent transportation systems and road safety.

The project's ultimate objective is to reduce human error brought on by weariness in order to improve transportation safety and dependability. The Driver Drowsiness Detection System reduces accidents, saves lives, and advances the goal of intelligent and safe mobility for all road users by offering real-time monitoring and timely notifications.

LITERATURE REVIEW

Over the past ten years, a significant area of research has been the development of intelligent driver aid and sleepiness detection systems. Researchers have suggested a number of techniques to track drivers' alertness levels in light of the rising incidence of traffic accidents brought on by fatigue and inattention. The current research in the fields of eye-blink detection, yawning detection, facial feature extraction, and alarm mechanism design is highlighted in this study.

1.1. Eye-Blink Detection Methods:-

One of the most reliable measures of driver weariness is eye-blink tracking. The PERCLOS method, which gauges the percentage of eye closure to identify drowsiness, was developed by Bergasa et al. [2]. An eyelid-movement model was also created by Ji et al.[5] to detect weariness. Jo et al. [6] used infrared imaging to detect eye closure in low light. While Murtaza et al. [13] increased accuracy by integrating EAR values with head posture estimation, Kaur and Kaur [7] employed visual features for blink analysis. Despite their effectiveness, these techniques frequently call for additional gear or steady lighting.

1.2. Facial Landmark Detection and EAR:-

dlib-based facial landmark detection has gained popularity for real-time monitoring. A quick 68-point landmark model that is still in use today was introduced by Kazemi and Sullivan [8]. In order to detect prolonged eye closure, Soukupová and Čech [19] devised the Eye Aspect Ratio (EAR), which assesses the vertical and horizontal eye distances. EAR is a straightforward and effective diagnostictechnique because it dramatically drops with tiredness. Bradski's OpenCV tools [3] facilitate the low-cost implementation of face detection and EAR computation.

1.3. Mouth Aspect Ratio (MAR) and Yawning Detection:-

Another telltale indicator of drowsiness is yawning. Park et al. [14] developed the MAR formula to gauge mouth openness, while Abtahi et al. [1] employed lip movement analysis to identify yawning. In order to recognize yawns, Vicente et al. [20] also examined facial expressions. Because MAR can identify both eye closure and mouth-based fatigue symptoms, it increases system accuracy when

paired with EAR.

1.4. Image Processing and Machine Learning Techniques:-

Driver state classification has made extensive use of machine learning techniques. Mehta and Jain [12] used machine learning methods to predict weariness, while Gupta and Verma [4] suggested a hybrid model including physiological and visual signals. Even better outcomes are produced by deep learning models: Patel and Joshi [15] and Singh and Tiwari [18] employed CNN architectures for real-time alertness monitoring, while Zhang et al. [22] created a CNN-based drowsiness detector. Kim and Lee's [9] and Sharma and Gupta's [17] AI-powered smart systems demonstrate how contemporary cars can incorporate intelligent tiredness monitoring.

1.5. Detection Systems' Alert Mechanisms:-

The system must notify the driver right away if it detects tiredness. A hybrid alarm that uses both vibration and sound to shorten reaction times was introduced by Lee et al. [11]. Sharma and Gupta's [17] discussion of IoT-supported alerts facilitates the transmission of warnings via linked car systems. These warning systems are crucial in reducing collisions brought on by slow driver reactions.

1.6. A Comparative Study of Current Methods:-

Although sensor-based techniques, like the study by Sahayadhas et al. [16] and the EEG analysis by Lal and Craig [10], offer great accuracy, they are frequently costly and invasive. Although they are more comfortable, vision-based systems like those created by Bergasa et al. [2], Jo et al. [6], and Soukupová & Čech [19] can be impacted by lighting and driver position. Although deep-learning techniques [15], [18], and [22] provide great accuracy, they may not be the best option for inexpensive cars and call for powerful hardware.

1.7. Motivation and Research Gap:-

Many current systems rely on complex computational models or expensive sensors. There are still few affordable, lightweight, and real-time options. Using OpenCV [3] and dlib face landmarks [8], EAR- and MAR-based techniques offer a quick, effective, and useful way to identify tiredness without the need for invasive equipment. This serves as the driving force behind the suggested system.

CHALLENGES AND LIMITATIONS

Despite being quite successful in theory, the Driver Drowsiness Detection System has a number of difficulties when used in actual driving situations. Lighting conditions are one of the main problems. Appropriate lighting has a major impact on the system's functioning. The camera may not be able to clearly capture face features when driving at night or in poor light, which could result in erroneous detection findings. Infrared cameras can get around this restriction, but they greatly raise the system's overall cost and complexity. The position and angle of the camera present another restriction. The camera needs to be positioned appropriately and in line with the driver's face in order to produce reliable data. False detections may result from alignment disruption caused by vibrations from uneven roadways or inadequate mounting. The accuracy of Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR) computations can also be impacted by face obstructions like masks, sunglasses, or spectacles that obscure important landmarks like the mouth or eyes.

The accuracy of the system as a whole is greatly impacted by individual differences. Every driver has unique yawning patterns, blinking frequency, and facial features. Therefore, it may not be appropriate for all people to use a fixed threshold value for metrics like the Eye Aspect Ratio (EAR) or Mouth Aspect Ratio (MAR), which could result in false alarms or missing fatigue detections. Additionally, in order to handle continuous video frames in real time, the system needs to have a high computing efficiency. These complex calculations may result in processing delays when performed on low-performance hardware, which would lower the alarm mechanism's responsiveness and dependability.

The performance of the system is also significantly impacted by environmental disruptions. The reliability of the fatigue recognition process can be decreased by variations in illumination intensity, reflections from nearby surfaces, and external vibrations that interfere with facial landmark detection. Furthermore, the quantity, diversity, and quality of the training dataset have a significant impact on accuracy in machine learning-based systems. The model may perform inconsistently under various driving or environmental conditions due to poor generalization caused by a small or biased dataset. Despite these difficulties, the Driver Drowsiness Detection System is still a realistic,

economical, and effective way to reduce driver fatigue-related accidents. It is anticipated that ongoing developments in calibrating methods, adaptive algorithms, and hardware performance will further lessen current constraints. These advancements will improve the system's scalability, resilience, and dependability, making it more appropriate for mass acceptance and real-world deployment.

BENEFITS

Numerous advantages offered by the Driver Drowsiness Detection System (DDDS) directly improve road safety and lower the likelihood of accidents brought on by fatigued drivers. This system's capacity to continuously monitor the driver's facial features and identify early indicators of tiredness in real time is one of its main advantages. The system detects eye closure, yawning, and decreased facial activity using methods such the Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR), enabling it to notify the driver prior to a total loss of focus. By allowing the motorist enough time to respond, this early identification can greatly reduce the risk of collisions and save lives.

This technology's pleasant and non-intrusive operation is another significant advantage. In contrast to wearing sensors or electrodes, which may cause pain for the driver, this device analyzes face landmarks using a normal camera. In situations when comfort and convenience are crucial, such as long drives and business transportation, it provides a frictionless solution.

Because the system mostly relies on open-source software like OpenCV, dlib, and Python libraries, it is also very economical and effective. It can be readily installed in both new and old cars because it simply needs a computer and a common webcam. It is the perfect answer for poor nations where accessibility and affordability are crucial because to its straightforward setup and low computational requirement.

Furthermore, the DDDS reduces human error, which is a major contributor to traffic accidents globally. It functions as an intelligent assistance to the driver rather than a substitute, enhancing driving awareness and encouraging safe driving practices by promptly sending out visual or audio alerts when drowsiness is detected.

To improve overall road safety, the system can also be combined with cutting-edge car technology like adaptive cruise control, automated braking, and lane- departure warning.

All things considered, the Driver Drowsiness Detection System is a useful advancement in intelligent transportation systems. In addition to improving driver and passenger safety, it also helps prevent traffic accidents, save lives, and promote the future development of safe and intelligent automobiles.

PROBLEM STATEMENT

One of the biggest problems in contemporary transportation is road accidents brought on by sleepy and fatigued drivers. Reduced focus, slowed reaction times, and occasionally total loss of control are frequently caused by long driving hours, boring routes, and inadequate sleep. Global traffic safety reports state that a significant portion of traffic accidents result from drivers dozing off or losing focus due to fatigue. This puts pedestrians and passengers at serious risk in addition to putting the driver's life at jeopardy. Currently, the majority of cars rely on drivers' manual awareness and self-control to prevent these kinds of accidents. But human alertness varies, and weariness can strike without warning. Conventional safety devices like airbags and seat belts only reduce damage after an accident has happened; they don't stop sleep-related crashes. A real-time monitoring system that can continuously track the driver's condition and notify them before a catastrophic situation arises is therefore desperately needed.

The lack of an effective, affordable, and real-time technology to precisely identify driver drowsiness and promptly notify the driver is the primary issue this study attempts to address. The objective is to create a system that tracks the driver's eye and mouth movements using image processing and facial landmark detection. The system should sound an alert to alert the driver as soon as it detects indicators of drowsiness, such as extended eye closing or yawning. This approach seeks to improve vehicle safety, lower the number of traffic accidents, and encourage cautious driving.

OBJECTIVES OF THE STUDY

This study's main goal is to create, develop, and assess an intelligent real-time system that can use facial landmark analysis to identify driver drowsiness. By continuously

observing the driver's facial expressions and warning them when they exhibit signs of fatigue or inattention, the technology aims to increase road safety. The particular goals are:

1.8. Create a Drowsiness Detection System in Real Time:

Create a reliable pipeline that uses a live video feed to continuously monitor the driver's mouth and eyes in order to detect exhaustion or sleepiness accurately and quickly. Apply the Mouth Aspect Ratio (MAR) and Eye Aspect Ratio (EAR):

Use MAR to record yawning and mouth-opening behavior and EAR to record ocular closure and blink dynamics. To successfully differentiate between normal behavior and drowsy occurrences among various drivers, establish adaptive thresholds (or customizable baselines) and temporal windows.

1.9. Send Out Alerts in Real Time:

Incorporate a visual and/or aural alarm system that activates instantly when sleepiness indications surpass certain thresholds to help avert such mishaps.

1.10. To Create an Economical and Non-Intrusive Model:

Create the system employing open-source Python libraries like OpenCV, dlib, and NumPy to make it practical, lightweight, and reasonably priced for usage in all kinds of cars without bothering the driver.

1.11. To Improve Traffic Safety and Lower Accident Rates:

By offering an automated safety solution that encourages responsible and attentive driving behavior, you may help reduce the number of fatigue-related traffic incidents.

WORKING PRINCIPLE

In order to track a driver's level of alertness, the Driver Drowsiness Detection System integrates computer vision, real-time picture processing, and facial landmark analysis. The technology takes a picture of the driver's face using a camera, then utilizes algorithms to identify early indicators of exhaustion, such yawning or extended eye closure. The following essential elements and procedures comprise the system's working principle: Real-Time Video Capture and Face Detection:

Using an in-car camera or webcam, the system continually records video frames of the driver's face. The OpenCV library is used to process the collected frames. The face region in every frame is found using dlib's face detector. This guarantees that even in different lighting conditions or head orientations, the system can reliably focus on the driver's facial region.

1.12. Facial Landmark Detection:

Using dlib's pre-trained shape predictor model, the system recognizes 68 facial landmarks, which are certain locations around the eyes, mouth, and nose. These landmarks aid in precisely measuring geometric connections that are essential for estimating weariness, such as the separation between the mouth opening and the eyelids.

1.13. Calculating the Eye Aspect Ratio (EAR):

The distances between vertical and horizontal eye landmarks are used to calculate the Eye Aspect Ratio (EAR). The EAR value is comparatively high while the eyes are open. The EAR drops when the eyes start to close. The system perceives drowsiness if the EAR consistently falls below a threshold (such as 0.25).

$$EAR = \frac{(|p2 - p6| + |p3 - p5|)}{(2 * |p1 - p4|)}$$

Accurate eye closure detection at low processing cost is made possible by this straightforward and effective mathematical paradigm.

1.14. Calculating the Mouth Aspect Ratio (MAR):

In a similar vein, the Mouth Aspect Ratio (MAR) gauges the extent of mouth opening. A driver's MAR value rises when they yawn because their upper and lower lips are farther apart vertically. The technology detects yawning behavior when the MAR surpasses a certain threshold for a predetermined amount of time.

$$MAR = (|p3 - p9| + |p4 - p8| + |p5 - p7|)\ (3 * |p1 - p11|)$$

because eye and mouth dimensions differ from person to person. This improves accuracy for various users and lowers false alerts. his metric uses mouth movement analysis and yawning frequency to help the system identify early indicators of exhaustion.

1.15. Decision-Making and Drowsiness Detection:

For decision-making, the system integrates the outcomes of both EAR and MAR: Eyes closed (possible drowsiness) if EAR < threshold. Yawning is noticed if MAR > threshold.

The system verifies drowsiness if either lasts for a few seconds. Python is used to develop this logic in order to continuously assess the driver's condition and avoid false alerts caused by casual facial movements or regular blinking.

1.16. Alert Mechanism:

Using Python modules like pygame, the system triggers an alert mechanism, such as a buzzer, alarm sound, or voice message, when drowsiness is detected. The signal helps avert possible collisions by promptly alerting the motorist to refocus or take a break.

1.17. Continuous Monitoring and Adaptability:

Real-time monitoring is done continuously. The technology adjusts to different camera angles and lighting conditions. Future iterations may incorporate IoT-based alerts or machine learning models (e.g., seat vibration, automatic braking, or sending notifications to emergency contacts). This guarantees dependable and constant driver monitoring during the trip.

1.18. Threshold adjustment and system calibration:

In order to modify EAR and MAR thresholds in accordance with the driver's typical facial expressions, the system has a calibration phase. Dynamic thresholds are established after examining the driver's
typical blinking and mouth movement patterns

Flow Chart




Fig 1: Drowsiness Detection System Flowchart

Description	Values
Image dimensions	500*400 Pixels
Total number of frames	0 - 255
Number of Frames considered for analyzing Alert	48
Threshold values of EAR & MAR	EAR = 0.25 MAR = 0.75
Driver is not drowsy	EAR ≥ 0.25 & MAR < 0.75
Driver is drowsy and drowsiness alert	EAR < 0.25 & MAR > 0.75

Yawn count initially	Yawn count = 0
Yawn count after driver yawning	Yawn count > 0

Table 1: EAR–MAR Threshold Parameters and Driver State Conditions

Flowchart Explanation

The flowchart shows the operational workflow of the suggested real-time driver monitoring system and shows how the complete detection pipeline operates sequentially. In order to enable face landmark identification and image processing, all necessary libraries, such as OpenCV, dlib, and NumPy, are loaded at the initialization stage. The camera is then turned on by the system to begin continuous frame acquisition at a predetermined frame rate.

The system uses a pre-trained frontal face detector to detect faces in each video frame. Following the identification of the face region, the algorithm extracts a set of 68 facial landmark points that are used to calculate the Mouth Aspect Ratio (MAR) and the Eye Aspect Ratio (EAR). Even in situations with different lighting or partial occlusions, these landmark points guarantee precise localization of the lips and eyes.

The EAR is calculated using the ratio of vertical to horizontal eye landmark distances in order to assess drowsiness. In contrast to a typical blink, a persistently low EAR value suggests that the driver's eyes are closed for a prolonged period of time. The system determines that the driver is showing signs of tiredness if the EAR stays below a predetermined threshold (EAR < 0.25) for n consecutive frames. In these situations, the alarm/buzzer is immediately triggered to get the driver's attention again, and a "DROWSINESS ALERT on the frame" is shown.

In order to identify early indicators of driver weariness, the system simultaneously examines eye and mouth activity utilizing EAR and MAR readings. A "YAWNING ALERT" is triggered on the frame when a high MAR value (MAR > 0.75) shows mouth opening related to yawning, whereas a "DROWSINESS ALERT" and an alert are triggered when a low EAR value over successive frames indicates prolonged eye closure. The technology can identify yawning and tiredness separately or jointly because both measurements are assessed in real time. Every frame is monitored until the user hits the "q" key, at which point the webcam is released and the system shuts off. By minimizing inattention-related accidents, our dual-analysis method improves driver safety by ensuring accurate and effective fatigue identification.

CONCLUSIONS AND FUTURE SCOPE

By examining facial characteristics like the Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR), the Driver Drowsiness Detection System offers a practical and non-intrusive way to spot early indicators of driver weariness. The device can identify tiredness in real time and send out an alert to get the driver's attention back by continuously tracking eye closure and yawning habits. This strategy improves overall traffic safety and dramatically lowers the likelihood of fatigue-related collisions. The system is appropriate for both private and commercial cars because to its affordability, dependability, and simplicity.

Advanced deep learning models that adjust to different facial structures, lighting, and camera angles can be used to improve the system in the future. Incorporating night-vision or infrared cameras can enhance performance in low-light situations, and extra features like physiological indicators and head-pose estimates can strengthen detection. Additionally, the device can be connected to intelligent car features like lane- keeping assistance or automated braking for safety automation. Additionally, fleet administration, trip analytics, and remote monitoring can be made possible by cloud or mobile-based connectivity, turning the system into a complete driver monitoring platform for next smart and autonomous cars. Additional ways to improve driver engagement include voice alerts and adaptive feedback systems. Future iterations might also facilitate cross-platform deployment, allowing for smooth operation in vehicles such as cars, trucks, and public transportation.

REFERENCES

[1] Abtahi, S., Omidyeganeh, M., Shirmohammadi, S., & Hariri, B. (2014). *Driver drowsiness monitoring based on yawning detection*. IEEE International Conference on Intelligent Transportation Systems.

[2] Bergasa, L. M., Nuevo, J., Sotelo, M. A., Barea, R., & Lopez, M. E. (2012). Real-time system for monitoring driver vigilance. *IEEE Transactions on Intelligent Transportation Systems*.

[3] Bradski, G. (2000). The OpenCV library. *Dr. Dobb's Journal of Software Tools*.

[4] Gupta, N., & Verma, R. (2019). A hybrid approach for driver drowsiness detection using facial and physiological

cues. *Procedia Computer Science*.

[5] Ji, Q., Zhu, Z., & Lan, P. (2010). Real-time non-intrusive monitoring and prediction of driver fatigue. *IEEE Transactions on Vehicular Technology*.

[6] Jo, S., Lee, D., & Jung, K. (2011). Vision-based driver drowsiness detection using infrared cameras. *Applied Optics, 50*(12), 2121–2130.

[7] Kaur, P., & Kaur, K. (2017). Driver drowsiness detection system based on visual features. *International Journal of Computer Applications*.

[8] Kazemi, V., & Sullivan, J. (2014). One millisecond face alignment with an ensemble of regression trees. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.

[9] Kim, J., & Lee, Y. (2024). AI-powered fatigue monitoring for intelligent vehicles. *Journal of Artificial Intelligence Research*.

[10] Lal, S. K. L., & Craig, A. (2011). Driver fatigue: Electroencephalography and psychological assessment. *Accident Analysis & Prevention*.

[11] Lee, B., Kuo, C., & Liao, C. (2020). A hybrid drowsiness detection and alert system for drivers. *Sensors, 20*(4), 1231.

[12] Mehta, A., & Jain, A. (2020). Drowsiness detection using machine learning techniques. *International Journal of Engineering Research & Technology (IJERT)*.

[13] Murtaza, M., Ali, M., & Khan, A. (2018). Real-time driver fatigue detection based on eye aspect ratio and head pose. *IEEE Access*.

[14] Park, S., Pan, R., Pavlidis, I., & Levine, J. (2018). Yawning detection using mouth geometry. *IEEE Transactions on Affective Computing*.

[15] Patel, D., & Joshi, H. (2021). Driver fatigue detection using CNN-based facial landmark recognition. *International Journal of Image Processing and Vision Science*. Sahayadhas, A., Sundaraj, K., & Murugappan, M. (2015). Detecting driver drowsiness based on sensors: A review. *Sensors Journal*.